

No. 1907/2006 (REACH)
Printed 05.08.2019

revision 17.07.2019 (GB) Version 1.4

**Urethane Hardener 80** 

# ! SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product Urethane Hardener 80 Code-Nr. 105104

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended intended purpose(s)

2-K Urethan - Hardener

1.3. Details of the supplier of the safety data sheet

**Distributor** WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster

Phone: +49(0)251 / 9322 - 0, Fax: +49(0)251 / 9322 - 244

E-Mail: msds@weicon.de Internet: www.weicon.de

Advice Produktsicherheit / Product-Safety-Department

Phone : +49(0)251 / 9322 - 0 Fax : +49(0)251 / 9322 - 244 E-mail (competent person):

msds@weicon.de

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:

++44 1865 407333 (English)

TRANSPORT EMERGENCY CONTACT - UK, UAE, South

Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):

Tel: ++49 69 222 25285 (Deutsch, Englisch)

# **SECTION 2: Hazards identification**

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard

Hazard Statements Classification procedure

categories

Aquatic Chronic 1 H410

**Hazard Statements** 

H410 Very toxic to aquatic life with long lasting effects.

2.2. Label elements



No. 1907/2006 (REACH) Printed 05.08.2019

revision 17.07.2019 (GB) Version 1.4

**Urethane Hardener 80** 

# Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS09

## Signal word

Warning

### **Hazard Statements**

H410 Very toxic to aquatic life with long lasting effects.

# **Precautionary Statements**

P102 Keep out of reach of children.

P273 Avoid release to the environment.

P391 Collect spillage.

P501 Dispose of contents/container to hazardous or special waste collection point.

# 2.3. Other hazards

# Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

# **SECTION 3: Composition/information on ingredients**

# 3.1. Substances

not applicable

### 3.2. Mixtures

#### **Description**

Preparation of different active substances

# **Hazardous ingredients**

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]		
38640-62-9	254-052-6	Bis(isopropyl)naphthalene	25 - 50	Asp. Tox. 1, H304 / Aquatic Chronic 1, H410 M=1		
106246-33-7	402-130-7	4,4'-Methylenebis(3-chloro-2,6-diethylaniline)	25 - 50	Aquatic Chronic 4, H413		
REACH						
CAS No	Name			REACH registration number		
38640-62-9	Bis(isopropyl	Bis(isopropyl)naphthalene 01-2119565150-48		01-2119565150-48		
106246-33-7	4,4'-Methyler	nebis(3-chloro-2,6-diethylaniline)		01-0000015192-78		

#### **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

#### **General information**

Remove contaminated soaked clothing immediately.

In the event of persistent symptoms receive medical treatment.



No. 1907/2006 (REACH) Printed 05.08.2019

revision 17.07.2019 (GB) Version 1.4

**Urethane Hardener 80** 

#### In case of inhalation

Remove the casualty into fresh air and keep him immobile.

In the event of symptoms refer for medical treatment.

#### In case of skin contact

In case of contact with skin wash off immediately with soap and water.

Consult a doctor if skin irritation persists.

# In case of eye contact

In case of contact with eyes rinse with plenty of water carefully. In the event of persistent symptoms seek medical treatment.

### In case of ingestion

Do not induce vomiting.

Call for a doctor immediately.

Rinse out mouth and give plenty of water to drink.

#### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No information available.

# **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

# Suitable extinguishing media

Alcohol-resistant foam

Dry fire-extinguishing substance

Carbon dioxide

Water spray jet

# Unsuitable extinguishing media

Full water jet

### 5.2. Special hazards arising from the substance or mixture

In case of fire formation of dangerous gases possible.

Ammonia

Nitrogen oxides (NOx)

Carbon monoxide (CO)

Carbon dioxide (CO2)

#### 5.3. Advice for firefighters

#### Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

# **Additional information**

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

Collect contaminated firefighting water separately, must not be discharged into the drains.

#### **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

Use breathing apparatus if exposed to vapours/dust/aerosol.



No. 1907/2006 (REACH)
Printed 05.08.2019

revision 17.07.2019 (GB) Version 1.4

**Urethane Hardener 80** 

#### 6.2. Environmental precautions

Inform pollution control authorities if product gets into the sewerage systems or open waters.

Do not discharge into the drains/surface waters/groundwater.

Do not discharge into the subsoil/soil.

#### 6.3. Methods and material for containment and cleaning up

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust). After taking up the material dispose according to regulation.

#### 6.4. Reference to other sections

Safe handling: see section 7 Disposal: see section 13

Personal protection equipment: see section 8

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

#### Advice on safe handling

Avoid formation of aerosols.

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

#### **General protective measures**

Do not inhale vapours.

Avoid contact with eyes and skin

#### Hygiene measures

At work do not eat, drink and smoke.

Remove soiled or soaked clothing immediately.

Work in rooms with good ventilation.

Wash hands before breaks and after work.

### Advice on protection against fire and explosion

Pay attention to general rules of internal fire prevention.

# 7.2. Conditions for safe storage, including any incompatibilities

# Requirements for storage rooms and vessels

Keep in closed original container.

# Advice on storage compatibility

Do not store with acids or alkalies.

Do not store with oxidizing agents.

Do not store together with animal feedstuffs.

Do not store together with food.

# Further information on storage conditions

Keep container tightly closed and store at cool and aired place.

Protect from frost.

Protect from heat and direct solar radiation.

Store in a dry place.

#### 7.3. Specific end use(s)

# Recommendation(s) for intended use

See section 1.2



Remark

No. 1907/2006 (REACH)
Printed 05.08.2019

revision 17.07.2019 (GB) Version 1.4

**Urethane Hardener 80** 

# ! SECTION 8: Exposure controls/personal protection

Substance name

# 8.1. Control parameters DNEL-/PNEC-values

**DNEL** worker

**CAS No** 

38640-62-9	Bis(isopropyl)naphthalene	4,3 mg/kg bw/day	DNEL long-term dermal (systemic)		
		30 mg/m3	B DNEL long-term inhalative (systemic)		
PNEC					
CAS No	Substance name	Value	Code	Remark	
38640-62-9	Bis(isopropyl)naphthalene	0,15 mg/l	PNEC sewage treatment plant (ST	P)	
		0,26 μg/l	PNEC aquatic, freshwater		
		0,094 mg/kg	PNEC sediment, marine water		
		0,94 mg/kg	PNEC sediment, freshwater		
		0,026 µg/l	PNEC aquatic, marine water		

Code

Value

#### ! Additional advice

The statutory local and national regulations have to be observed.

#### 8.2. Exposure controls

### Respiratory protection

In case of insufficient ventilation or long-term effect use breathing apparatus.

Short term: filter apparatus, filter A

#### Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]:: Nitrile rubber; 0,4mm; 480min:60min

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

#### Eye protection

tightly fitting goggles

# Other protection measures

protective clothing

# Appropriate engineering controls

Sufficient ventilation and exhaustion.

# ! SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

AppearanceColourOdourliquidyellowishcharacteristic

**Odour threshold** 



No. 1907/2006 (REACH)
Printed 05.08.2019

revision 17.07.2019 (GB) Version 1.4

**Urethane Hardener 80** 

not determined Important health, safety and environmental information Value Temperature Method Remark at not determined pH value > 250 °C DIN 53171 boiling point melting point not determined > 140 °C closed cup Flash point Vapourisation rate not determined not applicable Flammable (solid) Flammability (gas) not applicable 365 °C DIN 51794 Ignition temperature Self ignition temperature The product is not self-igniting. Lower explosion limit 0,4 Vol-% 4,7 Vol-% **Upper explosion limit** Vapour pressure not determined 20 °C ISO 2811 Relative density 1 g/cm3 not determined Vapour density No or low immiscibility Solubility in water not determined Solubility/other Partition coefficient nnot determined octanol/water (log P O/W) not determined Decomposition temperature 200 mPa\*s ISO 9371 25 °C Viscosity dynamic > 21 mm2/s 40 °C Viscosity kinematic 0,7 % Solvent content **Solids content** 28,2 % **Oxidising properties** No information available. **Explosive properties** 

no



No. 1907/2006 (REACH)
Printed 05.08.2019

revision 17.07.2019 (GB) Version 1.4

**Urethane Hardener 80** 

#### 9.2. Other information

No information available.

# ! SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No information available.

#### 10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

#### 10.3. Possibility of hazardous reactions

Reactions with strong acids.

Exothermic reaction with hardener component.

Reactions with strong alkalies and oxidising agents.

Violent reactions with concentrated alkalies and oxidising agents.

#### 10.4. Conditions to avoid

Keep away from heat.

# 10.5. Incompatible materials

# Substances to avoid

Alkali (lye), concentrated

Isocyanate

Acid, concentrated

Oxidising agent, strong

# 10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Nitrous oxides (NOx)

Ammonia

#### Thermal decomposition

Remark No decomposition if used as directed.

# **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

# Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark
LD50 acute oral	> 4000 mg/kg	rat		CAS: 38640-62-9
LD50 acute dermal	> 2000 mg/kg	rat	OECD 402	CAS: 106246-33-7
LC50 acute inhalation	> 5,6 mg/l (4 h)	rat	OECD 403	CAS: 38640-62-9
Skin irritation	low irritant effect - not necessary to label			
Eye irritation	low irritant - no labeling duty			
Skin sensitization	non-sensitizing			



No. 1907/2006 (REACH)
Printed 05.08.2019

revision 17.07.2019 (GB) Version 1.4

**Urethane Hardener 80** 

#### **Subacute Toxicity - Carcinogenicity**

	Value	Species	Method	Validation
Mutagenicity				No experimental information on genotoxicity in vitro available.
Reproduction- Toxicity				No indications of toxic effects were observed in reproduction studies in animals.
Carcinogenicity				No indications of carcinogenic effects are available from long-term trials

#### **Experiences made from practice**

Frequent contact specially if dried out may cause skin and eye irritations.

#### **Additional information**

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

The product has not been tested. The information is derived from the properties of the individual components.

# **SECTION 12: Ecological information**

#### 12.1. Toxicity

#### **Ecotoxicological effects**

•	Value	Species	Method	Validation
Fish	LC50 > 1 mg/l (96 h)	guppy	OECD 203	CAS: 106246-33-7
Daphnia	EC 50 > 0,1 mg/l (48 h)	Daphnia magna	OECD 202	CAS: 106246-33-7
Algae	EC0 0,15 mg/l (72 h)	Green algae	OECD 201	CAS: 38640-62-9
Bacteria	EC0 > 10 mg/l (3 h)	activated sludge	OECD 209	CAS: 106246-33-7

# 12.2. Persistence and degradability

No information available.

### 12.3. Bioaccumulative potential

The product has not been tested. Because of the product's consistency and low solubility in water bioavailability is not likely.

#### 12.4. Mobility in soil

No information available.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

# 12.6. Other adverse effects

#### **General regulation**

Very toxic to aquatic life with long lasting effects.

Even in the event of low quantities penetration into the underground drinking water is contaminated.

Toxic to fishes.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into the ground water or aquatic environment.



No. 1907/2006 (REACH) Printed 05.08.2019

revision 17.07.2019 (GB) Version 1.4

**Urethane Hardener 80** 

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

#### Recommendations for the product

Remove in accordance with local official regulations.

Dispose of as hazardous waste.

#### Recommendations for packaging

Dispose of according to the local waste regulations.

### **General information**

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

# **SECTION 14: Transport information**

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	3082	3082	3082
14.2. UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N. O.S. (Bis(isopropyl) naphthalene)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bis(isopropyl)naphthalene)	Environmentally hazardous substance, liquid, n.o.s. (Bis(isopropyl)naphthalene)
14.3. Transport hazard class(es)	9	9	9
14.4. Packing group	III	III	III
14.5. Environmental hazards	Yes	Yes	Yes

#### 14.6. Special precautions for user

No information available.

# 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

#### Land and inland navigation transport ADR/RID

Hazard label(s) 9

tunnel restriction code E

Classification code M6

#### **Marine transport IMDG**

MARINE POLLUTANT

# ! SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**VOC** standard

 $\begin{array}{lll} \textbf{VOC content} & 0.6 \ \% \\ \textbf{VOC value} & 6 \ \text{g/L} \end{array}$ 

# 15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.



No. 1907/2006 (REACH) Printed 05.08.2019

revision 17.07.2019 (GB) Version 1.4

**Urethane Hardener 80** 

# ! SECTION 16: Other information

# ! Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed. For industrial use only.

#### **Further information**

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EUdirectives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 1.3

H304 May be fatal if swallowed and enters airways.
 H410 Very toxic to aquatic life with long lasting effects.
 H413 May cause long lasting harmful effects to aquatic life.