

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

**Name of product** WEICON UW Resin  
Code-Nr. 104401

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Recommended intended purpose(s)**

2-Component Epoxy Resin - Resin Component

**1.3. Details of the supplier of the safety data sheet****Distributor**

WEICON GmbH & Co. KG  
Königsberger Str. 255, DE-48157 Münster  
Phone : +49(0)251 / 9322 - 0, Fax : +49(0)251 / 9322 - 244  
E-Mail : msds@weicon.de  
Internet : www.weicon.de

**Advice**

Produktsicherheit / Product-Safety-Department  
Phone : +49(0)251 / 9322 - 0  
Fax : +49(0)251 / 9322 - 244  
E-mail (competent person):  
msds@weicon.de

**1.4. Emergency telephone number**

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:  
++44 1865 407333 (English)  
TRANSPORT EMERGENCY CONTACT - UK, UAE, South  
Africa (24h): Tel: ++44 1865 407333 (English)

**Manufacturer**

WEICON GmbH & Co. KG  
Königsberger Str. 255, DE-48157 Münster

**1.4. Emergency telephone number**

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):  
Tel: ++49 69 222 25285 (Deutsch, Englisch)

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]**

Hazard classes and Hazard categories	Hazard Statements	Classification procedure
--------------------------------------	-------------------	--------------------------

Acute Tox. 4	H302	
Acute Tox. 4	H312	
Skin Irrit. 2	H315	
Eye Irrit. 2	H319	
Skin Sens. 1	H317	
Aquatic Chronic 2	H411	

**Hazard Statements**

H302 + H312	Harmful if swallowed or in contact with skin.
H315	Causes skin irritation.

H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

## 2.2. Label elements

### Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS07



GHS09

### Signal word

Warning

### Hazard Statements

H302 + H312	Harmful if swallowed or in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

### Precautionary Statements

P102	Keep out of reach of children.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P362	Take off contaminated clothing.
P363	Wash contaminated clothing before reuse.
P391	Collect spillage.
P501	Dispose of contents/container to hazardous or special waste collection point.

### Hazardous ingredients for labeling

1,4-bis(2,3-epoxypropoxy)butane, reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight  $\leq 700$ )

### Special rules for supplemental label elements for certain mixtures

Contains epoxy constituents. May produce an allergic reaction.

## 2.3. Other hazards

### Information pertaining to special dangers for human and environment

Harmful by inhalation and in contact with skin.

### Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**SECTION 3: Composition/ information on ingredients****3.1. Substances**

not applicable

**3.2. Mixtures****Hazardous ingredients**

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
25068-38-6	500-033-5	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	25 - 50	Eye Irrit. 2, H319 / Skin Irrit. 2, H315 / Skin Sens. 1, H317 / Aquatic Chronic 2, H411
2425-79-8	219-371-7	1,4-bis(2,3-epoxypropoxy)butane	3 < 5	Acute Tox. 4, H332 / Acute Tox. 4, H312 / Eye Irrit. 2, H319 / Skin Irrit. 2, H315 / Skin Sens. 1, H317
14807-96-6	238-877-9	talcum (Mg3H2(SiO3)4)	<= 10	

**REACH**

CAS No	Name	REACH registration number
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	01-2119456619-26
2425-79-8	1,4-bis(2,3-epoxypropoxy)butane	01-2119494060-45
14807-96-6	talcum (Mg3H2(SiO3)4)	01-2120140278-58

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

Remove contaminated soaked clothing immediately.

**In case of inhalation**

Remove the casualty into fresh air and keep him immobile.

Seek medical treatment immediately.

**In case of skin contact**

In case of contact with skin wash off with soap and water.

Consult a doctor if skin irritation persists.

**In case of eye contact**

After eye contact, rinse opened eye for 15 minutes under running water. Transfer to hospital for specialist examination.

**In case of ingestion**

Do not induce vomiting.

Refer to medical treatment.

Give water to drink in small sips.

Rinse out mouth thoroughly with water.

**4.2. Most important symptoms and effects, both acute and delayed****Physician's information / possible symptoms**

Stomache -ache

vomiting

Respiratory complaints

Allergic symptoms

Nausea

Confusion

skin irritation

**Physician's information / possible dangers**

allergic reactions



---

#### 4.3. Indication of any immediate medical attention and special treatment needed

##### Treatment (Advice to doctor)

If swallowed or in the event of vomiting, risk of entering the lungs.

---

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

##### Suitable extinguishing media

Fire-extinguishing activities according to surrounding.

#### 5.2. Special hazards arising from the substance or mixture

In case of fire formation of dangerous gases possible.

Methanol

#### 5.3. Advice for firefighters

##### Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

##### Additional information

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

Collect contaminated firefighting water separately, must not be discharged into the drains.

---

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### For non-emergency personnel

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

Use breathing apparatus if exposed to vapours/dust/aerosol.

#### 6.2. Environmental precautions

Inform pollution control authorities if product gets into the sewerage systems or open waters.

Collect contaminated water / firefighting water separately.

Do not discharge into the drains/surface waters/groundwater.

Do not discharge into the subsoil/soil.

#### 6.3. Methods and material for containment and cleaning up

Take up with absorbent material.

After taking up the material dispose according to regulation.

#### 6.4. Reference to other sections

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8

---

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

##### Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

Open and handle container with care!

**General protective measures**

Avoid contact with eyes and skin  
Do not inhale gases/vapours/aerosols.

**Hygiene measures**

At work do not eat, drink and smoke.  
Remove soiled or soaked clothing immediately.  
Wash hands before breaks and after work.

**Advice on protection against fire and explosion**

Pay attention to general rules of internal fire prevention.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep in closed original container.

**Advice on storage compatibility**

Do not store together with animal feedstuffs.  
Do not store together with food.

**Further information on storage conditions**

Store at +5 till +25 °C.  
Keep container tightly closed and store at cool and aired place.  
Protect from heat and direct solar radiation.  
Store in a dry place.

**7.3. Specific end use(s)****Recommendation(s) for intended use**

See section 1.2

**! SECTION 8: Exposure controls/personal protection****8.1. Control parameters****! Ingredients with occupational exposure limits to be monitored**

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
14807-96-6	Talc respirable dust	8 hours	1		EH40/2005

**DNEL-/PNEC-values****DNEL worker**

CAS No	Substance name	Value	Code	Remark
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	8,33 mg/kg bw/day	DNEL long-term dermal (local)	
		12,25 mg/m3	DNEL long-term inhalative (systemic)	
		8,33 mg/kg bw/day	DNEL long-term dermal (systemic)	

**PNEC**

CAS No	Substance name	Value	Code	Remark
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	0,0996 mg/kg	PNEC sediment, marine water	
		0,006 mg/l	PNEC aquatic, freshwater	
		0,0006 mg/l	PNEC aquatic, marine water	
		10 mg/l	PNEC sewage treatment plant (STP)	

**WEICON UW Resin****DNEL-/PNEC-values (continued)**

CAS No	Substance name	Value	Code	Remark
		0,996 mg/kg	PNEC sediment, freshwater	
		0,018 mg/l	PNEC aquatic, intermittent release	
		11 mg/kg	PNEC Secondary Poisoning	

**! Additional advice**

The statutory local and national regulations have to be observed.

**8.2. Exposure controls****Respiratory protection**

If ventilation insufficient, wear respiratory protection.

Short-term: filter apparatus, filter AX/P2, otherwise environment-independent breathing apparatus.

**Hand protection**

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: natural rubber, 0,6mm; 480min; 60min;

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

**Eye protection**

tightly fitting goggles

**Other protection measures**

protective clothing

**Appropriate engineering controls**

Sufficient ventilation and exhaustion.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties****Appearance**

pasty

**Colour**

green

**Odour**

perceptible

**Odour threshold**

not determined

**Important health, safety and environmental information**

	Value	Temperature	at	Method	Remark
<b>pH value</b>	not applicable				
<b>Boiling temperature / boiling range</b>	not determined				
<b>Melting point / Freezing point</b>	not determined				
<b>Flash point</b>	not applicable			closed cup	
<b>Vapourisation rate</b>	not applicable				
<b>Flammable (solid)</b>	not determined				



# Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 05.08.2019

revision 21.09.2018 (GB) Version 1.5

## WEICON UW Resin

	Value	Temperature	at	Method	Remark
<b>Flammability (gas)</b>	not determined				
<b>Ignition temperature</b>	not determined				
<b>Self ignition temperature</b>	not determined				
<b>Lower explosion limit</b>	not determined				
<b>Upper explosion limit</b>	not determined				
<b>Vapour pressure</b>	not determined				
<b>Relative density</b>	1,44				
<b>Vapour density</b>	not determined				
<b>Solubility in water</b>					insoluble
<b>Solubility/other</b>	not determined				
<b>Partition coefficient n-octanol/water (log P O/W)</b>	2,64 - 3,78				CAS: 25068-38-6
<b>Decomposition temperature</b>	not determined				
<b>Viscosity kinematic</b>	not applicable				
<b>Viscosity dynamic</b>	not applicable				

### Oxidising properties

No information available.

### Explosive properties

No information available.

### 9.2. Other information

No information available.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No information available.

### 10.2. Chemical stability

No information available.

### 10.3. Possibility of hazardous reactions

No hazardous reactions known.

### 10.4. Conditions to avoid

Keep away from heat.

### 10.5. Incompatible materials

No information available.

**10.6. Hazardous decomposition products**

Gases/vapours, harmful  
methanol

**Thermal decomposition**

Remark No decomposition if used as directed.

**SECTION 11: Toxicological information****11.1. Information on toxicological effects****Acute toxicity/Irritation/Sensitization**

	Value/Validation	Species	Method	Remark
<b>LD50 acute dermal</b>	1307,8 mg/kg			ATE
<b>LC50 acute inhalation</b>	12,73 mg/l ( )			ATE
<b>Skin irritation</b>	irritant	rabbit		
<b>Eye irritation</b>	strong irritant	rabbit eye		
<b>Skin sensitization</b>	sensitizing			

**Subacute Toxicity - Carcinogenicity**

	Value	Species	Method	Validation
<b>Mutagenicity</b>				No experimental information on genotoxicity in vitro available.
<b>Reproduction-Toxicity</b>				No indications of toxic effects were observed in reproduction studies in animals.
<b>Carcinogenicity</b>				No indications of carcinogenic effects are available from long-term trials.

**Experiences made from practice**

Harmful to health by prolonged exposure.  
Sensitization through skin contact possible.  
Allergic reactions possible ( analogy-reasons ).  
Irritates respiratory tract.  
Irritates mucous membranes.  
Irritates eyes and skin.

**Additional information**

The product is to be handled with the caution usual with chemicals.  
Other hazardous properties may not be excluded.



**SECTION 12: Ecological information****12.1. Toxicity**

No information available.

**12.2. Persistence and degradability**

No information available.

**12.3. Bioaccumulative potential**

The product has not been tested. Because of the product's consistency and low solubility in water bioavailability is not likely.

**12.4. Mobility in soil**

No information available.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Other adverse effects****Additional ecological information**

	Value	Method	Remark
<b>AOX</b>			The product contains organically bound halogen in accordance with the formulation. It can contribute to the adsorbable organic halogen value in the effluent from sewage treatment plants.

**General regulation**

Toxic to aquatic life, fishes and plankton.

Toxic to aquatic life with long lasting effects.

Even in the event of low quantities penetration into the underground drinking water is contaminated.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into the ground water or aquatic environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Waste code No.**

08 04 09\*

15 01 10\*

**Name of waste**

waste adhesives and sealants containing organic solvents or other hazardous substances

packaging containing residues of or contaminated by hazardous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

**Recommendations for the product**

Remove in accordance with local official regulations.

Dispose of as hazardous waste.

**Recommendations for packaging**

Dispose of according to the local waste regulations.

**SECTION 14: Transport information**

	ADR/RID	IMDG	IATA-DGR
<b>14.1. UN number</b>	3077	3077	3077

**WEICON UW Resin**

	<b>ADR/RID</b>	<b>IMDG</b>	<b>IATA-DGR</b>
<b>14.2. UN proper shipping name</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700))	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700))	Environmentally hazardous substance, solid, n.o.s. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700))
<b>14.3. Transport hazard class(es)</b>	9	9	9
<b>14.4. Packing group</b>	III	III	III
<b>14.5. Environmental hazards</b>	Yes	Yes	Yes
<b>14.6. Special precautions for user</b>	No information available.		
<b>14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code</b>	not applicable		
<b>Land and inland navigation transport ADR/RID</b>	Hazard label(s) 9 tunnel restriction code E Classification code M7		
<b>Marine transport IMDG</b>	MARINE POLLUTANT		

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****VOC standard**

VOC content 0 %

**15.2. Chemical Safety Assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information****Recommended uses and restrictions**

National and local regulations concerning chemicals shall be observed.

For industrial use only.

**Further information**

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 05.08.2019

revision 21.09.2018 (GB) Version 1.5

**WEICON UW Resin**

---

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 1.4

- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H411 Toxic to aquatic life with long lasting effects.