



! SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product WEICON WP Resin
Code-Nr. 104901

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended intended purpose(s)

2-Component Epoxy Resin - Resin Component

1.3. Details of the supplier of the safety data sheet

Distributor

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster
Phone : +49(0)251 / 9322 - 0, Fax : +49(0)251 / 9322 - 244
E-Mail : msds@weicon.de
Internet : www.weicon.de

Advice

Produktsicherheit / Product-Safety-Department
Phone : +49(0)251 / 9322 - 0
Fax : +49(0)251 / 9322 - 244
E-mail (competent person):
msds@weicon.de

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:
++44 1865 407333 (English)
TRANSPORT EMERGENCY CONTACT - UK, UAE, South
Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):
Tel: ++49 69 222 25285 (Deutsch, Englisch)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard categories	Hazard Statements	Classification procedure
--------------------------------------	-------------------	--------------------------

Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
Aquatic Chronic 2	H411

Hazard Statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

2.2. Label elements**Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]**

GHS07



GHS09

Signal word

Warning

Hazard Statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

Precautionary Statements

P102	Keep out of reach of children.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P362	Take off contaminated clothing.
P363	Wash contaminated clothing before reuse.
P391	Collect spillage.
P501	Dispose of contents/container to hazardous or special waste collection point.

! Hazardous ingredients for labeling

1,4-bis(2,3-epoxypropoxy)butane, bisphenol f epoxy resin, reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700)

Special rules for supplemental label elements for certain mixtures

Contains epoxy constituents. May produce an allergic reaction.

2.3. Other hazards**Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/ information on ingredients**3.1. Substances**

not applicable

3.2. Mixtures**Description**

Epoxy resin compound containing mineral fillers.



Safety Data Sheet according to Regulation (EC)
No. 1907/2006 (REACH)

Printed 05.08.2019
revision 17.09.2018 (GB) Version 1.5

WEICON WP Resin

Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
25068-38-6	500-033-5	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	25 < 30	Eye Irrit. 2, H319 / Skin Irrit. 2, H315 / Skin Sens. 1, H317 / Aquatic Chronic 2, H411
2425-79-8	219-371-7	1,4-bis(2,3-epoxypropoxy)butane	1 < 5	Acute Tox. 4, H332 / Acute Tox. 4, H312 / Eye Irrit. 2, H319 / Skin Irrit. 2, H315 / Skin Sens. 1, H317
9003-36-5	500-006-8	bisphenol f epoxy resin	10 < 15	Skin Irrit. 2, H315 / Skin Sens. 1, H317 / Aquatic Chronic 2, H411

REACH

CAS No	Name	REACH registration number
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	01-2119456619-26
2425-79-8	1,4-bis(2,3-epoxypropoxy)butane	01-2119494060-45
9003-36-5	bisphenol f epoxy resin	01-2119454392-40

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

In case of inhalation

Remove the casualty into fresh air and keep him immobile.
In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off immediately with soap and water.
Consult a doctor if skin irritation persists.

In case of eye contact

After eye contact, rinse opened eye for 15 minutes under running water. Transfer to hospital for specialist examination.

In case of ingestion

Do not induce vomiting.
Call for a doctor immediately.
Rinse out mouth and give plenty of water to drink.

4.2. Most important symptoms and effects, both acute and delayed

Physician's information / possible symptoms

vomiting
Respiratory complaints
Allergic symptoms
Skin burns
Nausea
skin irritation

Physician's information / possible dangers

allergic reactions
Causes serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam

Dry fire-extinguishing substance

Carbon dioxide

Water spray jet

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire formation of dangerous gases possible.

Carbon monoxide (CO)

Carbon dioxide (CO₂)

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

Additional information

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

Collect contaminated firefighting water separately, must not be discharged into the drains.

! SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

Use breathing apparatus if exposed to vapours/dust/aerosol.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).

After taking up the material dispose according to regulation.

6.4. Reference to other sections

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Avoid formation of aerosols.

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

Open and handle container with care!

**General protective measures**

Avoid contact with eyes and skin
Do not inhale gases/vapours/aerosols.

Hygiene measures

At work do not eat, drink and smoke.
Remove soiled or soaked clothing immediately.
Wash hands before breaks and after work.

Advice on protection against fire and explosion

Pay attention to general rules of internal fire prevention.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep in closed original container.

Advice on storage compatibility

Do not store with acids or alkalis.
Do not store together with animal feedstuffs.
Do not store together with food.
Do not store together with oxidizing agents.

Further information on storage conditions

Keep container tightly closed and store at cool and aired place.
Protect from direct solar radiation.
Protect from heat/overheating.

7.3. Specific end use(s)**Recommendation(s) for intended use**

See section 1.2

! SECTION 8: Exposure controls/personal protection**8.1. Control parameters****DNEL-/PNEC-values****DNEL worker**

CAS No	Substance name	Value	Code	Remark
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	8,33 mg/kg bw/day	DNEL long-term dermal (local)	
		8,33 mg/kg bw/day	DNEL long-term dermal (systemic)	
		12,25 mg/m ³	DNEL long-term inhalative (systemic)	
9003-36-5	bisphenol f epoxy resin	104,15 mg/kg	DNEL long-term dermal (systemic)	
		0,0083 mg/cm ²	DNEL acute dermal, short-term (local)	
		29,39 mg/m ³	DNEL long-term inhalative (systemic)	

PNEC

CAS No	Substance name	Value	Code	Remark
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	0,018 mg/l	PNEC aquatic, intermittent release	
		11 mg/kg	PNEC Secondary Poisoning	



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 05.08.2019

revision 17.09.2018 (GB) Version 1.5

WEICON WP Resin**DNEL-/PNEC-values (continued)**

CAS No	Substance name	Value	Code	Remark
		0,996 mg/kg	PNEC sediment, freshwater	
		10 mg/l	PNEC sewage treatment plant (STP)	
		0,0006 mg/l	PNEC aquatic, marine water	
		0,006 mg/l	PNEC aquatic, freshwater	
		0,0996 mg/kg	PNEC sediment, marine water	
9003-36-5	bisphenol f epoxy resin	11 mg/kg	PNEC Secondary Poisoning	
		0,0006 mg/l	PNEC aquatic, marine water	
		0,294 mg/kg	PNEC sediment, freshwater	
		10 mg/l	PNEC sewage treatment plant (STP)	

! Additional advice

The statutory local and national regulations have to be observed.

8.2. Exposure controls**Respiratory protection**

If ventilation insufficient, wear respiratory protection.

Short term: filter apparatus, combination filter A-P2

! Hand protection

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: butyl rubber; 0,5 mm; 480min, Strauss Butyl special gloves.

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Eye protection

tightly fitting goggles

Other protection measures

protective clothing

Appropriate engineering controls

Sufficient ventilation and exhaustion.

! SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties****Appearance**

pasty

Colour

grey

Odour

product-specific

Odour threshold

No data available

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value	not applicable				
boiling point	not applicable				



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 05.08.2019

revision 17.09.2018 (GB) Version 1.5

WEICON WP Resin

	Value	Temperature	at	Method	Remark
Melting point / Freezing point	not determined				
Flash point	> 100 °C				
Vapourisation rate	not determined				
Flammable (solid)	not determined				
Flammability (gas)	not determined				
Ignition temperature	not determined				
Self ignition temperature					The product is not self-igniting.
Lower explosion limit	not determined				
Upper explosion limit	not determined				
Vapour pressure	not determined				
Relative density	ca. 2,5 g/cm ³	20 °C			
Vapour density	not determined				
Solubility in water					more or less insoluble
Solubility/other	not determined				
Partition coefficient n-octanol/water (log P O/W)	not determined				
Decomposition temperature	not determined				
Viscosity dynamic	> 500 Pa*s	25 °C			
Oxidising properties	No information available.				
Explosive properties	no				
9.2. Other information	No information available.				

SECTION 10: Stability and reactivity**10.1. Reactivity**

No hazardous reactions known.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

**10.3. Possibility of hazardous reactions**

Reactions with acids, alkalies and oxidising agents.

10.4. Conditions to avoid

Keep away from heat.

10.5. Incompatible materials**Substances to avoid**

Alkali (lye)

Acid

Oxidising agent

10.6. Hazardous decomposition products

Gases/vapours, toxic

Carbon monoxide and carbon dioxide.

Thermal decomposition

Remark No decomposition if used as directed.

! SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity/Irritation/Sensitization**

	Value/Validation	Species	Method	Remark
LD50 acute oral	> 5000 mg/kg	rat		CAS: 9003-36-5
LD50 acute dermal	1100 mg/kg	CAS: 2425-79-8		ATE
LC50 acute inhalation	1,5 mg/l ()	CAS: 2425-79-8	Aerosol	ATE
Skin irritation	irritant			
Eye irritation	irritant			
Skin sensitization	sensitizing			

Subacute Toxicity - Carcinogenicity

	Value	Species	Method	Validation
Subacute Toxicity				No data available
Subchronic Toxicity				No data available
Chronic Toxicity				No data available
Mutagenicity				No data available
Reproduction-Toxicity				No data available
Carcinogenicity				No data available

**Specific target organ toxicity (single exposure)**

No data available

Specific target organ toxicity (repeated exposure)

No data available

Aspiration hazard

No data available

Experiences made from practice

Sensitization through skin contact possible.

Irritates mucous membranes.

Irritates eyes and skin.

Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

The product has not been tested. The information is derived from the properties of the individual components.

! SECTION 12: Ecological information**12.1. Toxicity****Ecotoxicological effects**

	Value	Species	Method	Validation
Fish	LC50 2,54 mg/l (96 h)	Fish		CAS: 9003-36-5
Daphnia	EC50 2,55 mg/l (48 h)	Daphnia magna		CAS: 9003-36-5
Algae	EC50 9,1 mg/l (48 h)	Selenastrum capricornutum		CAS: 25068-38-6

12.2. Persistence and degradability

	Elimination rate	Method of analysis	Method	Validation
Biological degradability				not readily degradable

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects**General regulation**

Toxic to aquatic life with long lasting effects.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into the ground water or aquatic environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

**! SECTION 13: Disposal considerations****13.1. Waste treatment methods****Recommendations for the product**

Remove in accordance with local official regulations.

! Recommendations for packaging

Dispose of according to the local waste regulations.

Packaging that cannot be cleaned should be disposed of like the product.

General information

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	3082	3082	3082
14.2. UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700))	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700))	Environmentally hazardous substance, liquid, n.o.s. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700))
14.3. Transport hazard class(es)	9	9	9
14.4. Packing group	III	III	III
14.5. Environmental hazards	Yes	Yes	Yes

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

Land and inland navigation transport ADR/RID

Hazard label(s) 9

tunnel restriction code E

Classification code M6

Marine transport IMDG

MARINE POLLUTANT

! SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****VOC standard**

VOC content 2,5 %

VOC value 40 g/L



15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

! SECTION 16: Other information

! Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 1.4

H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H411	Toxic to aquatic life with long lasting effects.