

**Brushable Zinc Paint****! SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Name of product Brushable Zinc Paint
Code-Nr. 150000

1.2. Relevant identified uses of the substance or mixture and uses advised against**Recommended intended purpose(s)**

Technical Liquids

1.3. Details of the supplier of the safety data sheet**Distributor**

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster
Phone : +49(0)251 / 9322 - 0, Fax : +49(0)251 / 9322 - 244
E-Mail : msds@weicon.de
Internet : www.weicon.de

Advice

Produktsicherheit / Product-Safety-Department
Phone : +49(0)251 / 9322 - 0
Fax : +49(0)251 / 9322 - 244
E-mail (competent person):
msds@weicon.de

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:
++44 1865 407333 (English)
TRANSPORT EMERGENCY CONTACT - UK, UAE, South
Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):
Tel: ++49 69 222 25285 (Deutsch, Englisch)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]**

Hazard classes and Hazard categories	Hazard Statements	Classification procedure
--------------------------------------	-------------------	--------------------------

Flam. Liq. 3	H226	
Eye Irrit. 2	H319	
STOT SE 3	H335	
Aquatic Acute 1		
Aquatic Chronic 1	H410	

Hazard Statements

H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.

H410 Very toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS02



GHS07



GHS09

Signal word

Warning

Hazard Statements

H226 Flammable liquid and vapour.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H410 Very toxic to aquatic life with long lasting effects.

Precautionary Statements

P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P243 Take precautionary measures against static discharge.
P264 Wash hands thoroughly after handling.
P273 Avoid release to the environment.
P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 If eye irritation persists: Get medical advice/attention.
P370 + P378 In case of fire: Use dry sand to extinguish.
P391 Collect spillage.
P403 + P235 Store in a well-ventilated place. Keep cool.
P501 Dispose of contents/container to hazardous or special waste collection point.

2.3. Other hazards

Information pertaining to special dangers for human and environment

In extensive use, formation of flammable / explosive vapour-air mixture is possible.

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/ information on ingredients

3.1. Substances

not applicable

3.2. Mixtures

Description

Corrosion protection agent



Safety Data Sheet according to Regulation (EC)
No. 1907/2006 (REACH)

Printed 05.08.2019
revision 13.07.2018 (GB) Version 8.8

Brushable Zinc Paint

Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
100-41-4	202-849-4	ethylbenzene	< 10	Flam. Liq. 2, H225 / Acute Tox. 4, H332 / STOT RE 2, H373 (hearing organs) / Asp. Tox. 1, H304
7440-66-6	231-175-3	zinc powder - zinc dust (stabilized)	25 < 50	Aquatic Acute 1, H400 / Aquatic Chronic 1, H410
1314-13-2	215-222-5	zinc oxide	2,5 < 10	Aquatic Acute 1, H400 / Aquatic Chronic 1, H410
64742-95-6	265-199-0	Solvent naphtha (petroleum), light arom. (NOTA P)	10 - 20	Flam. Liq. 3, H226 / Asp. Tox. 1, H304 / STOT SE 3, H335, H336 / Aquatic Chronic 2, H411 / Skin Irrit.2, H315 / , EUH066
1305-78-8	215-138-9	calcium oxide	1 < 3	Skin Irrit. 2, H315 / Eye Dam. 1, H318 / STOT SE 3, H335
1330-20-7	215-535-7	xylene	5 < 10	Flam. Liq. 3, H226 / STOT RE 2, H373 / Asp. Tox. 1, H304 / Acute Tox. 4, H312, H332 / Skin Irrit. 2, H315 / Eye Irrit. 2, H319 / STOT SE 3, H335

REACH

CAS No	Name	REACH registration number
100-41-4	ethylbenzene	01-2119489370-35
7440-66-6	zinc powder - zinc dust (stabilized)	01-2119467174-37
1314-13-2	zinc oxide	01-2119463881-32
64742-95-6	Solvent naphtha (petroleum), light arom. (NOTA P)	01-2119455851-35
1305-78-8	calcium oxide	01-2119475325-36
1330-20-7	xylene	01-2119488216-32

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

In case of inhalation

Remove the casualty into fresh air and keep him immobile.

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off with soap and water.

Consult a doctor if skin irritation persists.

In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

In case of ingestion

Seek medical advice.

Do not induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.



SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Dry powder
Carbon dioxide
sand

Unsuitable extinguishing media

water

5.2. Special hazards arising from the substance or mixture

In case of fire formation of dangerous gases possible.

Carbon monoxide (CO)
Carbon dioxide (CO₂)

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

Additional information

Cool endangered containers with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

Collect contaminated firefighting water separately, must not be discharged into the drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Ensure adequate ventilation.
Use personal protective clothing.
Keep away sources of ignition.
Use breathing apparatus if exposed to vapours/dust/aerosol.

6.2. Environmental precautions

Inform pollution control authorities if product gets into the sewerage systems or open waters.
Do not discharge into the drains or bodies of water..
Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and material for containment and cleaning up

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).
After taking up the material dispose according to regulation.

Additional Information

Sort out leaky cans and dispose according to regulations.

6.4. Reference to other sections

Safe handling: see section 7
Disposal: see section 13
Personal protection equipment: see section 8

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Avoid formation of aerosols.

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

General protective measures

Avoid contact with eyes and skin

Do not inhale gases/vapours/aerosols.

Hygiene measures

At work do not eat, drink and smoke.

Remove soiled or soaked clothing immediately.

Wash hands before breaks and after work.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking

Do not spray on a naked flame or any incandescent material.

Vapours can form an explosive mixture with air.

Take precautionary measures against static discharges.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep only in original container.

Advice on storage compatibility

Do not store with acids or alkalis.

Do not store together with animal feedstuffs.

Do not store together with food.

Do not store together with oxidizing agents.

Further information on storage conditions

Keep container tightly closed, store at cool and aired place, open and handle carefully.

Keep container dry.

Recommended storage temperature: room temperature.

7.3. Specific end use(s)**Recommendation(s) for intended use**

See section 1.2

! SECTION 8: Exposure controls/personal protection**8.1. Control parameters****! Ingredients with occupational exposure limits to be monitored**

CAS No	Name	Code	[mg/m ³]	[ppm]	Remark
1305-78-8	Calcium oxide	8 hours	2		EH40/2005
100-41-4	Ethylbenzene	8 hours Short-term	441 552	100 125	EH40/2005
1330-20-7	Xylene, o-, m-, p- or mixed isomers	8 hours Short-term	220 441	50 100	EH40/2005

Indicative occupational exposure limit values (91/322/EEC, 2000/39/EC, 2006/15/EC or 2009/161/EU)

CAS No	Name	Code	[mg/m ³]	[ppm]	Remark
100-41-4	ethylbenzene	8 hours Short-term	442 884	100 200	skin



Safety Data Sheet according to Regulation (EC)
No. 1907/2006 (REACH)

Printed 05.08.2019
revision 13.07.2018 (GB) Version 8.8

Brushable Zinc Paint

**DNEL-/PNEC-values
DNEL worker**

CAS No	Substance name	Value	Code	Remark
100-41-4	ethylbenzene	77 mg/m ³	DNEL long-term inhalative (systemic)	
1314-13-2	zinc oxide	5 mg/m ³	DNEL long-term inhalative (systemic)	
		83 mg/kg	DNEL long-term dermal (systemic)	
1330-20-7	xylene	289 mg/m ³	DNEL acute inhalative (systemic)	
		289 mg/m ³	DNEL acute inhalative (local)	
		289 mg/m ³	DNEL acute inhalative (local)	
		180 mg/kg	DNEL long-term dermal (systemic)	
		77 mg/m ³	DNEL long-term inhalative (systemic)	
64742-95-6	Solvent naphtha (petroleum), light arom. (NOTA P)	25 mg/kg	DNEL long-term dermal (systemic)	
		150 mg/m ³	DNEL long-term inhalative (systemic)	
7440-66-6	zinc powder - zinc dust (stabilized)	83 mg/kg	DNEL long-term dermal (systemic)	
		5 mg/m ³	DNEL long-term inhalative (systemic)	

PNEC

CAS No	Substance name	Value	Code	Remark
1314-13-2	zinc oxide	0,0206 mg/l	PNEC aquatic, freshwater	
		0,0061 mg/l	PNEC aquatic, marine water	
		117,8 mg/kg	PNEC sediment, freshwater	
		56,5 mg/kg	PNEC sediment, marine water	
1330-20-7	xylene	2,31 mg/kg	PNEC sediment, freshwater	
		0,327 mg/l	PNEC aquatic, freshwater	
		12,46 mg/kg	PNEC sediment, freshwater	
		0,327 mg/l	PNEC aquatic, marine water	
		12,46 mg/kg	PNEC sediment, marine water	
64742-95-6	Solvent naphtha (petroleum), light arom. (NOTA P)	0,99 mg/kg	PNEC soil, marine water	
7440-66-6	zinc powder - zinc dust (stabilized)	0,0061 mg/l	PNEC aquatic, marine water	
		0,0206 mg/l	PNEC aquatic, freshwater	
		56,5 mg/kg	PNEC sediment, marine water	
		117,8 mg/kg	PNEC sediment, freshwater	

Additional advice

The statutory local and national regulations have to be observed.

8.2. Exposure controls

Respiratory protection

If ventilation insufficient, wear respiratory protection.

In case of insufficient ventilation or long-term effect use breathing apparatus.

Short-term: filter apparatus, filter AX/P2, otherwise environment-independent breathing apparatus.

**Brushable Zinc Paint****Hand protection**

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: NBR (Nitrile rubber) oder Butyl rubber, $\geq 0,5$ mm, ≥ 60 min

Eye protection

tightly fitting goggles

Other protection measures

protective clothing

Appropriate engineering controls

Sufficient ventilation and exhaustion.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties****Appearance**

liquid

Colour

silver-coloured

Odour

solvent-like

Odour threshold

not determined

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value	not determined				
boiling point	137 °C				
melting point	not determined				
Flash point	30 °C				
Vapourisation rate	not determined				
Flammable (solid)	not applicable				
Flammability (gas)	not applicable				
Ignition temperature	> 200 °C				estimate
Self ignition temperature					The product is not self-igniting.
Lower explosion limit	not determined				
Upper explosion limit	not determined				
Vapour pressure	not determined				
Relative density	ca. 1,84 g/cm ³				
Vapour density	not determined				

**Brushable Zinc Paint**

	Value	Temperature	at	Method	Remark
Solubility in water					insoluble
Solubility/other	not determined				
Partition coefficient n-octanol/water (log P O/W)	not determined				
Decomposition temperature	not determined				
Viscosity kinematic	> 21 mm ² /s	40 °C			
Viscosity Outflow time	60 - 80 s	20 °C		4 DIN 53211	

Oxidising properties

No information available.

Explosive properties

The product is considered non-explosive ; nevertheless explosive vapour/air mixtures can be generated .

9.2. Other information

No information available.

SECTION 10: Stability and reactivity**10.1. Reactivity**

No information available.

10.2. Chemical stability

No information available.

10.3. Possibility of hazardous reactions

Reactions with strong acids and alkalis.

Reactions with oxidising agents.

Formation of explosive gas/air mixtures.

10.4. Conditions to avoid

Keep away from heat.

Hydrogen formation in heat under influence of acids and alkalis.

10.5. Incompatible materials**Substances to avoid**

Alkali (lye)

Acid

oxidising agent

10.6. Hazardous decomposition products

Hydrogen

Toxic gases/vapours

Thermal decomposition

Remark No decomposition if used as directed.

! SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark
LD50 acute oral	> 2000 mg/kg	rat		CAS: 7440-66-6
LD50 acute dermal	1100 mg/kg	rabbit		CAS: 1330-20-7
LC50 acute inhalation	5,41 mg/l (4 h)	rat		CAS: 7440-66-6
Skin irritation	irritant			
Eye irritation	irritant			
Skin sensitization	non-sensitizing			

Subacute Toxicity - Carcinogenicity

	Value	Species	Method	Validation
Mutagenicity				No experimental information on genotoxicity in vitro available.
Reproduction-Toxicity				No indications of toxic effects were observed in reproduction studies in animals.
Carcinogenicity				No indications of carcinogenic effects are available from long-term trials.

Experiences made from practice

Often and long skin contact may cause degreasing and desiccation of the skin which may cause skin irritation.

Risk of strong eye injuries.

Irritates eyes and skin.

Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

The product has not been tested. The information is derived from the properties of the individual components.

SECTION 12: Ecological information

12.1. Toxicity

No information available.

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

The product has not been tested. Because of the product's consistency and low solubility in water bioavailability is not likely.

12.4. Mobility in soil

**Brushable Zinc Paint**

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects**General regulation**

Very toxic to aquatic life with long lasting effects.

Even in the event of low quantities penetration into the underground drinking water is contaminated.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into aquatic environment.

The ecotoxic effect of the product has not been tested. The information on this is given on the basis of details in the literature.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Waste code No.**

08 01 11*

Name of waste

waste paint and varnish containing organic solvents or other hazardous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

Recommendations for the product

Remove in accordance with local official regulations.

Dispose of as hazardous waste.

Recommendations for packaging

Dispose of according to the local waste regulations.

Packaging that cannot be cleaned should be disposed of like the product.

General information

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	1263	1263	1263
14.2. UN proper shipping name	PAINT (zinc powder - zinc dust (stabilized))	PAINT (zinc powder - zinc dust (stabilized))	Paint (zinc powder - zinc dust (stabilized))
14.3. Transport hazard class(es)	3	3	3
14.4. Packing group	III	III	III
14.5. Environmental hazards	Yes	Yes	Yes

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

**Brushable Zinc Paint****Land and inland navigation transport ADR/RID**

Hazard label(s) 3

tunnel restriction code D/E

Special provisions 640E

Classification code F1

transport in "limited quantities" according to 3.4 ADR is possible

Marine transport IMDG

MARINE POLLUTANT

Transport as limited quantities according to 3.4 IMDG Code is possible.

! SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****VOC standard**

VOC content 25,4 %

VOC value 467,4 g/L

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

! SECTION 16: Other information**! Recommended uses and restrictions**

National and local regulations concerning chemicals shall be observed.

For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.7

EUH066 Repeated exposure may cause skin dryness or cracking.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312, -?-

~~H332~~ Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H335, -?-

~~H336~~ May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.