

SIZING GUIDE

FIND THE RIGHT LINIAN CLIP FOR YOUR CABLES WITH THIS DETAILED SIZING GUIDE.

THIS DOCUMENT IS INTENDED AS A GUIDE TO ASSIST YOU WHEN CHOOSING A CLIP TO FIT YOUR CABLE. CABLE SIZES MAY VARY DEPENDING ON THE MANUFACTURER. ALWAYS CHECK THE OVERALL DIAMETER OF THE ACTUAL CABLE YOU ARE INSTALLING WITH THE CABLE MANUFACTURER.

1 Sizing Guide 2021 2 Sizing Guide 2021

Standard Fire Rated Soft Skin Cable

	Cable size		Recommended clip size	Part number
	Nominal cable cross sectional area	Cable overall diameter	DISCLAIMER: sizing may vary slightly according to manufacturer	(x) = colour i.e. B for black, R for Red, W for white and GALV for Galvanised
2 CORE				
	1mm²	8mm	6-8mm Single (x 1 cable) OR 6-8mm Double (x 2 cables)	1LC(X)608 OR 1LC(X)682
	1.5mm²	8.1mm	6-8mm Single (x 1 cable) OR 6-8mm Double (x 2 cables)	1LC(X)608 OR 1LC(X)682
	2.5mm²	9.5mm	9-11mm Single (x 1 cable) OR 9-11mm Double (x 2 cable)	1LC(X)911 OR 1LC(X)9112
	4mm²	11.6mm	9-11mm Single (x 1 cable) OR 9-11mm Double (x 2 cable)	1LC(X)911 OR 1LC(X)9112
3 CORE				
	1mm²	8.2mm	6-8mm Single (x 1 cable) OR 6-8mm Double (x 2 cables)	1LC(X)608 OR 1LC(X)682
	1.5mm²	8.4mm	6-8mm Single (x 1 cable) OR 6-8mm Double (x 2 cables)	1LC(X)608 OR 1LC(X)682
	2.5mm²	10.4mm	9-11mm Single (x 1 cable) OR 9-11mm Double (x 2 cable)	1LC(X)911 OR 1LC(X)9112
	4mm²	12.3mm	12-14mm Superclip (single cable only)	1LS(X)1214
4 CORE				
	1mm²	8.5mm	6-8mm Single (x 1 cable) OR 6-8mm Double (x 2 cables)	1LC(X)608 OR 1LC(X)682
	1.5mm²	10mm	9-11mm Single (x 1 cable) OR 9-11mm Double (x 2 cable)	1LC(X)911 OR 1LC(X)9112
	2.5mm²	11.9mm	9-11mm Double	1LC(X)9112
	4mm²	13.5mm	12-14mm Superclip (single cable only)	1LS(X)1214

Standard Fire Rated Soft Skin Cable

	Cable siz	е	Recommended clip size	Part number
	Nominal cable cross sectional area	Cable overall diameter	DISCLAIMER: sizing may vary slightly according to manufacturer	(x) = colour i.e. B for black, R for Red, W for white and GALV for Galvanised
7 CORE				
	1mm²	12.1mm	12-14mm Superclip (single cable only)	1LS(X)1214
	1.5mm²	13.3mm	12-14mm Superclip (single cable only)	1LS(X)1214
	2.5mm²	16.3mm	15-18mm Superclip (single cable only)	1LS(X)1518
12 CORE				
	1.5mm²	17.5mm	15-18mm Superclip (single cable only)	1LS(X)1518
	2.5mm²	21.7mm	20-22mm Superclip (single cable only)	1LS(X)2022
19 CORE				
	1.5mm²	20.5mm	20-22mm Superclip (single cable only)	1LS(X)2022





3 Sizing Guide 2021 4 Sizing Guide 2021

Enhanced Fire Rated Soft Skin Cable

	Cable size	е	Recommended clip size	Part number
	Nominal cable cross sectional area	Cable overall diameter	DISCLAIMER: sizing may vary slightly according to manufacturer	(x) = colour i.e. B for black, R for Red, W for white and GALV for Galvanised
2 CORE				
	1.5mm²	9.5mm	9-11mm Single (x 1 cable) OR 9-11mm Double (x 2 cable)	1LC(X)911 OR 1LC(X)9112
	2.5mm²	11.5mm	9-11mm Single (x 1 cable) OR 9-11mm Double (x 2 cable)	1LC(X)911 OR 1LC(X)9112
	4mm²	12.2mm	12-14mm Superclip (single cable only)	1LS(X)1214
3 CORE				
	1.5mm²	11.7mm	12-14mm Superclip (single cable only)	1LS(X)1214
	2.5mm²	12.7mm	12-14mm Superclip (single cable only)	1LS(X)1214
	4mm²	14mm	12-14mm Superclip (single cable only)	1LS(X)1214
4 CORE				
	1.5mm²	12.5mm	9-11mm Single (x 1 cable) OR 9-11mm Double (x 2 cable)	1LC(X)911 OR 1LC(X)9112
	2.5mm²	13.5mm	9-11mm Double	1LC(X)9112
	4mm²	14.7mm	12-14mm Superclip (single cable only)	1LS(X)1214

Fire Rated Heavy Duty SWA Power Cable

Cable siz	е	Recommended clip size	Part number		
Nominal cable cross sectional area	Cable overall diameter	DISCLAIMER: sizing may vary slightly according to manufacturer	(x) = colour i.e. B for black, R for Red, W for white and GALV for Galvanised		
2 CORE					
4mm²	21mm	20-22mm Superclip (single cable only)	1LC(X)2022		
6mm²	21mm	20-22mm Superclip (single cable only)	1LC(X)2022		
10mm²	23mm	23-25mm Superclip (single cable only)	1LS(X)2325		
16mm²	25mm	23-25mm Superclip (single cable only)	1LS(X)2325		
NB: for larger diameter cables - larger clips are under d	development				
3 CORE					
4mm²	22mm	20-22mm Superclip (single cable only)	1LC(X)2022		
6mm²	21mm	20-22mm Superclip (single cable only)	1LC(X)2022		
10mm²	25mm	23-25mm Superclip (single cable only)	1LS(X)2325		
NB: for larger diameter cables - larger clips are under c	NB: for larger diameter cables - larger clips are under development				
4 CORE					
4mm²	13.9mm	12-14mm Superclip (single cable only)	1LC(X)2022		
6mm²	15.5mm	15-18mm Superclip (single cable only)	1LS(X)2325		
NB: for larger diameter cables - larger clips are under d					
5 CORE					
4mm²	24mm	23-25mm Superclip (single cable only)	1LC(X)2325		
6mm²	24mm	23-25mm Superclip (single cable only)	1LC(X)2325		
NB: for larger diameter cables - larger clips are under d	development				





5 Sizing Guide 2021 6 Sizing Guide 2021

Fire rated SWA cable

	Cable size		Recommended clip size	Part number
	Nominal cable cross sectional area	Cable overall diameter	DISCLAIMER: sizing may vary slightly according to manufacturer	(x) = colour i.e. B for black, R for Red, W for white and GALV for Galvanised
2 CORE SWA				
	1.5mm²	13.5mm	12-14mm Superclip (single cable only)	1LS(X)1214
	2.5mm²	14.8mm	12-14mm Superclip (single cable only)	1LS(X)1214
	4mm²	15.8mm	15-18mm Superclip (Single cable only)	1LS(X)1518
	6mm²	16.6mm	15-18mm Superclip (Single cable only)	1LS(X)1518
	10mm²	19.9mm	18-20mm Superclip (Single cable only)	1LS(X)1518
	16mm²	22mm	20-22mm Superclip (Single cable only)	1LC(X)2022
	25mm²	26mm	23-25mm Superclip (single cable only)	1LS(X)2325
3 CORE				
	1.5mm²	13.9mm	12-14mm Superclip (single cable only)	1LS(X)1214
	2.5mm²	15.5mm	15-18mm Superclip (Single cable only)	1LS(X)1518
	4mm²	16.4mm	15-18mm Superclip 3(Single cable only)	1LS(X)1518
	6mm²	17.9mm	15-18mm Superclip (Single cable only)	1LS(X)1518
	10mm²	22mm	20-22mm Superclip (Single cable only)	1LC(X)2022
	16mm²	24mm	23-25mm Superclip (single cable only)	1LS(X)2325

Fire rated SWA cable

	Cable siz	е	Recommended clip size	Part number
	Nominal cable cross sectional area	Cable overall diameter	DISCLAIMER: sizing may vary slightly according to manufacturer	(x) = colour i.e. B for black, R for Red, W for white and GALV for Galvanised
4 CORE				
	1.5mm²	19.9mm	18-20mm Superclip (single cable only)	1LC(X)1820
	2.5mm²	16.9mm	12-14mm Superclip (single cable only)	1LS(X)1214
	4mm²	17.7mm	15-18mm Superclip (single cable only)	1LS(X)1518
	6mm²	21mm	20-22mm Superclip (single cable only)	1LC(X)2022
	10mm²	24mm	23-25mm Superclip (single cable only)	1LC(X)2325
	16mm²	25mm	23-25mm Superclip (single cable only)	1LC(X)2325
	25mm²	26mm	23-25mm Superclip (single cable only)	1LS(X)2325
5 CORE				
	1.5mm²	15.6mm	15-18mm Superclip (single cable only)	1LS(X)1518
	2.5mm²	17.3mm	15-18mm Superclip (single cable only)	1LS(X)1518
	4mm²	18.8mm	18-20mm Superclip (single cable only)	1LC(X)1820
	6mm²	23mm	23-25mm Superclip (single cable only)	1LC(X)2325
	10mm²	25mm	23-25mm Superclip (single cable only)	1LC(X)2325
NB: for larger diamet	ter cables - larger clips are under d	evelopment		





Sizing Guide 2021 8 Sizing Guide 2021

PVC Insulated Flex

Cable siz	e	Recommended clip size	Part number
Nominal cable cross sectional area	Cable overall diameter	DISCLAIMER: sizing may vary slightly according to manufacturer	(x) = colour i.e. B for black, R for Red, W for white and GALV for Galvanised
218Y PVC 2 CORE			
0.5mm²	5.2mm	4-6mm Single (9-11mm single 2 cables)	1LC(X)406 (1LC(X)911
0.75mm²	5.6mm	4-6mm Single (9-11mm single 2 cables)	1LC(X)406 (1LC(X)911
218Y PVC 3 CORE			
0.5mm²	5.6mm	4-6mm Single (9-11mm single 2 cables)	1LC(X)406 (1LC(X)911
0.75mm²	5.mm	4-6mm Single (9-11mm single 2 cables)	1LC(X)406 (1LC(X)911
0.75mm²	5.6mm	4-6mm Single (9-11mm single 2 cables)	1LC(X)406 (1LC(X)911
2.5mm²	17.05mm	15-18mm Superclip (single cable only)	1LS(X)1518
NB: for larger diameter cables - larger clips are under d	development		
3 CORE SWA BROWN, BLACK & GR	REY		
1.5mm²	12.17mm	12-14mm Superclip (single cable only)	1LS(X)1214
2.5mm²	13.55mm	12-14mm Superclip (single cable only)	1LS(X)1214
4mm²	14.68mm	12-14mm Superclip (single cable only)	1LS(X)1214
6mm²	15.87mm	15-18mm Superclip (single cable only)	1LS(X)1518
10mm²	18.63mm	18-20mm Superclip (single cable only)	1LC(X)1820
16mm²	20.78mm	20-22mm Superclip (single cable only)	1LC(X)2022
25mm²	24.9mm	23-25mm Superclip (single cable only)	1LS(X)2325

PVC Insulated Flex

Cable siz	е	Recommended clip size	Part number		
Nominal cable cross sectional area	Cable overall diameter	DISCLAIMER: sizing may vary slightly according to manufacturer	(x) = colour i.e. B for black, R for Red, W for white and GALV for Galvanised		
4 CORE SWA: BROWN, BLACK, GR	EY & BLUE				
1.5mm²	12.88mm	12-14mm Superclip (single cable only)	1LS(X)1214		
2.5mm²	14.43mm	12-14mm Superclip (single cable only)	1LS(X)1214		
4mm²	16.87mm	15-18mm Superclip (single cable only)	1LS(X)1518		
6mm²	17.87mm	15-18mm Superclip (single cable only)	1LS(X)1518		
10mm²	20.1mm	20-22mm Superclip (single cable only)	1LC(X)2022		
16mm²	22.4mm	20-22mm Superclip (single cable only)	1LC(X)2022		
NB: for larger diameter cables - larger clips are under d	NB: for larger diameter cables - larger clips are under development				
5 CORE SWA: WHITE NUMBERED	CORES WITH BI	LACK PRINT			
1.5mm²	13.72mm	12-14mm Superclip (single cable only)	1LS(X)1214		
2.5mm²	15.46mm	15-18mm Superclip (single cable only)	1LS(X)1518		
4mm²	17.38mm	15-18mm Superclip (single cable only)	1LS(X)1518		
6mm²	19.05mm	18-20mm Superclip (single cable only)	1LC(X)1820		
10mm²	22.06mm	20-22mm Superclip (single cable only)	1LC(X)2022		
16mm²	24.14mm	23-25mm Superclip (single cable only)	1LS(X)2325		
NB: for larger diameter cables - larger clips are under d	evelopment				





Sizing Guide 2021 10 Sizing Guide 2021

PVC Insulated Flex

Cable size	Cable size		Part number
Nominal cable cross sectional area	Cable overall diameter	DISCLAIMER: sizing may vary slightly according to manufacturer	(x) = colour i.e. B for black, R for Red, W for white and GALV for Galvanised
7 CORE SWA: WHITE NUMBERED V	VITH BLACK PI	RINT	
1.5mm²	14.65mm	15-18mm Superclip (single cable only)	1LS(X)1518
2.5mm²	16.53mm	15-18mm Superclip (single cable only)	1LS(X)1518
4mm²	18.96mm	18-20mm Superclip (single cable only)	1LC(X)1820
6mm²	21.6mm	20-22mm Superclip (single cable only)	1LC(X)2022
10mm²	25.3mm	23-25mm Superclip (single cable only)	1LS(X)2325
NB: for larger diameter cables - larger clips are under d	evelopment		
12 CORE SWA: WHITE NUMBERED	CORES WITH E	SLACK PRINT	
1.5mm²	18.9mm	18-20mm Superclip (Single cable only)	1LC(X)1820
2.5mm²	21.76mm	20-22mm Superclip (Single cable only)	1LC(X)2022
NB: for larger diameter cables - larger clips are under d	evelopment		
19 CORE SWA: WHITE NUMBERED	CORES WITH E	BLACK PRINT	
1.5mm²	21.99mm	20-22mm Superclip (single cable only)	1LC(X)2022
NB: for larger diameter cables - larger clips are under d	evelopment		
27 CORE SWA: WHITE NUMBERED	CORES WITH I	BLACK PRINT	
1.5mm²	21.99mm	20-22mm Superclip (single cable only)	1LC(X)2022
NB: for larger diameter cables - larger clips are under d			
37 CORE SWA: WHITE NUMBERED			
1.5mm²	21.99mm	20-22mm Superclip (single cable only)	1LC(X)2022
NB: for larger diameter cables - larger clips are under d	evelopment		



SWA Armoured power cable standard

Cable a	·	December de d'alim aire	Down worselver
Cable si		Recommended clip size	Part number
Nominal cable cross sectional area	Cable overall diameter	DISCLAIMER: sizing may vary slightly according to manufacturer	(x) = colour i.e. B for black, R for Red, W for white and GALV for Galvanised
2 CORE SWA : BROWN & BLUE			
1.5mm	11.06mm	9-11mm Single (x 1 cable) OR 9-11mm Double (x 2 cable)	1LC(X)911 OR 1LC(X)9112
2.5mm	12.4mm	12-14mm Superclip (single cable only)	1LS(X)1214
4mm	13.38mm	12-14mm Superclip (single cable only)	1LS(X)1214
6mm	14.38mm	12-14mm Superclip (single cable only)	1LS(X)1214
10mm	16.18mm	15-18mm Superclip (single cable only)	1LS(X)1518
16mm	19.06mm	18-20mm Superclip (single cable only)	1LC(X)1820
25mm	20mm	18-20mm Superclip (single cable only)	1LC(X)1820
35mm	23.2mm	23-25mm Superclip (single cable only)	1LS(X)2325
50mm	25.1mm	23-25mm Superclip (single cable only)	1LS(X)2325
NB: for larger diameter cables - larger clips are under	development		
3 CORE SWA BROWN, BLACK & G	REY		
1.5mm²	12.17mm	12-14mm Superclip (single cable only)	1LS(X)1214
2.5mm²	13.55mm	12-14mm Superclip (single cable only)	1LS(X)1214
4mm²	14.68mm	15-18mm Superclip (Single cable only)	1LS(X)1518
6mm²	15.87mm	15-18mm Superclip (single cable only)	1LS(X)1518
10mm²	18.63mm	18-20mm Superclip (single cable only)	1LC(X)1820
16mm²	20.78mm	20-22mm Superclip (single cable only)	1LC(X)2022
25mm²	24.9mm	23-25mm Superclip (single cable only)	1LS(X)2325
NB: for larger diameter cables - larger clips are under	development		



Sizing Guide 2021 12 Sizing Guide 2021 2021

SWA Armoured power cable standard

Cable size	е	Recommended clip size	Part number
Nominal cable cross sectional area	Cable overall diameter	DISCLAIMER: sizing may vary slightly according to manufacturer	(x) = colour i.e. B for black, R for Red, W for white and GALV for Galvanised
4 CORE SWA: BROWN, BLACK, GRI	EY & BLUE		
1.5mm²	12.88mm	12-14mm Superclip (single cable only)	1LS(X)1214
2.5mm²	14.43mm	12-14mm Superclip (single cable only)	1LS(X)1214
4mm²	16.87mm	15-18mm Superclip (single cable only)	1LS(X)1518
6mm²	17.87mm	15-18mm Superclip (single cable only)	1LS(X)1518
10mm²	20.1mm	20-22mm Superclip (single cable only)	1LC(X)2022
16mm²	22.4mm	20-22mm Superclip (single cable only)	1LC(X)2022
NB: for larger diameter cables - larger clips are under d			
5 CORE SWA: WHITE NUMBERED (CORES WITH BL	ACK PRINT	
1.5mm²	13.72mm	12-14mm Superclip (single cable only)	1LS(X)1214
2.5mm²	15.46mm	15-18mm Superclip (single cable only)	1LS(X)1518
4mm²	17.38mm	15-18mm Superclip (single cable only)	1LS(X)1518
6mm²	19.05mm	18-20mm Superclip (single cable only)	1LC(X)1820
10mm²	22.06mm	20-22mm Superclip (single cable only)	1LC(X)2022
16mm²	24.14mm	23-25mm Superclip (single cable only)	1LS(X)2325
NB: for larger diameter cables - larger clips are under d	evelopment		

SWA Armoured power cable standard

Cable siz	е	Recommended clip size	Part number		
Nominal cable cross sectional area	Cable overall diameter	DISCLAIMER: sizing may vary slightly according to manufacturer	(x) = colour i.e. B for black, R for Red, W for white and GALV for Galvanised		
7 CORE SWA: WHITE NUMBERED	WITH BLACK PI	RINT			
1.5mm²	14.65mm	15-18mm Superclip (single cable only)	1LS(X)1518		
2.5mm²	16.53mm	15-18mm Superclip (single cable only)	1LS(X)1518		
4mm²	18.96mm	18-20mm Superclip (single cable only)	1LC(X)1820		
6mm²	21.6mm	20-22mm Superclip (single cable only)	1LC(X)2022		
10mm²	25.3mm	23-25mm Superclip (single cable only)	1LS(X)2325		
NB: for larger diameter cables - larger clips are under c	levelopment				
12 CORE SWA: WHITE NUMBERED	CORES WITH B	SLACK PRINT			
1.5mm²	18.9mm	18-20mm Superclip (single cable only)	1LC(X)1820		
2.5mm²	21.76mm	20-22mm Superclip (single cable only)	1LC(X)2022		
NB: for larger diameter cables - larger clips are under c	levelopment				
19 CORE SWA: WHITE NUMBERED	CORES WITH E	BLACK PRINT			
1.5mm²	21.99mm	20-22mm Superclip (single cable only)	1LC(X)2022		
NB: for larger diameter cables - larger clips are under c	levelopment				
27 CORE SWA: WHITE NUMBERED	CORES WITH E	BLACK PRINT			
1.5mm²	21.99mm	20-22mm Superclip (single cable only)	1LC(X)2022		
NB: for larger diameter cables - larger clips are under c	NB: for larger diameter cables - larger clips are under development				
37 CORE SWA: WHITE NUMBERED	CORES WITH E	BLACK PRINT			
1.5mm²	21.99mm	20-22mm Superclip (single cable only)	1LC(X)2022		
NB: for larger diameter cables - larger clips are under d	NB: for larger diameter cables - larger clips are under development				





3 Sizing Guide 2021 14 Sizing Guide 2021

SWA Armoured power cable LS(H)F

Cable siz	е	Recommended clip size	Part number
Nominal cable cross sectional area	Cable overall diameter	DISCLAIMER: sizing may vary slightly according to manufacturer	(x) = colour i.e. B for black, R for Red, W for white and GALV for Galvanised
2 CORE SWA : BROWN & BLUE			
1.5mm²	12.3mm	12-14mm Superclip (single cable only)	1LS(X)1214
2.5mm²	12.9mm	12-14mm Superclip (single cable only)	1LS(X)1214
4mm²	13.9mm	12-14mm Superclip (single cable only)	1LS(X)1214
6mm²	15mm	15-18mm Superclip (single cable only)	1LS(X)1518
10mm²	17.05mm	15-18mm Superclip (single cable only)	1LS(X)1518
16mm²	19.5mm	18-20mm Superclip (single cable only)	1LC(X)1820
25mm²	22.1mm	23-25mm Superclip (single cable only)	1LS(X)2325
35mm²	24.95mm	23-25mm Superclip (single cable only)	1LS(X)2325
50mm²	25.4mm	23-25mm Superclip (single cable only)	1LS(X)2325
NB: for larger diameter cables - larger clips are under development			
3 CORE SWA BROWN, BLACK & GR	EY		
1.5mm²	12.17mm	12-14mm Superclip (single cable only)	1LS(X)1214
2.5mm²	13.55mm	12-14mm Superclip (single cable only)	1LS(X)1214
4mm²	14.68mm	15-18mm Superclip (Single cable only)	1LS(X)1518
6mm²	15.87mm	15-18mm Superclip (single cable only)	1LS(X)1518
10mm²	18.63mm	18-20mm Superclip (single cable only)	1LC(X)1820
16mm²	20.78mm	20-22mm Superclip (single cable only)	1LC(X)2022
25mm²	24.9mm	23-25mm Superclip (single cable only)	1LS(X)2325
NB: for larger diameter cables - larger clips are under d	evelopment		

SWA Armoured power cable LS(H)F

Cable size	e	Recommended clip size	Part number
Nominal cable cross sectional area	Cable overall diameter	DISCLAIMER: sizing may vary slightly according to manufacturer	(x) = colour i.e. B for black, R for Red, W for white and GALV for Galvanised
4 CORE SWA: BROWN, BLACK, GRI	EY & BLUE		
1.5mm²	12.88mm	12-14mm Superclip (single cable only)	1LS(X)1214
2.5mm²	14.43mm	12-14mm Superclip (single cable only)	1LS(X)1214
4mm²	16.87mm	15-18mm Superclip (single cable only)	1LS(X)1518
6mm²	17.87mm	15-18mm Superclip (single cable only)	1LS(X)1518
10mm²	20.1mm	20-22mm Superclip (single cable only)	1LC(X)2022
16mm²	22.4mm	20-22mm Superclip (single cable only)	1LC(X)2022
NB: for larger diameter cables - larger clips are under development			
5 CORE SWA: WHITE NUMBERED CORES WITH BLACK PRINT			
1.5mm²	13.72mm	12-14mm Superclip (single cable only)	1LS(X)1214
2.5mm²	15.46mm	15-18mm Superclip (single cable only)	1LS(X)1518
4mm²	17.38mm	15-18mm Superclip (single cable only)	1LS(X)1518
6mm²	19.05mm	18-20mm Superclip (single cable only)	1LC(X)1820
10mm²	22.06mm	20-22mm Superclip (single cable only)	1LC(X)2022
16mm²	24.14mm	23-25mm Superclip (single cable only)	1LS(X)2325
NB: for larger diameter cables - larger clips are under development			





SWA Armoured power cable LS(H)F

Cable size	е	Recommended clip size	Part number
Nominal cable cross sectional area	Cable overall diameter	DISCLAIMER: sizing may vary slightly according to manufacturer	(x) = colour i.e. B for black, R for Red, W for white and GALV for Galvanised
7 CORE SWA: WHITE NUMBERED V	NITH BLACK P	RINT	
1.5mm²	14.65mm	15-18mm Superclip (single cable only)	1LS(X)1518
2.5mm²	16.53mm	15-18mm Superclip (single cable only)	1LS(X)1518
4mm²	18.96mm	18-20mm Superclip (single cable only)	1LC(X)1820
6mm²	21.6mm	20-22mm Superclip (single cable only)	1LC(X)2022
10mm²	25.3mm	23-25mm Superclip (single cable only)	1LS(X)2325
NB: for larger diameter cables - larger clips are under d	evelopment		
12 CORE SWA: WHITE NUMBERED	CORES WITH E	BLACK PRINT	
1.5mm²	18.9mm	18-20mm Superclip (single cable only)	1LC(X)1820
2.5mm²	21.76mm	20-22mm Superclip (single cable only)	1LC(X)2022
NB: for larger diameter cables - larger clips are under d	evelopment		
19 CORE SWA: WHITE NUMBERED CORES WITH BLACK PRINT			
1.5mm²	21.99mm	20-22mm Superclip (Single cable only)	1LC(X)2022
NB: for larger diameter cables - larger clips are under development			
27 CORE SWA: WHITE NUMBERED	CORES WITH	BLACK PRINT	
1.5mm²	21.99mm	20-22mm Superclip (single cable only)	1LC(X)2022
NB: for larger diameter cables - larger clips are under development			
37 CORE SWA: WHITE NUMBERED			
1.5mm²	21.99mm	20-22mm Superclip (single cable only)	1LC(X)2022
NB: for larger diameter cables - larger clips are under development			

Conduit

	Conduit size	Recommended clip size	Part number
	Actual Overall diameter	DISCLAIMER: sizing may vary slightly according to manufacturer	
GALVANISED			
	16mm	15-18mm Superclip (Galvanised)	1LSGALV1518
	20mm	18-20mm Superclip (Galvanised)	1LSGALV1820
	25mm	23-25mm Superclip (Galvanised)	1LSGALV2325
BLACK ENAMEL			
	16mm	15-18mm Superclip (Black)	1LSB1518
	20mm	18-20mm Superclip (Black)	1LSB1820
	25mm	23-25mm Superclip (Black)	1LSB2325
WHITE PVC			
	16mm	15-18mm Superclip (White)	1LSW1518
	20mm	18-20mm Superclip (White)	1LSW1820
	25mm	23-25mm Superclip (White)	1LSW2325
BLACK PVC			
	16mm	15-18mm Superclip (Black)	1LSB1518
	20mm	18-20mm Superclip (Black)	1LSB1820
	25mm	23-25mm Superclip (Black)	1LSB2325





17 Sizing Guide 2021

Conduit



	Conduit size	Recommended clip size	Part number
	Actual Overall diameter	DISCLAIMER: sizing may vary slightly according to manufacturer	
BLACK FLEXIBLE			
	10mm	9-11mm Fireclip (Black)	1LCB911
	16mm	15-18mm Superclip (Black)	1LSB1518
	20mm	18-20mm Superclip (Black)	1LSB1820
	25mm	23-25mm Superclip (Black)	1LSB2325
WHITE FLEXIBLE			
	10mm	9-11mm Fireclip (White)	1LCW911
	16mm	15-18mm Superclip (White)	1LSW1518
	20mm	18-20mm Superclip (White)	1LSW1820
	25mm	23-25mm Superclip (White)	1LSW2325
BLACK FLEXIBLE			
	10mm	9-11mm Fireclip (Grey)	1LCG911
	16mm	15-18mm Superclip (Grey)	1LSG1518
	20mm	18-20mm Superclip (Grey)	1LSG1820
	25mm	23-25mm Superclip (Grey)	1LSG2325
BLACK FLEXIBLE			
	10mm	9-11mm Fireclip (Galvanised)	1LCGALV911
	16mm	15-18mm Superclip (Galvanised)	1LSGALV1518
	20mm	18-20mm Superclip (Galvanised)	1LSGALV1820
	25mm	23-25mm Superclip (Galvanised)	1LSGALV2325



0141 465 4858

info@linianclip.co.uk

THIS DOCUMENT IS INTENDED AS A GUIDE TO ASSIST YOU WHEN CHOOSING A CLIP TO FIT YOUR CABLE. CABLE SIZES MAY VARY DEPENDING ON THE MANUFACTURER. ALWAYS CHECK THE OVERALL DIAMETER OF THE ACTUAL CABLE YOU ARE INSTALLING WITH THE CABLE MANUFACTURER.