

SAFETY DATA SHEET

DOW CHEMICAL (AUSTRALIA) PTY LTD

Product name: NOVITHOR Termite Proof Flexi Gel Sealant, Issue Date: 26.12.2022

Light Grey

Print Date: 25.01.2023

DOW CHEMICAL (AUSTRALIA) PTY LTD encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

SECTION 1: IDENTIFICATION: PRODUCT IDENTIFIER AND CHEMICAL IDENTITY

Product name: NOVITHOR Termite Proof Flexi Gel Sealant, Tile Grey

Recommended use of the chemical and restrictions on use

Identified uses: Adhesive, binding agents Construction materials and additives

COMPANY IDENTIFICATION

DOW CHEMICAL (AUSTRALIA) PTY LTD LEVEL 29 367 COLLINS STREET MELBOURNE VIC 3000 AUSTRALIA

Customer Information Number: 1800-780-074

SDSQuestion@dow.com

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: 1800-033-882 **Local Emergency Contact:** 1800-033-882

For advice, contact a doctor (at once) or the Australian Poisons Information Centre: 131 126

Transport Emergency Only Dial 000

SECTION 2: HAZARD(S) IDENTIFICATION

GHS Classification

Serious eye damage/eye irritation - Category 2A Skin sensitisation - Category 1 Reproductive toxicity - Category 1B Short-term (acute) aquatic hazard - Category 3 Long-term (chronic) aquatic hazard - Category 3

GHS label elements Hazard pictograms





Signal word: DANGER!

Hazard statements

May cause an allergic skin reaction.
Causes serious eye irritation.
May damage the unborn child.
Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention

Obtain special instructions before use.

Avoid breathing dust.

Use only outdoors or in a well-ventilated area.

Avoid release to the environment.

Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response

IF exposed or concerned: Get medical advice/ attention.

If skin irritation or rash occurs: Get medical advice/ attention.

If eye irritation persists: Get medical advice/ attention.

Take off contaminated clothing and wash it before reuse.

Disposal

Dispose of contents and/or container to an approved waste disposal plant.

Other hazards

No data available

SECTION 3: COMPOSITION AND INFORMATION ON INGREDIENTS, IN ACCORDANCE WITH SCHEDULE 8

This product is a mixture.

Component	CASRN	Concentration
Silicon dioxide	7631-86-9	>= 7.0 - <= 8.0 %
2-Butanone, O,O',O"- (methylsilylidyne)trioxime	22984-54-9	>= 4.3 - < 5.0 %

Distillates (petroleum), hydrotreated middle	64742-46-7	>= 2.8 - <= 3.0 %
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	64742-46-7	<= 3.0 %
Titanium dioxide	13463-67-7	>= 0.3 - <= 1.3 %
Vinyltri (methylethylketoxime) silane	2224-33-1	<= 1.1 %
3-Aminopropyltriethoxysilane	919-30-2	>= 0.9 - <= 0.99 %
Methyltri(ethylmethylketoxime)sila ne isomers and oligomers	Not available	<= 0.48 %
Propiconazole	60207-90-1	>= 0.08 - <= 0.45 %

SECTION 4: FIRST AID MEASURES

Description of first aid measures General advice:

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air and keep comfortable for breathing; consult a physician.

Skin contact: Remove material from skin immediately by washing with soap and plenty of water. Remove contaminated clothing and shoes while washing. Seek medical attention if irritation or rash occurs. Wash clothing before reuse. Discard items which cannot be decontaminated, including leather articles such as shoes, belts and watchbands. Suitable emergency safety shower facility should be available in work area.

Eye contact: Wash immediately and continuously with flowing water for at least 30 minutes. Remove contact lenses after the first 5 minutes and continue washing. Obtain prompt medical consultation, preferably from an ophthalmologist. Suitable emergency eye wash facility should be immediately available.

Ingestion: If swallowed, seek medical attention. Do not induce vomiting unless directed to do so by medical personnel.

Most important symptoms and effects, both acute and delayed:

May cause an allergic skin reaction. Causes serious eye irritation. May damage the unborn child.

Indication of any immediate medical attention and special treatment needed

Notes to physician: No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient. Skin contact may aggravate preexisting dermatitis.

SECTION 5: FIREFIGHTING MEASURES

Hazchem Code

None Allocated

Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam. Carbon dioxide (CO2). Dry chemical. Water spray.

Unsuitable extinguishing media: None known...

Special hazards arising from the substance or mixture

Hazardous combustion products: Carbon oxides. Silicon oxides. Nitrogen oxides (NOx).

Unusual Fire and Explosion Hazards: Exposure to combustion products may be a hazard to health..

Advice for firefighters

Fire Fighting Procedures: Use water spray to cool unopened containers.. Evacuate area.. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.. Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage..

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Remove undamaged containers from fire area if it is safe to do so.

Special protective equipment for firefighters: In the event of fire, wear self-contained breathing apparatus.. Use personal protective equipment..

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Remove all sources of ignition. Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions: Do not release the product to the aquatic environment above defined regulatory levels. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up: Wipe up or scrape up and contain for salvage or disposal. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine

which regulations are applicable. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Dispose of saturated absorbent or cleaning materials appropriately, since spontaneous heating may occur.

See sections: 7, 8, 11, 12 and 13.

SECTION 7: HANDLING AND STORAGE, INCLUDING HOW THE CHEMICAL MAY BE SAFELY USED

Precautions for safe handling: Do not get on skin or clothing. Do not swallow. Do not get in eyes. Keep container tightly closed. Protect from moisture. Take care to prevent spills, waste and minimize release to the environment. Handle in accordance with good industrial hygiene and safety practice. CONTAINERS MAY BE HAZARDOUS WHEN EMPTY. Since emptied containers retain product residue follow all (M)SDS and label warnings even after container is emptied. Use with local exhaust ventilation. See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Conditions for safe storage: Keep in properly labelled containers. Store locked up. Keep tightly closed. Store in accordance with the particular national regulations.

Do not store with the following product types: Strong oxidizing agents. Organic peroxides. Explosives. Gases.

Unsuitable materials for containers: Do not store in or use iron or steel containers.

SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value
Silicon dioxide	Dow IHG	TWA Respirable dust	2 mg/m3
	Dow IHG	TWA Total dust	6 mg/m3
	AU OEL	TWA Respirable dust	2 mg/m3
Distillates (petroleum), hydrotreated middle	AU OEL	TWA Mist	5 mg/m3
Hydrocarbons, C15-C20, n-	AU OEL	TWA Mist	5 mg/m3
alkanes, isoalkanes, cyclics, < 0.03% aromatics			
Titanium dioxide	Dow IHG	TWA	2.4 mg/m3
	ACGIH	TWA	2.5 mg/m3
	Further information: A3: Co humans	nfirmed animal carcinogen wi	th unknown relevance to
	AU OEL	TWA	10 mg/m3
	Further information: a: This crystalline silica	value is for inhalable dust co	ntaining no asbestos and < 1%
3-Aminopropyltriethoxysilane	Dow IHG	TWA	0.5 mg/m3
Methyl Ethyl Ketoxime	US WEEL	TWA	10 ppm
		Dermal Sensitization Notatio	n
	Dow IHG	TWA	0.15 ppm
	Further information: Skin S	ensitizer	

The following substance(s), which have Occupational Exposure Limit(s) (OEL), may be formed during handling or processing:

Methyl ethyl ketoxime

Although some of the components of this product may have exposure guidelines, no exposure would be expected under normal handling conditions due to the physical state of the material.

Exposure controls

Engineering controls: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

Individual protection measures

Eye/face protection: Use chemical goggles.

Skin protection

Hand protection: Use chemical resistant gloves classified under standard AS/NZS 2161.10: Protective gloves against chemicals and micro-organisms. Examples of preferred glove barrier materials include: Butyl rubber. Natural rubber ("latex"). Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl chloride ("PVC" or "vinyl"). When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to AS/NZS 2161.10) is recommended. When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to AS/NZS 2161.10) is recommended. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions no respiratory protection should be needed; however, if discomfort is experienced, use an approved air-purifying respirator.

The following should be effective types of air-purifying respirators: Organic vapor cartridge.

Other Information: Selection and use of personal protective equipment should be in accordance with the recommendations in one or more of the relevant Australian/New Zealand Standards, including:

AS/NZS 1336: Eye and face protection – Guidelines.

AS/NZS 1337: Personal eye protection - Eye and face protectors for occupational applications.

AS/NZS 1715: Selection, use and maintenance of respiratory protective equipment.

AS/NZS 2161: Occupational protective gloves.

AS/NZS 2210: Occupational protective footwear.

AS/NZS 4501: Occupational protective clothing Set

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical statepasteColorgreyOdorslight

Odor Threshold No data available pH Not applicable

Melting point/freezing point

Melting point/rangeNo data availableFreezing pointNo data availableBoiling point, initial boiling point and boiling range

Boiling point (760 mmHg)Not applicableFlash pointNot applicableEvaporation Rate (Butyl AcetateNot applicable

= 1)

Flammability

Flammability (solid, gas) Not classified as a flammability hazard

Flammability (liquids) No data available

Lower explosion limit and upper explosion limit / flammability limit

Lower explosion limit
Upper explosion limit
No data available
No data available
Not applicable

Relative vapour density

Relative Vapor Density (air No data available

= 1)

Density and / or relative density

Relative Density (water = 1) 0.985

Solubility(ies)

Water solubility No data available Partition coefficient: n- No data available

octanol/water (log value)

Auto-ignition temperatureNo data availableDecomposition temperatureNo data availableDynamic ViscosityNot applicableKinematic ViscosityNot applicableExplosive propertiesNot explosive

Oxidizing properties The substance or mixture is not classified as oxidizing.

Molecular weight No data available

Particle characteristics

Particle size No data available

NOTE: The physical data presented above are typical values and should not be construed as a specification.

General Business

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Not classified as a reactivity hazard.

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: Can react with strong oxidizing agents.

Conditions to avoid: Do not expose to temperatures above 212 °F/100 °C. Exposure to moisture

Incompatible materials: Avoid contact with oxidizing materials.

Hazardous decomposition products:

Decomposition products can include and are not limited to: Formaldehyde. Methyl Ethyl Ketoxime.

SECTION 11: TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data are available.

Exposure routes

Eye contact, Skin contact, Ingestion.

Acute toxicity (represents short term exposures with immediate effects - no chronic/delayed effects known unless otherwise noted)

Acute Toxicity Endpoints:

Not classified based on available information.

Acute oral toxicity

Information for the Product:

Very low toxicity if swallowed. Swallowing may result in irritation of the mouth, throat, and gastrointestinal tract. May cause nausea and vomiting.

As product: Single dose oral LD50 has not been determined.

Based on information for component(s): LD50, Rat, > 5,000 mg/kg Estimated.

Information for components:

Silicon dioxide

LD50, Rat, > 5,000 mg/kg

2-Butanone, O,O',O"-(methylsilylidyne)trioxime

LD50, Rat, male and female, 2,463 mg/kg OECD Test Guideline 401

Distillates (petroleum), hydrotreated middle

LD50, Rat, > 5,000 mg/kg

Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics

LD50, Rat, male and female, > 5,000 mg/kg

Titanium dioxide

LD50, Rat, > 10,000 mg/kg

Vinyltri (methylethylketoxime) silane

LD50, Rat, > 2,000 mg/kg

3-Aminopropyltriethoxysilane

LD50, Rat, female, 1,479 mg/kg

LD50, Rat, male, 2,665 mg/kg

Methyltri(ethylmethylketoxime)silane isomers and oligomers

For similar material(s): LD50, Rat, male and female, 2,463 mg/kg OECD Test Guideline 401

Propiconazole

LD50, Rat, female, 550 mg/kg OECD Test Guideline 425

Acute dermal toxicity

Information for the Product:

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

As product: The dermal LD50 has not been determined.

Based on information for component(s):

LD50, Rabbit, > 2,000 mg/kg Estimated.

Information for components:

Silicon dioxide

LD50, Rabbit, > 5,000 mg/kg

2-Butanone, O,O',O"-(methylsilylidyne)trioxime

LD50, Rat, male and female, > 2,000 mg/kg OECD Test Guideline 402 No deaths occurred at this concentration.

Distillates (petroleum), hydrotreated middle

LD50, Rabbit, > 3,160 mg/kg No deaths occurred at this concentration.

Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics

LD50, Rabbit, >3,160 mg/kg

Titanium dioxide

LD50, Rabbit, 10,000 mg/kg

Vinyltri (methylethylketoxime) silane

LD50, Rat, > 2,000 mg/kg

3-Aminopropyltriethoxysilane

Based on product testing: LD50, Rabbit, male and female, 4,041 mg/kg

Methyltri(ethylmethylketoxime)silane isomers and oligomers

For similar material(s): LD50, Rat, male and female, > 2,000 mg/kg OECD Test Guideline 402 No deaths occurred at this concentration.

Propiconazole

LD50, Rat, male and female, > 5,000 mg/kg OECD 402 or equivalent No deaths occurred at this concentration.

Acute inhalation toxicity

Information for the Product:

Brief exposure (minutes) is not likely to cause adverse effects. Excessive exposure may cause: Respiratory irritation Central nervous system depression

As product: The LC50 has not been determined.

Information for components:

Silicon dioxide

Maximum attainable concentration. LC50, Rat, 4 Hour, dust/mist, > 2.08 mg/l No deaths occurred at this concentration.

2-Butanone, O,O',O"-(methylsilylidyne)trioxime

The LC50 has not been determined.

Distillates (petroleum), hydrotreated middle

LC50, Rat, 4 Hour, dust/mist, > 5.2 mg/l No deaths occurred at this concentration.

Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics

LC50, Rat, 4 Hour, dust/mist, >5.266 mg/l

Titanium dioxide

LC50, Rat, male, 4 Hour, dust/mist, > 6.82 mg/l No deaths occurred at this concentration.

Vinyltri (methylethylketoxime) silane

The LC50 has not been determined.

3-Aminopropyltriethoxysilane

Based on product testing: LC50, Rat, male, 6 Hour, vapour, > 5 ppm No deaths occurred at this concentration.

Based on product testing: LC50, Rat, female, 6 Hour, vapour, > 16 ppm No deaths occurred at this concentration.

Based on product testing: LC50, Rat, male and female, 4 Hour, Aerosol, > 7.35 mg/l

Sealant, Tile Grey

Methyltri(ethylmethylketoxime)silane isomers and oligomers

The LC50 has not been determined.

Propiconazole

LC50, Rat, male and female, 4 Hour, dust/mist, > 5.8 mg/l OECD Test Guideline 403

Issue Date: 26.12.2022

Skin corrosion/irritation

Not classified based on available information.

Information for the Product:

Based on information for component(s):

Brief contact may cause slight skin irritation with local redness.

May cause drying and flaking of the skin.

Information for components:

Silicon dioxide

Brief contact is essentially nonirritating to skin.

May cause skin irritation due to mechanical abrasion.

May cause drying and flaking of the skin.

2-Butanone, O,O',O"-(methylsilylidyne)trioxime

Brief contact may cause slight skin irritation with local redness.

Distillates (petroleum), hydrotreated middle

Brief contact may cause slight skin irritation with local redness.

Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics

Prolonged contact may cause skin irritation with local redness.

May cause drying and flaking of the skin.

Titanium dioxide

Essentially nonirritating to skin.

Vinyltri (methylethylketoxime) silane

Brief contact may cause slight skin irritation with local redness.

3-Aminopropyltriethoxysilane

Brief contact may cause severe skin burns. Symptoms may include pain, severe local redness and tissue damage.

Methyltri(ethylmethylketoxime)silane isomers and oligomers

For similar material(s):

Brief contact may cause slight skin irritation with local redness.

Propiconazole

Brief contact may cause slight skin irritation with local redness.

Serious eye damage/eye irritation

Causes serious eye irritation.

Sealant, Tile Grey

Information for the Product:

Based on information for component(s): May cause moderate eye irritation. May cause corneal injury.

Information for components:

Silicon dioxide

Solid or dust may cause irritation or corneal injury due to mechanical action.

2-Butanone, O,O',O"-(methylsilylidyne)trioxime

May cause slight eye irritation. May cause slight corneal injury.

Distillates (petroleum), hydrotreated middle

May cause slight eye irritation.

Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics

May cause slight temporary eye irritation.

May cause pain disproportionate to the level of irritation to eye tissues.

Titanium dioxide

Solid or dust may cause irritation due to mechanical action.

Vinyltri (methylethylketoxime) silane

May cause severe irritation with corneal injury which may result in permanent impairment of vision, even blindness. Chemical burns may occur.

3-Aminopropyltriethoxysilane

May cause severe irritation with corneal injury which may result in permanent impairment of vision, even blindness. Chemical burns may occur.

Vapor or mist may cause eye irritation.

Methyltri(ethylmethylketoxime)silane isomers and oligomers

For similar material(s):

May cause slight eye irritation.

Propiconazole

May cause slight eye irritation.

Corneal injury is unlikely.

Sensitization

For skin sensitization:

May cause an allergic skin reaction.

For respiratory sensitization:

Not classified based on available information.

Information for the Product:

Sealant, Tile Grey

For skin sensitization:

A component in this mixture has been shown to be a skin sensitizer.

For respiratory sensitization:

No relevant information found.

Information for components:

Silicon dioxide

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

2-Butanone, O,O',O"-(methylsilylidyne)trioxime

Has caused allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

Distillates (petroleum), hydrotreated middle

For similar material(s):

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics

For similar material(s):

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

Titanium dioxide

Did not demonstrate the potential for contact allergy in mice.

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

Vinyltri (methylethylketoxime) silane

Has caused allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

3-Aminopropyltriethoxysilane

Has caused allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

Sealant, Tile Grey

Methyltri(ethylmethylketoxime)silane isomers and oligomers

For skin sensitization:

For similar material(s):

Has demonstrated the potential for contact allergy in mice.

For respiratory sensitization:

No relevant data found.

Propiconazole

For skin sensitization:

Has caused allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

Not classified based on available information.

Information for the Product:

Product test data not available.

Information for components:

Silicon dioxide

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

2-Butanone, O,O',O"-(methylsilylidyne)trioxime

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Distillates (petroleum), hydrotreated middle

Available data are inadequate to determine single exposure specific target organ toxicity.

Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Titanium dioxide

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Vinyltri (methylethylketoxime) silane

Available data are inadequate to determine single exposure specific target organ toxicity.

3-Aminopropyltriethoxysilane

Material is corrosive. Material is not classified as a respiratory irritant; however, upper respiratory tract irritation or corrosivity may be expected.

Methyltri(ethylmethylketoxime)silane isomers and oligomers

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Propiconazole

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Sealant, Tile Grey

Aspiration Hazard

Not classified based on available information.

Information for the Product:

Based on physical properties, not likely to be an aspiration hazard.

Information for components:

Silicon dioxide

Based on physical properties, not likely to be an aspiration hazard.

2-Butanone, O,O',O"-(methylsilylidyne)trioxime

Based on physical properties, not likely to be an aspiration hazard.

Distillates (petroleum), hydrotreated middle

May be fatal if swallowed and enters airways.

Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics

Aspiration into the lungs may occur during ingestion or vomiting, causing lung damage or even death due to chemical pneumonia.

Titanium dioxide

Based on physical properties, not likely to be an aspiration hazard.

Vinyltri (methylethylketoxime) silane

Based on available information, aspiration hazard could not be determined.

3-Aminopropyltriethoxysilane

Aspiration into the respiratory system may occur during ingestion or vomiting. Due to corrosivity, tissue damage or lung injury may occur.

Methyltri(ethylmethylketoxime)silane isomers and oligomers

Based on available information, aspiration hazard could not be determined.

Propiconazole

Based on available information, aspiration hazard could not be determined.

Chronic toxicity (represents longer term exposures with repeated dose resulting in chronic/delayed effects - no immediate effects known unless otherwise noted)

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Not classified based on available information.

Information for the Product:

Product test data not available.

Information for components:

Silicon dioxide

Sealant, Tile Grey

No relevant data found.

2-Butanone, O,O',O"-(methylsilylidyne)trioxime

For similar material(s):

In animals, effects have been reported on the following organs:

Blood

Distillates (petroleum), hydrotreated middle

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

Titanium dioxide

Repeated excessive inhalation exposures to dusts may cause respiratory effects.

In animals, effects have been reported on the following organs:

Lung.

Due to the physical state of the material, this component is not expected to be bioavailable under normal handling and processing conditions.

Vinyltri (methylethylketoxime) silane

In animals, effects have been reported on the following organs: Blood.

3-Aminopropyltriethoxysilane

In animals, effects have been reported on the following organs: Liver.

Methyltri(ethylmethylketoxime)silane isomers and oligomers

For similar material(s):

In animals, effects have been reported on the following organs:

Blood

Propiconazole

In animals, effects have been reported on the following organs:

Liver

Carcinogenicity

Not classified based on available information.

Information for the Product:

During use of the material, small amounts of methylethylketoxime (MEKO) will be released. Rodents exposed to chronic MEKO inhalation throughout their lifetimes showed significant increases in liver tumour rates.

Information for components:

Silicon dioxide

No relevant data found.

2-Butanone, O,O',O"-(methylsilylidyne)trioxime

No relevant data found.

Distillates (petroleum), hydrotreated middle

For similar material(s): Did not cause cancer in laboratory animals.

Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics

No relevant data found.

Titanium dioxide

Lung fibrosis and tumors have been observed in rats exposed to titanium dioxide in two lifetime inhalation studies. Effects are believed to be due to overloading of the normal respiratory clearance mechanisms caused by the extreme study conditions. Workers exposed to titanium dioxide in the workplace have not shown an unusual incidence of chronic respiratory disease or lung cancer. Titaniumdioxide was not carcinogenic in laboratory animals in lifetime feeding studies. Due to the physical state of the material, this component is not expected to be bioavailable under normal handling and processing conditions.

Vinyltri (methylethylketoxime) silane

No relevant data found.

3-Aminopropyltriethoxysilane

Did not cause cancer in laboratory animals.

Methyltri(ethylmethylketoxime)silane isomers and oligomers

No relevant data found.

Propiconazole

Has caused cancer in some laboratory animals. However, the relevance of this to humans is unknown.

Teratogenicity

May damage the unborn child.

Information for the Product:

Product test data not available.

Information for components:

Silicon dioxide

No relevant data found.

2-Butanone, O,O',O"-(methylsilylidyne)trioxime

For similar material(s): Did not cause birth defects or any other fetal effects in laboratory animals.

Distillates (petroleum), hydrotreated middle

For similar material(s): Did not cause birth defects or any other fetal effects in laboratory animals.

Sealant, Tile Grey

Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics

Did not cause birth defects in laboratory animals.

Titanium dioxide

No relevant data found.

Vinyltri (methylethylketoxime) silane

No relevant data found.

3-Aminopropyltriethoxysilane

Did not cause birth defects or other effects in the fetus even at doses which caused toxic effects in the mother.

Methyltri(ethylmethylketoxime)silane isomers and oligomers

For similar material(s): Did not cause birth defects or other effects in the fetus even at doses which caused toxic effects in the mother.

Propiconazole

Has been toxic to the fetus in laboratory animal tests. Has caused birth defects in laboratory animals.

Reproductive toxicity

May damage the unborn child.

Information for the Product:

Contains component(s) which did not interfere with reproduction in animal studies.

Information for components:

Silicon dioxide

No relevant data found.

2-Butanone, O,O',O"-(methylsilylidyne)trioxime

For similar material(s): In animal studies, did not interfere with reproduction.

Distillates (petroleum), hydrotreated middle

For similar material(s): In animal studies, did not interfere with reproduction.

Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics

In animal studies, did not interfere with reproduction.

Titanium dioxide

No relevant data found.

Vinyltri (methylethylketoxime) silane

No relevant data found.

3-Aminopropyltriethoxysilane

In animal studies, did not interfere with fertility.

Methyltri(ethylmethylketoxime)silane isomers and oligomers

For similar material(s): In animal studies, did not interfere with fertility. In animal studies, did not interfere with reproduction.

Propiconazole

In laboratory animal studies, effects on reproduction have been seen only at doses that produced significant toxicity to the parent animals.

Mutagenicity

Not classified based on available information.

Information for the Product:

Product test data not available.

Information for components:

Silicon dioxide

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

2-Butanone, O,O',O"-(methylsilylidyne)trioxime

For similar material(s): In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

Distillates (petroleum), hydrotreated middle

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics

In vitro genetic toxicity studies were predominantly negative. Animal genetic toxicity studies were negative.

Titanium dioxide

In vitro genetic toxicity studies were negative in some cases and positive in other cases. Animal genetic toxicity studies were negative.

Vinyltri (methylethylketoxime) silane

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

3-Aminopropyltriethoxysilane

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

Methyltri(ethylmethylketoxime)silane isomers and oligomers

For similar material(s): In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

Propiconazole

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data are available.

Ecotoxicity

Silicon dioxide

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested). LC50, Danio rerio (zebra fish), 96 Hour, 5,000 - 10,000 mg/l

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), 24 Hour, > 1,000 mg/l

Acute toxicity to algae/aquatic plants

EC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, Biomass, 440 mg/l

2-Butanone, O,O',O"-(methylsilylidyne)trioxime

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

For similar material(s):

LC50, Fathead minnow (Pimephales promelas), Static, 96 Hour, 843 mg/l, OECD Test Guideline 203

For similar material(s):

LC50, Oryzias latipes (Japanese medaka), Static, 96 Hour, > 100 mg/l, OECD Test Guideline 203

Acute toxicity to aquatic invertebrates

For similar material(s):

EC50, Daphnia magna (Water flea), static test, 48 Hour, 201 mg/l, OECD Test Guideline 202

Acute toxicity to algae/aquatic plants

For similar material(s):

EC50, Selenastrum capricornutum (green algae), Static, 72 Hour, Growth rate, 16 mg/l, OECD Test Guideline 201

For similar material(s):

NOEC, Selenastrum capricornutum (green algae), Static, 72 Hour, Growth rate, 2.6 mg/l, OECD Test Guideline 201

Toxicity to bacteria

For similar material(s):

EC50, activated sludge, 3 Hour, Respiration rates., > 390.45 mg/l, OECD Test Guideline 209

Chronic toxicity to fish

For similar material(s):

NOEC, Oryzias latipes (Orange-red killifish), flow-through test, 14 d, mortality, 50 mg/l

Chronic toxicity to aquatic invertebrates

For similar material(s):

NOEC, Daphnia magna, semi-static test, 21 d, number of offspring, > 100 mg/l

Distillates (petroleum), hydrotreated middle

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested). LL50, Scophthalmus maximus (turbot), 96 Hour, > 1,028 mg/l, Test substance: Water Accommodated Fraction

Acute toxicity to aquatic invertebrates

LL50, Acartia tonsa, 48 Hour, > 3,193 mg/l, Test substance: Water Accommodated Fraction

Acute toxicity to algae/aquatic plants

EL50, Skeletonema costatum (marine diatom), 72 Hour, > 10,000 mg/l, Test substance: Water Accommodated Fraction

Toxicity to bacteria

EC50, 3 Hour, > 100 mg/l, OECD Test Guideline 209

Chronic toxicity to aquatic invertebrates

NOELR, Ceriodaphnia dubia (water flea), 8 d, > 100 mg/l, Test substance: Water Accommodated Fraction

Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/LL50 >100 mg/L in the most sensitive species tested). LL50, Scophthalmus maximus (turbot), 96 Hour, 1,028 mg/l, OECD Test Guideline 203

Acute toxicity to aquatic invertebrates

For similar material(s):

EL50, Daphnia magna, static test, 48 Hour, 210 mg/l, OECD Test Guideline 202 LL50, Acartia tonsa, 48 Hour, > 3,193 mg/l, ISO 14669 and PARCOM method

Acute toxicity to algae/aquatic plants

EL50, Skeletonema costatum (marine diatom), 72 Hour, Growth rate, > 10,000 mg/l, ISO 10253

Toxicity to bacteria

Tetrahymena pyriformis, 40 Hour, Growth inhibition

Titanium dioxide

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested). NOEC, Leuciscus idus (Golden orfe), static test, 48 Hour, > 1,000 mg/l

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), static test, 48 Hour, > 1,000 mg/l

Acute toxicity to algae/aquatic plants

EC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, > 100 mg/l, OECD Test Guideline 201

Toxicity to bacteria

EC50, 3 Hour, > 1,000 mg/l, OECD Test Guideline 209

Sealant, Tile Grey

Vinyltri (methylethylketoxime) silane

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 > 100 mg/L in the most sensitive species tested).

LC50, Oncorhynchus mykiss (rainbow trout), 96 Hour, > 120 mg/l, OECD Test Guideline 203

LC50, Oryzias latipes (Orange-red killifish), 96 Hour, > 100 mg/l, OECD Test Guideline 203

3-Aminopropyltriethoxysilane

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

LC50, Danio rerio (zebra fish), semi-static test, 96 Hour, > 934 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), static test, 48 Hour, 331 mg/l, OECD Test Guideline 202 or Equivalent

Acute toxicity to algae/aquatic plants

ErC50, Desmodesmus subspicatus (green algae), static test, 72 Hour, Growth rate inhibition, > 1,000 mg/l

NOEC, Desmodesmus subspicatus (green algae), static test, 72 Hour, Growth rate inhibition, 1.3 mg/l

Toxicity to bacteria

EC50, Pseudomonas putida, 5.75 Hour, Respiration rates., 43 mg/l

Methyltri(ethylmethylketoxime)silane isomers and oligomers

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

For the hydrolysis product(s)

LC50, Oncorhynchus mykiss (rainbow trout), Static, 96 Hour, > 120 mg/l, OECD Test Guideline 203

Acute toxicity to aquatic invertebrates

For the hydrolysis product(s)

EC50, Daphnia magna (Water flea), static test, 48 Hour, > 120 mg/l, OECD Test Guideline 202

Acute toxicity to algae/aquatic plants

For the hydrolysis product(s)

EC50, Selenastrum capricornutum (green algae), Static, 72 Hour, Growth rate, 94 mg/l, OECD Test Guideline 201

For the hydrolysis product(s)

NOEC, Selenastrum capricornutum (green algae), Static, 72 Hour, Growth rate, 30 mg/l, OECD Test Guideline 201

Chronic toxicity to fish

For similar material(s):

NOEC, Oryzias latipes (Orange-red killifish), flow-through test, 14 d, 50 mg/l

Chronic toxicity to aquatic invertebrates

Sealant, Tile Grey

For similar material(s):

NOEC, Daphnia magna, semi-static test, 21 d, > 100 mg/l

Propiconazole

Acute toxicity to fish

Material is highly toxic to aquatic organisms on an acute basis (LC50/EC50 between 0.1 and 1 mg/L in the most sensitive species tested).

LC50, Leuciscus idus (Golden orfe), 96 Hour, 5.1 mg/l

LC50, Oncorhynchus mykiss (rainbow trout), 96 Hour, 4.3 mg/l

LC50, Cyprinus carpio (Carp), 96 Hour, 5.7 - 46 mg/l

Acute toxicity to aquatic invertebrates

LC50, saltwater mysid Mysidopsis bahia, 96 Hour, 0.51 mg/l

LC50, scud Gammarus sp., flow-through test, 96 Hour, 1.3 mg/l

EC50, Daphnia magna (Water flea), 48 Hour, 10.2 mg/l, OECD Test Guideline 202 or Equivalent

Acute toxicity to algae/aquatic plants

ErC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, Growth rate, 9 mg/l, OECD Test Guideline 201 or Equivalent

NOEC, Pseudokirchneriella subcapitata (green algae), 72 Hour, Growth rate, 0.46 mg/l, OECD Test Guideline 201 or Equivalent

EC50, diatom Navicula sp., 11 d, 0.093 mg/l

Toxicity to bacteria

EC50, activated sludge, 3 Hour, Respiration rates., > 100 mg/l, OECD Test Guideline 209

Chronic toxicity to fish

NOEC, Cyprinodon variegatus (sheepshead minnow), 100 d, number of offspring, 0.068 mg/l NOEC, Fathead minnow (Pimephales promelas), 256 d, number of offspring, 0.188 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna (Water flea), 21 d, growth, 0.37 mg/l

Toxicity to Above Ground Organisms

Material is slightly toxic to birds on an acute basis (LD50 between 501 and 2000 mg/kg). Material is practically non-toxic to birds on a dietary basis (LC50 > 5000 ppm). oral LD50, Coturnix japonica (Japanese quail), 1,777 - 2,223 mg/kg dietary LC50, Anas platyrhynchos (Mallard duck), 8 d, > 5,620 ppm contact LD50, Apis mellifera (bees), 48 Hour, > 100micrograms/bee oral LD50, Apis mellifera (bees), 48 Hour, > 100micrograms/bee

Persistence and degradability

Silicon dioxide

Biodegradability: Biodegradation is not applicable.

2-Butanone, O,O',O"-(methylsilylidyne)trioxime

Biodegradability: Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

10-day Window: Fail

Biodegradation: 20 - 28 %

Sealant, Tile Grey

Exposure time: 28 d

Method: OECD Test Guideline 301C or Equivalent

Distillates (petroleum), hydrotreated middle

Biodegradability: Material is expected to be readily biodegradable.

10-day Window: Not applicable

Biodegradation: 74 % Exposure time: 28 d

Method: OECD Test Guideline 306

Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics

Biodegradability: Based on stringent OECD test guidelines, this material cannot be

considered as readily biodegradable; however, these results do not necessarily mean that the

material is not biodegradable under environmental conditions.

For similar material(s): 10-day Window: Fail

Biodegradation: 57.5 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Biodegradation: 74 % Exposure time: 28 d

Method: OECD Test Guideline 306

Titanium dioxide

Biodegradability: Biodegradation is not applicable.

Vinyltri (methylethylketoxime) silane

Biodegradability: Material is expected to biodegrade very slowly (in the environment). Fails

to pass OECD/EEC tests for ready biodegradability.

10-day Window: Fail **Biodegradation:** 0 % **Exposure time:** 28 d

Method: OECD Test Guideline 301A

Stability in Water (1/2-life)

Hydrolysis, DT50, < 1 min, Half-life Temperature 2 °C, OECD Test Guideline 111

3-Aminopropyltriethoxysilane

Biodegradability: Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

10-day Window: Fail **Biodegradation:** 67 % **Exposure time:** 28 d

Method: OECD Test Guideline 301A or Equivalent

Stability in Water (1/2-life)

Hydrolysis, half-life, 8.5 Hour, pH 7, Half-life Temperature 24.7 °C

Methyltri(ethylmethylketoxime)silane isomers and oligomers

Biodegradability: For similar material(s): This material rapidly hydrolyzes to products that are either readily or ultimately biodegradable.

10-day Window: Fail

Sealant, Tile Grey

Biodegradation: 0 % **Exposure time:** 28 d

Method: OECD Test Guideline 301A

Propiconazole

Biodegradability: Material is not readily biodegradable according to OECD/EEC guidelines.

Biodegradation: 0 % **Exposure time:** 28 d

Method: OECD Test Guideline 301B or Equivalent

Theoretical Oxygen Demand: 2.01 mg/mg

Photodegradation

Test Type: Half-life (indirect photolysis)

Sensitization: OH radicals

Atmospheric half-life: 5.533 Hour

Method: Estimated.

Bioaccumulative potential

Silicon dioxide

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): 0.53

Bioconcentration factor (BCF): 3.16

2-Butanone, O,O',O"-(methylsilylidyne)trioxime

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3). **Partition coefficient:** n-octanol/water(log Pow): 1.69 Estimated by Structure-Activity

Relationship (SAR).

Distillates (petroleum), hydrotreated middle

Bioaccumulation: No relevant data found.

Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics

Bioaccumulation: No relevant data found.

Vinyltri (methylethylketoxime) silane

Bioaccumulation: No relevant data found.

3-Aminopropyltriethoxysilane

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): 1.7 at 20 °C Calculated.

Bioconcentration factor (BCF): 3.4 Cyprinus carpio (Carp) 56 d

Methyltri(ethylmethylketoxime)silane isomers and oligomers

Bioaccumulation: For similar material(s): Bioconcentration potential is low (BCF less than

100 or log Pow greater than 7).

Partition coefficient: n-octanol/water(log Pow): 11.2

Propiconazole

Bioaccumulation: Bioconcentration potential is moderate (BCF between 100 and 3000 or Log Pow between 3 and 5).

General Business

Sealant, Tile Grey

Partition coefficient: n-octanol/water(log Pow): 3.72 Measured

Bioconcentration factor (BCF): 180 Lepomis macrochirus (Bluegill sunfish) 28 d OECD

Test Guideline 305 or Equivalent

Mobility in Soil

Silicon dioxide

Partition coefficient (Koc): 21.73

2-Butanone, O,O',O"-(methylsilylidyne)trioxime

No relevant data found.

Distillates (petroleum), hydrotreated middle

No relevant data found.

Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics

Expected to be relatively immobile in soil (Koc > 5000).

Vinyltri (methylethylketoxime) silane

No relevant data found.

3-Aminopropyltriethoxysilane

No relevant data found.

Methyltri(ethylmethylketoxime)silane isomers and oligomers

No relevant data found.

Propiconazole

Partition coefficient (Koc): 382 - 1789 Measured

Results of PBT and vPvB assessment

Silicon dioxide

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

2-Butanone, O,O',O"-(methylsilylidyne)trioxime

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

Distillates (petroleum), hydrotreated middle

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

Titanium dioxide

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

Vinyltri (methylethylketoxime) silane

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

3-Aminopropyltriethoxysilane

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

Methyltri(ethylmethylketoxime)silane isomers and oligomers

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

Propiconazole

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

Other adverse effects

Silicon dioxide

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

2-Butanone, O,O',O"-(methylsilylidyne)trioxime

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

Distillates (petroleum), hydrotreated middle

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

Titanium dioxide

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

Vinyltri (methylethylketoxime) silane

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

3-Aminopropyltriethoxysilane

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

Methyltri(ethylmethylketoxime)silane isomers and oligomers

This substance is not on the Montreal Protocol list of substances that deplete the ozone laver.

Propiconazole

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

SECTION 13: DISPOSAL CONSIDERATIONS

Disposal methods: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed,

Sealant, Tile Grey

permitted: Recycler. Reclaimer. Incinerator or other thermal destruction device. For additional information, refer to: Handling & Storage Information, MSDS Section 7 Stability & Reactivity Information, MSDS Section 10 Regulatory Information, MSDS Section 15

Treatment and disposal methods of used packaging: Empty containers should be recycled or otherwise disposed of by an approved waste management facility. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. Do not re-use containers for any purpose.

SECTION 14: TRANSPORT INFORMATION

ADG

Not regulated for transport

Classification for SEA transport (IMO-IMDG):

Not regulated for transport Consult IMO regulations before transporting ocean bulk

Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code

Classification for AIR transport (IATA/ICAO):

Not regulated for transport

Hazchem Code None Allocated

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

SECTION 15: REGULATORY INFORMATION

Poison Schedule

Not Scheduled

Australian Inventory of Industrial Chemicals (AIIC)

All substances contained in this product are listed on the Australian Inventory of Industrial Chemicals, or are not required to be listed.

General Business

Prohibition/Licensing Requirements

There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regulations.

Issue Date: 26.12.2022

SECTION 16: ANY OTHER RELEVANT INFORMATION

Revision

Identification Number: 4073625 / A142 / Issue Date: 26.12.2022 / Version: 8.0 Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

ACGIH	USA. ACGIH Threshold Limit Values (TLV)
AU OEL	Australia. Workplace Exposure Standards for Airborne Contaminants.
Dow IHG	Dow Industrial Hygiene Guideline
TWA	Time weighted average
US WEEL	USA. Workplace Environmental Exposure Levels (WEEL)

Full text of other abbreviations

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil: ASTM - American Society for the Testing of Materials: bw - Body weight: CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL -Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx -Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG -Emergency Response Guide: GHS - Globally Harmonized System: GLP - Good Laboratory Practice: IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan): ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and

Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

DOW CHEMICAL (AUSTRALIA) PTY LTD urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.