



# AL-N9

AUTO LENSMETER

# AUTO LENSMETER

# AL-N9



## ■ Specifications

### 1. Measuring range:

Sphere: 0 to  $\pm 35D$  (0.01D/0.06D/0.12D/0.25D steps)  
 Cylinder: 0 to  $\pm 10D$  (0.01D/0.06D/0.12D/0.25D steps)  
 Axis: 0-180° (1°step)  
 ADD: 0 to 10D (0.01D/0.06D/0.12D/0.25D steps)  
 Prism: 0 to 15 $\Delta$ (0.01 $\Delta$ )

### 2. Cylinder Mode: +, +/-, -

3. Prism Mode: X-Y: Cartesian Coordinates H:I, O. V:U, D.  
 P-B: Polar Coordinates  
 mm: mm expression

4. Reading resolving power: 0.01D, 0.06D, 0.12D, 0.25D

5. PD measure

6. Measure single vision lens, bifocal lens, trifocal lens and progressive lens, etc.

7. Contact lenses measure

8. UV transmissivity test

9. Measurable transmissivity: >10%; >20% at  $\pm 10D$  and over

10. Contact lenses: 0 to  $\pm 25D$ , BC 6.00 to 9.00

11. Display: 5.7inches TFT LCD Monitor

12. Menu: readable diagram, easy operation

13. Lens diameter: 20mm – 100mm

14. Power source: AC100 ( $\pm 10\%$ ) - 240( $\pm 10\%$ )V 50/60Hz 40VA

15. Power consumption: 40W

16. N.Weight: 9Lbs

17. Dimensions(packaging): (L)20" x (W)13" x (H)12"mm

18. Environmental condition:

- a. Temperature: 5-40°C (In usage)  
-20-60°C (In storage/transference)
- b. Humidity: 30-85% (Non-condensing) (In usage)  
10-95% (In storage/transference)
- c. Atmospheric pressure: 700-1060hpa
- d. Altitude: up to 2000m
- e. Others: no harmful dust or smoke

19. Printer : built-in high-speed thermal printer, paper size 57mm



Lunar Health

### Lunar Health

17 Spectrum Pointe Dr Suite 508 Lake Forest, CA 92630  
 Tel: (949) 624-5566 Email: vision@lunar-health.com  
 www.lunar-health.com

Manufactured by Ray Vision