

Carbon Block Filter Cartridges

Thick wall carbon construction for superior performance. Low cost for economy!

Top-of-the-line coconut shell carbon block filter cartridge for chlorine, taste, odor and sediment reduction.

Features


- Competitively priced!
- Outperform GAC cartridges four ways:
 - 1. Superior chlorine reduction
 - 2. Lower pressure drop.
 - 3. Will not channel
 - 4. Lower cost
- Media wrap between center tube and carbon block to reduce carbon fines.
- 100% Coconut shell Carbon.
- Up to 99% chlorine reduction*.
- FDA grade components & materials.

Recommended Flow Rate

Part Number	OD	Length	GPM
CB-5-210-G	2.5"	9-3/4"	1
CB-5-220-G	2.5"	20"	2
CB-5-410-G	4.5"	9-3/4"	4
CB-5-420-G	4.5"	20"	8



Initial Pressure Drop



Maximum operating pressure: 125 PSIG
Operating temperature: 50° F to 125° F

10° C to 52° C

*Performance tested @ flow with 2ppm chlorine

^{*} Tested and verified by independent labatory testing.

Part Number	Туре	OD	Length	Mircon Rating*	Chlorine Reduction*	No. / Case
CB-5-210-G	Thick Wall	2.5"	9-3/4"	5 nominal	>4,000 Gal @ 1 gpm	20
CB-5-220-G	Thick Wall	2.5"	20"	5 nominal	>8,000 Gal @ 2 gpm	12
CB-5-410-G	Thick Wall	4.5"	9-3/4"	5 nominal	>10,000 Gal @ 2 gpm	12
CB-5-420-G	Thick Wall	4.5"	20"	5 nominal	>20,000 Gal @ 4 gpm	6

NOTE: Use only with microbiologically safe and adequately disinfected water, do notuse with water of any unknown origin or water quality.

Website: www.ereinc.com • Call toll free: 1-888-287-3732 • Email: sales@ereinc.com