


THE EVOLUTION OF UV DISINFECTION

OEM MODULE AND INTEGRATED LED SYSTEM

As the development of UVC LED technology continues its rapid growth, LUMINOR has expanded on the proven efficacy of UV germicidal irradiation, and coupled it with high-tech UVC LED technology, to produce an energy efficient, environmentally friendly technology of the future. These compact UVC LED modules provide 99.99% pathogen reduction and have a global reach with a myriad of applications ranging from residential water treatment, water dispensers, appliances, food service, RV, marine, medical, disaster relief and many more.



*shown with
optional
mounting
bracket

GU-4S

GU-5S

Why LED?

- Compact footprint, high power density UVC LEDs combined with integral solid state control architecture allow for a much smaller installation footprint than traditional UV systems.
- UVC LEDs are “instant-on” devices, requiring no warm-up time to achieve disinfection. This allows for eco-friendly operation in response to water flow.
- UVC LEDs have an extremely long service life resulting in reductions in lamp replacement and labour expenses.
- Unlike traditional UV lamps containing mercury, UVC LEDs are free of hazardous materials, which eliminates the risk of a mercury spill due to a lamp breakage.
- Eco friendly, extremely low power consumption and no potentially dangerous chemicals used in their construction.
- Unlimited cycling, UVC LED is not impacted by on/off cycles.
- Temperature independent constant UVC output regardless of water temperature. Plus, UVC LEDs do not transfer heat from the light emitting surface, thus limiting lamp fouling.
- Wavelength selectivity: LUMINOR can custom tailor the wavelength of the LED module for customized UVC applications.

GLACIER UVC LED System Specifications

MODEL	GUV-4S	GUV-5S
Flow Rate @ (10 mJ/cm ² at 95% UVT)	1.5 GPM 5.6 lpm	1.5 GPM 5.6 lpm
Flow Rate @ (16 mJ/cm ² at 95% UVT)	1.3 GPM 4.9 lpm	1.3 GPM 4.9 lpm
Flow Rate @ (30 mJ/cm ² at 95% UVT)	0.6 GPM 2.4 lpm	0.6 GPM 2.4 lpm
Flow Rate @ (40 mJ/cm ² at 95% UVT)	0.4 GPM 1.3 lpm	0.4 GPM 1.3 lpm
UVT (%)	Recommended above 90%	
Headloss at Max Flow	166 mBar (2.4 psi)	
Max Pressure	6.9 bar (100psi)	
Max Ambient Temperature	50° C (122° F)	
Operating Water Temperature	0-45° C (32-113° F)	
Water Connections	3/8" OD Tube (fits John Guest® style quick connect fittings)	
Input Voltage	12VDC	
Input Power	15W	16W
Electrical Connection	Standard 12VDC barrel connector, 2.1 x 5.5 mm	
LED Status Monitoring	YES	
LED Life Monitoring	YES	
LED Life	5,000 hours	
Solenoid Output	NA	YES (optional module (MOD-SOL) sold separately)
Dry Contacts (solenoid ready)	NA	YES (optional module (MOD-RAM) sold separately)
Sherpa	NA	YES (optional module (MOD-SHERPA) sold separately)
IoT	NA	YES (optional module (MOD-APP) sold separately)
Display	Dual colour LED	Full customizable colour screen
Overall Dimensions (with mounting brackets)	241mm x 104mm x 107mm (9.5in x 4.1in x 4.2in)	
Shipping Weight	400 g (14 oz)	

Specifications subject to change without notice.



Third party microbiological testing in accordance with the US EPA drinking water guidelines



System Tested and Certified by WQA against NSF/ANSI-61 for material safety only. Certified to NSF/ANSI-372 for lead free compliance.

Manufacturer's Warranty

GLACIER UV LED modules are covered by a One (1) year Limited Warranty
See website for LUMINOR's complete warranty document
including conditions and exclusions.



Environmental
ERE Remediation Equipment Inc.

ERE INC
8605 rue Champ d'Eau
St. Leonard QC, H1P 3B8 Canada
Tel: (514) 326-8852
Fax: (514) 326-8961
www.ereinc.com