

## Cantina Frigo 264 bottiglie\* MONOTEMPERATURA

\* tipo Bordolese da 0,75 Lt.



- . Capacità: 264 bottiglie\*
- . Libera installazione
- . Colore: Black
- . Raffreddamento: Compressore
- . Temperatura regolabile da 5° a 18°C
- . Regolazione elettronica
- . Termometro elettronico con display digitale
- . Porta piena con lavagna interna



Temperatura d'Esercizio: da 10° a 32°C

### ATTREZZATURE INCLUSE

- . 4 Ripiani fissi in legno
- . 1 Ripiano scorrevole in legno
- . 2 Piedini Regolabili (altezza 4 cm)
- . 2 Ruote
- . 1 Filtro a carboni attivi
- . Sistema Antivibrazione
- . Sbrinamento Automatico

### CARATTERISTICHE TECNICHE

- . Classe energetica: G
- . Consumo elettrico annuale: 169 kWh
- . Classe climatica: SN-N
- . Rumorosità: 35 dB
- . Voltaggio: 220 - 240 V.
- . Potenza assorbita: 48 W.
- . Tipo di gas: R600a
- . Dimensioni (LxPxA cm): 62x71x186
- . Peso: 72 Kg

### SICUREZZA

- . Funzione Inverno: garantisce il mantenimento della temperatura anche quando nell'ambiente dove è collocata la cantina frigo si ha una temperatura inferiore a quella impostata.

VINOTAG® 

- . Applicazione gratuita per la gestione della tua cantina.

## Wine Cellar 264 bottles\* MONOTEMPERATURE

\* Calculated with 0.75 Lt. Bordeaux bottles.



- . Capacity: 264 bottles \*
- . Free installation
- . Color: Black
- . Cooling: Compressor
- . Adjustable temperature from 5 ° to 18 ° C
- . Electronic regulation
- . Electronic thermometer with digital display
- . Full door with internal whiteboard



Ambient temperature: from 10° a 32°C

### EQUIPMENT INCLUDED

- . 4 Fixed wooden shelves
- . 1 Sliding wooden shelf
- . 2 Adjustable Feet (height 4 cm)
- . 2 Wheels
- . 1 Activated carbon filter
- . Antivibration system
- . Automatic defrost

### TECHNICAL FEATURES

- . Energy class: G.
- . Annual electricity consumption: 169 kWh
- . Climate class: SNN
- . Noise: 35 dB
- . Voltage: 220 - 240 V.
- . Power consumption: 48 W.
- . Gas type: R600a
- . Dimensions (LxWxH cm): 62 x 71x 186
- . Weight: 72Kg

### SAFETY

- . Winter function: guarantees the maintenance of the temperature even when the temperature in the room where the refrigerated cellar is located is lower than the set one.

VINOTAG® 

- . Free application for the management of the cellar