

Glicket LAME A+



Large

80.4%



Medium

5kW Output

85.1%



Small

4.9kW 82.7%



UK UK CE OPTIONAL Snoke Control OptionAL Snok





















SMALL 139-S-FLICKRFL

Wood

4.9

Fuel

kW



MEDIUM 139-M-FLICKRFL



LARGE 139-I-FLICKREI



Efficiency	82.7%	
Flue size	125mm	
Outlet	Top & rear	
Outside air	Optional	
Materials	Steel body cast iron door	
Weight	65kg	
Height	494mm	
Width	446mm	
Depth	353mm	
Distance to combustibles		

Width	446mm	
Depth	353mm	
Distance to combustibles		
Back	300mm	
Sides	400mm	
Distance to non-combustibles		
Back	50mm	
Sides	75mm	
Hearth projection		
Front	400mm	
Side	150mm	
Distance to furniture		
Front	1075mm	
Suitable for 12mm hearth		

Yes

Fuel	Wood
kW	5
Efficiency	85.1%
Flue size	125mm
Outlet	Top & rear
Outside air	Optional
Materials	Steel body, cast iron door
Weight	64kg
Height	530mm
Width	410mm

Distance to combustibles		
Back	250mm	
Sides	400mm	
Distance to non-combustibles		
Back	50mm	
Sides	75mm	
Hearth projection		
Front	400mm	
Side	150mm	

330mm

Depth

	· - · - J · · ·	
Front	400mm	
Side	150mm	
Distance to furniture		
Front	1075mm	
Suitable for 12mm hearth		
Yes		

139-L-FLICKRFL		
Fuel	Wood	
kW	5	
Efficiency	80.4%	
Flue size	125mm	
Outlet	Top & rear	
Outside air	·	
Materials	Steel body, cast iron door	
Weight	76kg	
Height	590mm	
Width	490mm	
Depth	353mm	
Distance to combustibles		
Back	250mm	
Sides	400mm	
Distance to non-combustibles		
Back	50mm	
Sides	75mm	
Hearth projection		
Front	400mm	
Side	150mm	

Distance to furniture

Suitable for 12mm hearth Yes









1075mm