

CARMEL GROUP INC.

SAFETY DATA SHEET

SECTION 1 – CHEMICAL PRODUCT AND COMPANY IDENTIFICATION								
Product Sprue wax				Revision date 6/22/2021				
Previous revision date 09/12/2019	Product code SW40X09 (See p.5)		Material use Casting of dental prostheses.					
Manufacture's Name and issuing location CARMEL GROUP INC. 10220 ARMAND LAVERGNE, MONTRÉAL, QUEBEC, CANADA, H1H 3N4 PHONE : 514-270-5377 FAX : 514-270-2025 INTERNET : www.carmelindustries.com			EMERGENCY PHONE NUMBER CHEMTREC USA 800-424-9300 International 1-703-527-3887					
SECTION 2 – COMPOSITION / INFORMATION ON INGREDIENTS								
Hazardous Ingredients	Note (Sect 15)	CAS #	Amount	Exposure Limits (ppm)				
				OSHA PEL-TWA	NIOSH REL-TWA	NIOSH REL-STEL	ACGIH TLV-TWA	ACGIH TLV-STEL
None as defined by OSHA 29 CFR 1910.1200 & by Canadian WHMIS CPR								
SECTION 3 – HAZARD IDENTIFICATION								
Emergency Overview								
The product is not expected to present any unusual hazards in proper use. The melted wax must be handled carefully as it may burn.								
SKIN CONTACT	No danger at room temperature. May cause minor burns when melted.							
EYE CONTACT	No danger at room temperature. May burn if splattered when melted.							
INHALATION	Not likely to occur as the product is not volatile at room temperature and low volatility when melted.							
INGESTION	May cause gastrointestinal irritation, nausea, vomiting and diarrhea if ingested in large quantity.							
Potential Health Effects (NFPA Classification)								
Fire hazard : 1	Health Hazard : 1	Reactivity : 0	Personal Protection : See Section 8					
0 = Minimal 1 = Slight hazard 2= Moderate Hazard 3 = Serious Hazard 4 = Severe Hazard								
Potential Health Effects (HMIS Rating)								
Health : 1		Flammability : 1		Reactivity : 0				
0 = Minimal 1 = Slight hazard 2= Moderate Hazard 3 = Serious Hazard 4 = Severe Hazard								
SECTION 4 – FIRST AID MEASURES								
EYE CONTACT	Exposure to fumes, vapors or smoke of the thermally degraded product can result in irritation to the eye and direct contact of the molten material will cause eye injury and burns. Should an accident occur, flush eyes with generous amounts of water for at least 15 minutes. Call a physician to attend to the injury.							
SKIN CONTACT	Exposure to fumes, vapors or smoke of thermally degraded product can result in irritation to skin and direct contact of the molten material will cause injury and burns. For burns apply running water over the injured area for 15 minutes. Do not attempt to remove any material bonded to skin. Call a physician to attend to the injury.							
INHALATION	Remove individual to a well-ventilated area for fresh air and call a physician to attend							

	to the injury.		
INGESTION	Material is not acutely toxic by ingestion. If material is ingested, do not induce vomiting. Call a physician.		
ADDITIONAL INFO	None		
SECTION 5 – FIRE FIGHTING MEASURES			
Extinguishing Media	Treat as an oil fire. Use Foam, Dry Chemical and CO ₂ .		
Special Firefighting Procedure	Keep people away from fire and smoke, Wear full firefighting turn-out gear and respiratory protection (SCBA).		
Unusual Fire and Explosion Hazards	This product will burn if involved in a fire.		
SECTION 6 – ACCIDENTAL RELEASE MEASURES			
Small Spills	Not likely to occur in solid format. Sweep and scrap the spill		
Large Spills	Not likely to occur in solid format. May melt if exposed to excessive heat. In that case, let the material solidify and scrap the spill.		
SECTION 7 – HANDLING AND STORAGE			
Handling procedures	Handle as a fragile material. Wash thoroughly exposed body part after using.		
Storage precautions	Normal precaution should be followed in handling and storage. Store in a dry & cool place. Keep out of strong sunlight. Do not store at temperature : > 50°C / 120°F or near spark or open flame.		
SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION			
PERSONAL PROTECTION			
Respiratory protection	No special respiratory protection is normally required.		
Protective gloves	Rubber glove to prevent burning with the melted wax.		
Eye protection	Protective goggle to prevent burning by splatter of melted wax.		
Clothing	Standard industrial.		
SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES			
Appearance Red narrow cylinder	Odor None	Physical state Solid @ 25°C/77°F	Boiling point N / AV.
Melting point ~ 65°C / 150°F	Specific gravity (H ₂ O=1) > 1	Vapor pressure (mm Hg) <0.01 @ 25°C/77°F	Solubility in water Insoluble
Solubility in organic solvent Soluble	Partitioning coefficient N / AV.	Flash point N / AV.	Percent volatiles Nil
SECTION 10 – STABILITY AND REACTIVITY DATA			
Stability Stable	Hazardous polymerization Will not occur.		
Incompatibility Normally unreactive; however avoid contact with strong oxidizing agent (ex. Peroxides, chlorine).			
Hazardous decomposition products Burning can produce noxious and toxic fumes, and the following combustion products: Oxides of carbon & Other complex chemical.			
SECTION 11 – TOXICOLOGICAL INFORMATION			
Carcinogenicity Not listed, not carcinogenic to date.	Mutagenicity / Teratogenicity Not listed		
Irritancy of Material None known	Sensitizing Capability None known		
Reproductive Effects None known	Synergistic Materials None known		
SECTION 12 – ECOLOGICAL INFORMATION			
This product is stable in water, and can be mechanically separated from water. The water may be suitable for disposal in a biological waste water treatment plant. Not expected to be acutely toxic to aquatic organism.			
SECTION 13 – DISPOSAL CONSIDERATION			
Incineration is probably the best mean of disposal. Dispose as industrial waste in accordance with appropriate Federal, State and local regulation.			

SECTION 14 – TRANSPORT INFORMATION	
Dot Hazard Classification	Not regulated
IATA Classification	Not regulated
ICAO Classification	Not regulated
IMO Classification	Not regulated
TDG Hazard Classification	Not regulated
UN / NA Hazard No.	None necessary
Other	N / AV.
SECTION 15 – REGULATORY INFORMATION	
Hazard Details of SECTION 2	None
SARA Status	No reporting requirement.
SARA Hazard Cat.	None
TSCA Status	All ingredients of this product are listed on the U.S. EPA TSCA (Toxic Substances Control Act) Chemical Substance Inventory.
DSL Status	All ingredients of this product are listed on the Canadian EPA (CEPA) Domestic Substances List (DSL).
EINECS Status	All ingredients of this product are listed on the European Inventory of Existing Chemical Substances (EINECS).
AICS Status	All ingredients of this product are listed on the Australian Inventory of Chemical Substances (AICS).
OSHA Status	Not a controlled or hazardous material as defined by U.S. OSHA HCS (29 CFR 1910.1200).
WHMIS Status	Not a controlled or hazardous material.
OSHA HCS Compliance	MSDS of the product is classified in accordance with all the required information for his hazard criteria under the Health Communication Standards of the U.S. OSHA.
WHMIS CPR Compliance	MSDS of the product is classified in accordance with all the required information for his hazard criteria under the Controlled Products Regulations of the Canadian WHMIS.
ANSI Z400.1-1993 Compliance	MSDS of the product is made following the Z400.1-1993 standards of the ANSI.
SECTION 16 – OTHER INFORMATION	
N/AV=NOT AVAILABLE	
SDS Originally made by Carmel Industries.	

The information contained in this document is derived from data supplied to Carmel Group by the manufacturers or distributors of the raw materials combined to form this product. However, Carmel Group makes no representations as to its completeness or accuracy. To the best of our knowledge all hazards have been noted for the intended use of the product and, since Carmel Group cannot control conditions of use, the end user is obliged to determine the conditions permitting safe use of the product. In no event will Carmel Group be responsible for damage of any nature whatsoever resulting from the use of or reliance upon the information contained herein.

CARMEL GROUP INC.

SPRUE WAX PRODUCTS

Product code	Product Description	Gauge
SW40009	Wax Red Sprue	5
SW40109	Wax Red Sprue	6
SW40209	Wax Red Sprue	8
SW40309	Wax Red Sprue	10
SW40409	Wax Red Sprue	1/4