

Item #	Project	
Quantity	Item #	
	Quantity	

# AF-50HE/25 HEAVY DUTY FRYER

**GAS TYPE:** 

NATURAL





## AF-50HE/25

#### STANDARD FEATURES

- All stainless steel front and sides.
- Heavy gauge stainless steel tank.
- Energy efficient burners rated at 40,000 BTU/hr. each.
- Millivolt control system with 100% safety shut off.
- Thermostatic control with 200°F to 400°F range.
- 1-1/4" full port drain valve.
- 4" legs or optional casters.
- Two year limited warranty, parts and labor.

#### **AVAILABLE OPTIONS**

- Stainless steel tank cover.
- Four casters front two with locking brakes.
- Matching "Dump Station."
- Stainless steel Splash Guard (easily removable without tools).
- Stainless steel side tray for working surface or dump station, can be used with optional heat lamp.
- Stainless steel spreader work top solid surface 12", 18" and 24".
- Quick disconnect and flexible gas hose.
- Joiner Strip: Connects two fryers and prevents oil from getting in between the fryers or drain station.



Model AF-50HE/25 Shown with optional casters

### **DESCRIPTION**


American Range, 50/25 pound fryer, model AF-50/25. All stainless steel front and sides, with heavy gauge stainless steel tank and rated at 40,000 BTU/hr. Standard Millivolt control system with 100% safety shut off and Thermostatic control with a temperature range of 200°F to 400°F. 1-1/4" full port drain valve for easy cleaning.

















Shipping Weight\*

MODEL	WIDTH (MM)	DEPTH (MM)	HEIGHT (MM)	BURNERS	COOKING AREA	BTU	(kW)	LBS	(KG)
AF-50HE/25	23 1/4" (591 mm	30-1/4" (768 mm)	45-3/4" (1162 mm)	5	(1) 14" x 14" (356 mm x 356 mm) (1) 8-3/4" x 14" (171 mm x 356 mm)	200,000	(59)	225	(102)

Specify type of gas and altitude if over 2000 feet. Please specify gas type when ordering.

MANIFOLD PRESSURE						
NATURAL GAS	PROPANE GAS	MANIFOLD SIZE				
5.0" W.C.	10.0" W.C.	3/4" (19MM)				

NMFCCODE: 25970-2 Class: 85

\*Shipping weight includes packaging and is approximate.

American Range is a quality manufacturer of commercial cooking equipment. Due to continuing product improvements, these specifications are subject to change without prior notice.

## COMBUSTIBLE WALL CLEARANCES:

For use only on non-combustible floors. Legs or casters are required, or 2" (51) overhang is required when curb mounted. Clearance from non-combustible walls is 0". When unit is placed next to combustible walls, clearances must exceed 12" (305) from sides, and 4" (102) from rear.

Commercial cooking equipment requires an adequate ventilation system. For additional information, refer to the National Fire Protection Association's standard.

NFPA96 "Vapor Removal from Cooking Equipment." (NOTE: For North America only)  $\,$ 





