

4184 E. Conant st., Long Beach, CA 90808 Tel. 800-500-3519 Fax. 310-900-1066 www.gkradiance.com

Project : Model # : Item # : Qty : Available W/H : Approval :

Deck Oven

Model : RBDO-33



*One electrical connection for all decks per model

____ FEATURES & BENEFITS =___

Microprocessor heating control

A consecutive step by step control method with a microprocessor allows for heating control from 0~100% to enable even and precise temperature control.

Heat distribution

A heating system that enables even heat distribution inside the oven and heat retention help ensures even colorization of the product.

Deck size

- May have 2 tray, 3 tray, or 4 tray deck option
- Optional rack stand for baked bread.

Steam injection & ceramic stone plate option

With room temperature, high pressure steam at micron level, fine steam is evenly supplied to the bread surface.

- User-friendly display
 Time setting allows for desired time setting using arrow buttons
- Overheat protection sensor

Once the unit is plugged in, protection sensors will set in to prevent serious burns.

Safety enforced

Each unit is thoughtfully designed with well-rounded corners for the benefit of bread bakers and chefs.

Variety

Perfect for variety of different bread types including cakes, pastries, and all other hard breads.



Model	Capacity	Tray Size (inches)	Length (inches)	Depth (inches)	Height (inches)	Net Weight (lbs.)
RBDO-33	3 trays	16 x 24	641/2	323/4	707/8	1015

Deck Oven

Model : RBD0-33

MODEL	RBDO-33		
Exterior Dimension (L x D x H) (in.)	641/2 x 323/4 x 707/8		
Interior Dimension (L x D x H) (in.)	48 x 265/8 x 77/8		
Capacity	3 Trays 3 Tiers		
Voltage	220V, 3PH, 50A, 19KW, 60Hz		
Wire Gauge	AWG 9		
Tray Size (in.)	16 x 24		
Temperature Range	90°F - 536°F		
Preset	5		
Net Weight (lbs.)	1015		
Option(s)	Steam + ceramic stone plate (1.5KW power / Deck)		
Water Feed Pipe	1/2" ball valve		
Drain Pipe (in.)	2		

Design and specifications subject to change without notice. Most updated spec sheets are available at www.gkradiance.com. Actual shipping weight may differ due to extra packing materials for product protection.

• WARRANTY : 1 Year Parts and Labor Warranty

