
# Stainless Steel Continuous Pin & Barrel Hinges

# Innovation, Quality, Customer Service...

# **Full Concealed**





#### **Standard Features**

- Full concealed, heavy duty
- ½" door inset
- 48" door width maximum
- 600 lbs. door weight maximum
- **Fasteners**: 10-24 x %" undercut, self-drilling, thread-forming tek machine screws, stainless steel and #10 x 1-1/4" undercut wood screws, stainless steel
- Lengths: 78-¾", 83-1/8", 85", 95" and 118-3/4"
- Finishes: US32D Satin Stainless Steel or US32 Bright Stainless Steel
- **Fire Rating** tested and certified by UL® (U.S.A. and Canada) on 4'0" x 10'0" fire rated doors, based on the following
  - 20 minutes wood doors
  - 90 minutes hollow metal and composite core wood fire doors
  - 3 hours hollow metal doors

# **Options Available**

 See pages G-6 to G-7 for modification availability and details





## **A500RB**

#### **Standard Features**

- Raised barrel (swaged) for door set back in deep reveals
- Full concealed, heavy duty
- 48" door width maximum
- 600 lbs. door weight maximum
- Fasteners:  $10\text{-}24 \times \%$ " undercut, self-drilling, thread-forming tek machine screws, stainless steel and #10 x 1- $\frac{1}{4}$ " undercut wood screws, stainless steel
- Lengths: 78-¾", 83-1/8", 85", 95" and 118-3/4"
- **Finishes:** US32D Satin Stainless Steel or US32 Bright Stainless Steel
- **Fire Rating** tested and certified by UL® (U.S.A. and Canada) on 4'0" x 10'0" doors, based on the following
  - 20 minutes wood doors
  - 90 minutes hollow metal and composite core wood fire doors
  - 3 hours hollow metal doors

### **Options Available**

• See pages G-6 to G-7 for modification availability and details



