



THRUBOLT VISION LITE: VLF

 UP TO 3 HOUR

Standard, multi-purpose, thru-bolted square profile vision lite for up to 1/4" thick glazing.

PRODUCT DETAILS:

Size:

Minimum Size: 4" x 4"

Maximum Size: 60" x 104"

Material: 18 gauge cold rolled steel

Construction: 1-1/4" trim with mitered and welded radius corners. Countersunk mounting holes on both sides.

Door Thickness: 1-3/4"

Standard Finish: Mineral bronze powder coat

Optional Powder Coat Finishes: Gray, black, flat black, white, silver, brass, sand, AMS beige, SC beige

GLAZING:

Glazing Thickness: 3/16" - 1/4"


Fire-Rated Glazing: WS, PPF, PYRO

Non-Rated Glazing: TEMP


FIRE RATING:

UL listed and labeled to ANSI/UL 10B and ANSI/UL 10C when properly installed in rated and approved door. Ratings up to 3 hours can be achieved, depending on glazing used and maximum exposed area.

Intertek - Warnock Hersey listed and labeled upon request to NFPA 252, CAN/ULC S104, ANSI/UL 10B and ANSI/UL 10C for ratings up to 90 min.



VLF in Mineral Bronze



ADDITIONAL PRODUCTS



Materials:

- 18 gauge 304 stainless steel #4 Finish
- 18 gauge galvalneal steel
- 18 gauge zinc plated steel



VLFR12:

12" dia. 18 gauge cold rolled steel

VLFR18:

18" dia. 18 gauge cold rolled steel

VLFR24:

24" dia. 18 gauge cold rolled steel



VLFGS:

18 gauge vision lite with 12 gauge cold rolled steel grille welded to both sides of frame.



VLFPVC:

16 gauge door on continuous hinges welded to vision lite. This product is not fire-rated.



VLFS10:

10 gauge cold rolled steel for security.

VLFS10SP:

10 gauge cold rolled steel with perforated steel speaker panel with staggered holed. This product is not fire-rated.



Mullions:

Vision lite with welded-on mullions for a divided lite look. See page 14.