

# S1150 & S1250 Series Exit Devices

## Classic Product

### Certification & Compliance:

- ANSI/BHMA A156.3, Grade 1
- ANSI A117.1 Accessibility Code
- Underwriters Laboratories (UL and CUL) listed for accident hazard (panic) standard.
- Fire Exit hardware for hollow metal doors, UL and CUL listed for 3 hour, A label and lesser doors, Prefix "F" before part number.
- Fire Exit hardware for wood doors, listed up to 1-1/2 hour, B label doors.
- All exit devices comply with life safety code NFPA 101.
- All fire rated devices comply with fire door and window code NFPA80.



**S1150**  
Vertical Rod Exit Device

**S1250**  
Rim Exit Device

### General Specifications:

	<b>S1150</b>	<b>S1250</b>
<b>Chassis &amp; Cover</b>	Non-ferrous alloy	Non-ferrous alloy
<b>End caps</b>	Metal	Metal
<b>Doors</b>	1-3/4" (44.45mm) thick wood or hollow metal 3-3/4" minimum stile for single doors 3-1/2" (88.90mm) minimum stile for double doors	1-3/4" (44.45mm) thick wood or hollow metal 4-1/2" (114.3mm) minimum stile 4-5/8" for fire-labeled devices
<b>Handing</b>	Reversible	Reversible
<b>Dogging</b>	Allen-type key standard, cylinder available.	Allen-type key standard, cylinder available.
<b>Top/Bottom Bolts/ Latchbolt</b>	Brass 1/2" (12.7mm) throw top, 3/4" (19.05mm) bottom	3/4" (19.05mm) throw, stainless steel
<b>Throughbolts</b>	Order separately	Order separately
<b>Rail Assembly</b>	Steel	Steel
<b>Rail Size</b>	Furnished standard for doors up to 36", can be cut down to accommodate 32" doors. Alternate rail sizes available for narrow or wide doors	Furnished standard for doors up to 36", can be cut down to accommodate 32" doors. Alternate rail sizes available for narrow or wide doors
<b>Rods</b>	90"-extension kits available	N/A
<b>Trim</b>	See trim page 105	See trim page 105
<b>Finishes</b>	AL, BRZ, LBZ (sprayed finishes)	AL, BRZ, LBZ (sprayed finishes)

ASSA ABLOY, the global leader  
in door opening solutions



**ASSA ABLOY**