## **TECH - SPEC:**

#### Pemko Product Reference Sheet

**ASSA ABLOY** 

The global leader in door opening solutions

## 158\_

#### **Commercial Thresholds**

Example: 158 | A | 36

Profile# Finish Length

**TYPE:** Offset Saddles

**FINISHES:** A (Mill Finish), D (Dark Anodized), G (Gold Anodized)

**LENGTHS:** Up to 185"

**WIDTH:** 5-1/2" (139.7 mm)

**HEIGHT:** 1/4" (6.4 mm) x 1/2" (12.7 mm)

**WEIGHT:** Estimated per foot: 0.927 lbs

**ANSI NUMBER:** |32100, |32130, |32138, |32180

**LEAD TIME:** 4 working days (or less)

**AVAILABLE:** 158\_ is shipped from the Memphis, Ventura, Vancouver and

Toronto locations

**CROSS REFERENCE:** Hager 438S; NGP: 653; Zero: 102A

#### **INSTRUCTIONS, CAD DRAWINGS, PROFILE DRAWINGS and CUT SHEET**

Available upon request and on website

# 

# Product Approvals /Ratings:

- ADAAG-1998

   (Amended); ICC/ANSI
   A117.1 and California

  Building Code, Title 24 for Barrier-Free Entry.
- Category J gaskets for use with listed steel frames and/or classified steel covered composite, hollow metal doors rated up to and including 3 hours; wood and plastic covered composite doors rated up to and including 1-1/2 hours; and wood core doors rated for 20 minutes.







#### www.pemko.com