Architectural **Door Accessories**



Experience a safer and more open world

Available Finishes

Rockwood 111 - Door Pull

US28/628 333/710 335/71 US38/63 US3/630 US3/630 US3/612 US3		Finisnes:
I '' dia.Specifications:CTC: 10'MATERIA! Aluminum, Brass, Bronze, Stainless SteelOVERALL: 11''FASTENER: 1/4'-20 x 2 1/4' thru bolt & finish washer (standard 1 3/4" door)BASE: 1'FOPTIONS: • Back to back mounting in pairs – use BTB suffix and mounting type number (111BTB5) • Concealed mounting single pulls – use C suffix and mounting type number (111BTB5) • Concealed mounting single pulls – use C suffix and mounting type number (111BTB5) • Advise if door thickness is other than 1 3/4"REIGHT: 3 '/j''Heavy duty versions of most fastening types available - use suffix HD to fastening type number (111BTB5HD) • Mounting selections for standard duty 1/4*-20 can be viewed at www.rockwoodmfg.com • 2 1/2* Barrier Free clearance – use BF prefix (BF111)WEIGHT: 3.5 lbs.		 313/710 315/711 US3/605 US4/606 US10/612 US10B/613 US10BE/613E US26/625 US26D/626 US32D/630 US32DMS US32D316 US32316
Specifications:10°MATERIAL: Aluminum, Brass, Bronze, Stainless SteelOVERALL: 11°FASTENER: 1/4°-20 x 2 1/4° thru bolt & finish washer (standard 1 3/4° door)BASE: 1°CPTIONS: • Back to back mounting in pairs — use BTB suffix and mounting type number (111BTB5) • Concealed mounting single pulls — use C suffix and mounting type number (111C6) • Advise if door thickness is other than 1 3/4° • Heavy duty versions of most fastening types available - use suffix HD to fastening type number (111BTB5HD) • Mounting selections for standard duty 1/4°-20 can be viewed at www.rockwoodmfg.com • 2 1/2° Barrier Free clearance — use BF prefix (BF111)Nost A156 6: 1401		
Aluminum, Brass, Bronze, Stainless Steel11"FASTENER: 1/4"-20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)BASE: 1"OPTIONS: • Back to back mounting in pairs — use BTB suffix and mounting type number (111BTB5) • Concealed mounting single pulls — use C suffix and mounting type number (111C6) • Advise if door thickness is other than 1 3/4" • Heavy duty versions of most fastening types available - use suffix HD to fastening type number (111BTB5HD) • Mounting selections for standard duty 1/a"-20 can be viewed at www.rockwoodmfg.com • 2 1/2" Barrier Free clearance — use BF prefix (BF111)WEIGHT: 3.5 lbs.	Specifications:	
1/4"-20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door) 1" PROJECTION: OPTIONS: • Back to back mounting in pairs — use BTB suffix and mounting type number (111BTB5) PROJECTION: • Concealed mounting single pulls — use C suffix and mounting type number (111C6) Advise if door thickness is other than 1 3/4" • Heavy duty versions of most fastening types available - use suffix HD to fastening type number (111BTB5HD) WEIGHT: • Nounting selections for standard duty 1/4"-20 can be viewed at www.rockwoodmfg.com 3.5 lbs. • 2 1/2" Barrier Free clearance — use BF prefix (BF111) ANSI A156 6: 1401		
OPTIONS: 3 1/2" • Back to back mounting in pairs — use BTB suffix and mounting type number (111BTB5) CLEARANCE: • Concealed mounting single pulls — use C suffix and mounting type number (111C6) CLEARANCE: • Advise if door thickness is other than 1 3/4" 2" • Heavy duty versions of most fastening types available - use suffix HD to fastening type number (111BTB5HD) WEIGHT: • Mounting selections for standard duty 1/4"-20 can be viewed at www.rockwoodmfg.com 3.5 lbs. • 2 1/2" Barrier Free clearance — use BF prefix (BF111) ANSI A156.6: 1401		
 Concealed mounting single pulls – use C suffix and mounting type number (111C6) Advise if door thickness is other than 1 ³/₄" Heavy duty versions of most fastening types available - use suffix HD to fastening type number (111BTB5HD) Mounting selections for standard duty ¹/₄"-20 can be viewed at www.rockwoodmfg.com 2 ¹/₂" Barrier Free clearance – use BF prefix (BF111) ANSI A156.6: 1401 		
 Mounting selections for standard duty ¹/₄"-20 can be viewed at www.rockwoodmfg.com 2 ¹/₂" Barrier Free clearance — use BF prefix (BF111) ANSI A156.6: 1401 	 Concealed mounting single pulls — use C suffix and mounting type number (111C6) Advise if door thickness is other than 1 ³/4" 	
NOTE: Pull projection is 3 1/2" for stainless steel and 3" for aluminum, brass and bronze.	$ullet$ Mounting selections for standard duty $^{1/4}$ "-20 can be viewed at www.rockwoodmfg.com	
	NOTE: Pull projection is 3 $1/2$ " for stainless steel and 3" for aluminum, brass and bronze.	ANSI A156.6: J401

ASSA ABLOY Opening Solutions Architectural Accessories Group Rockwood, PA P: 800.458.2424 • F: 800.922.9212 www.assaabloydooraccessories.us

Copyright © 2019-2021, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.