

# Rockwood 2845

## Combination Flush Bolt Set

Experience a safer  
and more open world



NOTE: UL for metal  
door application

### SPECIFICATIONS:

#### MATERIAL:

Brass, Stainless Steel

NOTE: There are ferrous and non-ferrous components within the material composition of the product.

#### FASTENERS:

18 ea. #8 x 3/4" Flat Head Combo Screws, 2 ea. #6-8 Plastic Anchors

#### FEATURES:

##### Top Bolt:

- Automatically engages when the inactive door closes. When the active door is opened, the inactive door stays latched at the top until the top bolt is released by pressing the plunger button on the bolt face.

##### Bottom Bolt:

- Non-handed
- Low closing force
- Fully automatic—opening active door retracts bottom bolt
- Override feature prevents damage to door or bolt if bolt head is blocked from entering strike
- Bolt head rod is adjustable up to 3/4"
- Thermal lock automatically locks the inactive door under high heat conditions due to fire

### AVAILABLE FINISHES:

- US3/605
- US4/606
- US10/612
- US10B/613
- 10BE/613E
- US26/625
- US26D/626
- US32D/630
- BSP (Black Suede Powder Coat)
- WSP (White Suede Powder Coat)
- Stock Powder Coats

Size: 1" x 6 3/4"

Weight: 2.4 lbs.

ANSI A156.3: Type 27

Rockwood Manufacturing Company  
300 Main St.  
Rockwood, PA 15557  
www.rockwoodmfg.com  
1 800 458 2424

Copyright © 2019-2022, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited. Printed in the U.S.A.