


Rockwood 2905

Self Latching Bolt

Top Bolt Only

Experience a safer
and more open world



SPECIFICATIONS:

MATERIAL:

Brass, Stainless Steel

NOTE: There are ferrous and non-ferrous components within the material composition of the product.

FASTENERS:

4 ea. #8 x 3/4" Flat Head Combo Screws, 2 ea.

#8-32 x 1/2" Flat Head Machine Screws, 3 ea.

#10 x 1" Flat Head Wood Screws. Note: *No plastic anchor required.*

FEATURES:

- For Wood Doors labeled B, C, D & E up to 4'w x 8'h
- Automatically engages when the inactive door closes. When the active door is opened, the inactive door stays latched at the top until the top bolt is released by pressing the plunger button on the bolt face.
- UL Listed

AVAILABLE FINISHES:

- US3/605
- US4/606
- US10/612
- US10B/613
- 10BE/613E
- US26D/626
- US32D/630
- US32/629
- BSP (Black Suede Powder Coat)
- WSP (White Suede Powder Coat)
- Stock Powder Coats

Size: 1" x 8 1/2"

Weight: 1.5 lbs.

ANSI A156.3: Type 27

Rockwood Manufacturing Company
300 Main St.
Rockwood, PA 15557
www.rockwoodmfg.com
1 800 458 2424

Copyright © 2019-2022, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited. Printed in the U.S.A.