

Rockwood 2942

Automatic Flush Bolt Set

Experience a safer
and more open world



SPECIFICATIONS:

MATERIAL:

Brass, Stainless Steel

NOTE: There are ferrous and non-ferrous components within the material composition of the product.

FASTENERS:

12 ea. #8 x 3/4" Flat Head Combo Screws

4 ea. #8-32 x 1/2" Flat Head Machine Screws

6 ea. #10 x 1" Flat Head Wood Screws

2 ea. #6-8 Plastic Anchors

FEATURES:

- For wood doors
- Non-handed
- Fully automatic—opening active door retracts top and bottom bolts
- Low closing force
- Override feature prevents damage to doors or bolts if bolt heads are blocked from entering strikes
- Bolt head rods are adjustable up to 3/8"
- Thermal lock automatically locks the inactive door under high heat conditions due to fire
- UL Listed

AVAILABLE FINISHES:

- US3/605
- US4/606
- US10/612
- US10B/613
- 10BE/613E
- US26/625
- US26D/626
- US32D/630
- BSP (Black Suede Powder Coat)
- WSP (White Suede Powder Coat)
- Stock Powder Coats

Size: 1" x 8 1/2"

Weight: 2.9 lbs.

ANSI A156.3: Type 25

OPTION:

Can be used with the No. 570 Dust Proof Strike

Rockwood Manufacturing Company
300 Main St.
Rockwood, PA 15557
www.rockwoodmfg.com
1 800 458 2424

Copyright © 2019-2022, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited. Printed in the U.S.A.