

Rockwood 2945

Combination Flush Bolt Set

Experience a safer
and more open world



SPECIFICATIONS:

MATERIAL:

Brass, Stainless Steel

NOTE: There are ferrous and non-ferrous components within the material composition of the product.

FEATURES:

- For wood doors
- Can be used with the No. 570 Dust Proof Strike
- UL Listed

Top Bolt:

- Automatically engages when the inactive door closes. When the active door is opened, the inactive door stays latched at the top until the top bolt is released by pressing the plunger button on the bolt face.

Bottom Bolt:

- Non-handed
- Low closing force
- Fully automatic—opening active door retracts bottom bolt
- Override feature prevents damage to door or bolt if bolt head is blocked from entering strike
- Bolt head rod is adjustable up to $\frac{3}{8}$ "
- Thermal lock automatically locks the inactive door under high heat conditions due to fire

FASTENERS:

10 ea. #8 x $\frac{3}{4}$ " Flat Head Combo Screws; 4 ea. #8-32 x $\frac{1}{2}$ " Flat Head Machine Screws; 6 ea. #10 x 1" Flat Head Wood Screws; 2 ea. #6-8 Plastic Anchors

AVAILABLE FINISHES:

- US3/605
- US4/606
- US10/612
- US10B/613
- 10BE/613E
- US26/625
- US26D/626
- US32D/630
- BSP (Black Suede Powder Coat)
- WSP (White Suede Powder Coat)
- Stock Powder Coats

Size: 1" x 8 $\frac{1}{2}$ "

Weight: 2.9 lbs.

ANSI A156.3: Type 27

Rockwood Manufacturing Company
300 Main St.
Rockwood, PA 15557
www.rockwoodmfg.com
1 800 458 2424

Copyright © 2019-2022, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited. Printed in the U.S.A.