

Rockwood 2948

Automatic Flush Bolt

With Bottom Fire Bolt for Wood Doors

Experience a safer
and more open world



SPECIFICATIONS:

MATERIAL:

Brass, Stainless Steel

NOTE: There are ferrous and non-ferrous components within the material composition of the product.

FEATURES:

- Non-handed
- Low (5 lbs. maximum) closing force
- Fully automatic; opening active door retracts top bolt
- Override feature prevents damage to doors or bolt if bolt head is blocked from entering strike
- Bolt head rod is adjustable up to 1/2"
- For fire rated UL listed 20-minute wood core and composite doors up to 4'w x 9'h
- Thermal lock automatically locks the inactive door under high heat conditions due to fire
- Bottom fire bolt eliminates need for floor prep
- Oversize fire bolt strike hole allows for slight door misalignment
- UL Listed

FASTENERS:

8 ea. #8 x 3/4" Flat Head Combo Screws; 2 ea. Plastic Anchors;
3 ea. #10 x 1" Flat Head Wood Screws.

AVAILABLE FINISHES:

- US3/605
- US4/606
- US10/612
- US10B/613
- 10BE/613E
- US32/629
- US32D/630
- BSP (Black Suede Power Coat)
- WSP (White Suede Powder Coat)
- Stock Powder Coats

Size:

Top Bolt: 1" x 8 1/2"

Bottom Bolt: Ø 13/16"

Weight: 1.6 lbs.

Rockwood Manufacturing Company
300 Main St.
Rockwood, PA 15557
www.rockwoodmfg.com
1 800 458 2424

Copyright © 2019-2022, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited. Printed in the U.S.A.