

Rockwood 2962

Automatic Flush Bolt Set

Experience a safer
and more open world



SPECIFICATIONS:

MATERIAL:

Brass, Stainless Steel

NOTE: There are ferrous and non-ferrous components within the material composition of the product.

FASTENERS:

8 ea. #8 x 1" Flat Head Sheet Metal Screws; 8 ea. #8 x 3/4" Flat Head Combo Screws; 4 ea. Plastic Anchors.

FEATURES:

- Durable, tested over 1 million cycles
- Smaller profile adds stability to the door
- Only two 1 1/8" diameter holes for easier door preparation
- Preparation prevents the veneer from splitting at the corners of the door
- Quiet & smooth activation
- Fully automatic; opening active door retracts top & bottom bolts
- Non-handed
- Override feature prevents damage to doors or bolt if bolt head is blocked from entering strike
- Low (3 lbs. maximum) closing force. ADA Compliant.
- Adjustable Bolt Head Rods: bolts can be vertically adjusted 1/2" for unusual clearances
- For up to 4'w x 9'h fire rated wood core & composite doors up to 1 1/2 hours fire rating
- UL Listed

AVAILABLE FINISHES:

- US3/605
- US4/606
- US10/612
- US10B/613
- 10BE/613E
- US32/629
- US32D/630
- BSP (Black Suede Power Coat)
- WSP (White Suede Powder Coat)
- Stock Powder Coats

Face Plate Size: 1 1/8" x 2 1/4"

Weight: 1.7 lbs.

Rockwood Manufacturing Company
300 Main St.
Rockwood, PA 15557
www.rockwoodmfg.com
1 800 458 2424

Copyright © 2019-2022, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited. Printed in the U.S.A.