Architectural Door Accessories



Experience a safer and more open world

Rockwood 585-12 - 12" Surface Bolt



Available Finishes:

∕!\WARNING

This product can expose you to

lead which is known to the state

of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65warnings.ca.gov.

Specifications:

MATERIAL:

Steel

Bolt: 4 ea. 1/4"-20 x 2 1/4" Flat Head Machine Screws; 4 ea. 1/4"-20 x 1 5/8" Sex Bolts Strikes: 2 ea. #14 x 2 1/2" Flat Head Sheet Metal Screws, 2 ea. Plastic Anchors; 2 ea. $\frac{1}{4}$ "-20 x 1" Flat Head Machine Screws, 2 ea. $\frac{1}{4}$ "-20 Anchors

- UL listed for use on inactive leaf of a pair of 3-hour labeled fire doors
- Includes a universal top strike and a mortise bottom strike
- Locks in both the up and down position
- Bolt locks automatically when thrown; can be released only by pressing knob toward door while retracting
- Can be used on any type of door
- Accommodates padlock



ASSA ABLOY Opening Solutions Architectural Accessories Group Rockwood, PA Phone: (800) 458-2424 • Fax: (800) 922-9212 www.assaabloydooraccessories.us