

Rockwood K1050

Metal Kick Plate

.050" Thick

Experience a safer
and more open world



SPECIFICATIONS:

MATERIAL:

.050" Aluminum, Brass,
Bronze, Stainless Steel

FASTENERS:

#6 x 5/8" Oval Head Sheet
Metal Screws

FEATURES:

- Push Side Plate Width - 2" less than door width.
- Pull Side Plate Width - 1 1/2" less than door width.
- All Edges come Beveled.

ORDERING:

Specify height x width x finish code. Add any options.

OPTIONS:

- SA - self-adhesive mounting
- TEK - self-drilling screws
- Heavy bevel available, specify HVBEV
- CSK - countersunk holes
- Cutouts for locks, louvers, or windows
- TORX - security torx screws

NFPA 80 STANDARDS - 2-4.5 Protection Plates: Factory-installed protection plates shall be installed in accordance with the listing of the door. Field-installed protection plates shall be labeled and installed in accordance with their listing.

Exception: Labeling is not required where the top of the protection plate is not more than 16 in. (406 mm) above the bottom of the door.

NOTE: Finishes US26/625 and US26D/626 are only available up to 24"H.

AVAILABLE FINISHES:

- US3/605
- US4/606
- US9/611
- US10/612
- US10B/613
- US10BE/613E
- US26/625
- US26D/626
- US28/628
- US32/629
- US32D/630
- US32D316
- US32DMS
- BSP
(Black Suede Powder Coat)
- WSP
(White Suede Powder Coat)
- Stock PC's

Weight: 8" x 34" = 4.0 lbs.

ANSI:

- J101 - metal armor plate
- J102 - metal kick plate
- J103 - metal stretcher & mop plate

Rockwood Manufacturing Company
300 Main St.
Rockwood, PA 15557
www.rockwoodmfg.com
1 800 458 2424

Copyright © 2019-2021, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited. Printed in the U.S.A.