

Healthcare Hardware




HP Series Bored Lock with Push/Pull ALP Trim


Healthcare Hardware

SARGENT ASSA ABLOY

HP Bored Lock with Push/Pull Trim

The HP Series Bored Lock with ALP push/pull trim provides an aesthetically- pleasing alternative to standard push/pull products. Ease of operation allows its use in many environments, including healthcare and education. The paddle shape and location create a comfortable target for door activation without using hands.







Features

- Paddle trim can be mounted in horizontal (up or down) or vertical (sideways) orientations in the field
- Easy installation
- 15 function trim is non-handed; lockbody is easily field reversible
- Through-bolted trim for stability
- Available in 2-3/4", 5" or 7" backsets
- UL Fire Rating standard
- Torx® and spanner screws optional with ALP
- Lead lining is optional: specify 74- option
- Covers and paddles are cast stainless steel
- Finish: 32D
- Patent pending and/or patent www.assaabloydss.com/patents

How To Order

SG-	HP	U65	ALP	32D	RHR
Option	Series	Function	Trim	Finish	Hand
Mechanical Options this page	HP Series Bored Locks	U15 - Passage U65 - Privacy	Push/Pull Trim	32D	RHR
					LHR
					RH
					LH

Always specify hand of lock

- 15 function is Non-Handed
- 5" Backset standard with square corner front, 2-1/4" x 1-1/8"

Series and Function	Descriptions	
HPU15 Passage	- Both paddles retract latch - Ideal for patient rooms and closets	
HPU65 Privacy	- I/S paddle always retracts latch - O/S paddle retracts latch, except when locked by inside push button - Closing door unlocks outside paddle - Includes emergency release - Ideal for bathrooms - Vertical orientation required	

Specifications

Door Thickness	1-3/4" (44mm) to 1-7/8" (47mm) standard; for doors greater than 1-7/8" (47mm) to 2-1/4" (57mm), specify 31- and door thickness (For thicker doors, consult factory)				
Backset	5" (127mm) standard. For 2-3/4" (70mm) backset (specify as 24-HP) and 7" (177mm) backset (specify as 26-HP) available on order				
Strike	2-3/4" (70mm) ANSI A115.2 curved lip strike # 800				
Bolt	Brass, 1/2" (13mm) throw				
Hand	Specify hand (RHR, RH, LHR or LH)				
Escutcheons	Cast stainless steel				
UL Listed	UL Listed for use on fire doors (4x10 opening)				
Options	Backsets	24-	2-3/4" (70mm) backset		
		26-	7" (177mm) backset		
	Strikes	14-	505 Full Lip Strike		
		28-	4-7/8" (124mm) ANSI curved lip strike # 808		
		WBS-	Wrought Box Strike		
	Thick Doors	31-	For doors thicker than 1-7/8" to 2-1/4"; specify 31- and door thickness		
	Security Screws	36-	6-Lobe Security Head Screws		
		37-	Spanner Security Head Screws		
	Lead Lining	74-	Lead lined		
	Antimicrobial Coating	SG-	MicroShield® – Antimicrobial clear powder coat (only available with 32D finish)		
	Markers	P-	Push/Pull Paddle Identification (non-handed)		
Finishes	32D For other finishes consult factory				
Finish Protection	CPC-		Clear Powder Coat		
Door Prep	ANSI A115.1 modified per SARGENT standard bored template 4695				
	· · · · · · · · · · · · · · · · · · ·				