



800/801 Series

Remote and local monitoring stations



800 Series

Local and remote monitoring station

The 800 Series monitoring stations can provide monitoring for a single zone with choice of audible or visual monitoring.

801 Series

Local and remote monitoring station

The 801 unit includes an audible and visual indication of lock status and delay activation. Interfaces with electromagnetic locks with magnetic bond sensor (MBS) option. Unit mounts in a standard single gang electrical box.

The 801-KS fulfills a code requirement stating that a local signal assures users that a delayed egress system is functional. The unit includes an audible and visual indication of lock status and delay activation. Provides a Single Pole, Double Throw (SPDT) momentary x SPDT maintained contact arrangement keyswitch for legal release and reset of the system, which interfaces with a standard 1 1/4" mortise cylinder with standard straight cam. Option to interface with electromagnetic locks with Magnetic Bond Sensor (MBS). Unit mounts in a standard double gang electrical box.

Features and benefits

- 800 Series local and remote monitoring stations
 - 800L1 with one LED indicator (red, green or amber)
 - 800L2 with two LED indicators (red, green or amber) (photo)
 - 800A horn monitor, 70 dB @ 2 ft
- 801 Series local and remote monitoring stations
 - 801 with three LED indicators and horn monitor, 70 dB @ 2 ft
 - 801KS with LED indicators, horn monitor and keyswitch (photo)

800 specifications

LED Operating power	12-24 VDC
LED current draw	3-14 mA ea.
Audible input	10-28 VDC
Audible current draw	3-14 mA
Decibel rating	70 dB @ 2 ft
Single gang unit	
Width	2 3/4"
Depth	1 1/8"
Height	4 1/2"
Finish	Stainless steel
800L1	One (1) LED Indicator - red, green, and amber
800L2	Two (2) LED Indicators - red, green, and amber
800A	Audible sounder

801 specifications

LED Operating power	12-24 VDC
LED current draw	3-14 mA ea.
Audible input	10-28 VDC
Audible current draw	3-14 mA
Decibel rating:	70 dB @ 2 ft
Single gang unit	
801* Local or remote monitoring system	
Width	2 3/4"
Depth	1 1/8"
Height	4 1/2"
Finish	Stainless steel
Double gang unit	
801-KS* local or remote monitoring system with keyswitch (less cylinder)	
Width	4 9/16"
Depth	1 15/16"
Height	4 1/2"
Finish	Stainless steel
Keyswitch contacts	5 Amp @ 30 VDC

*Note: 801/801-KS requires MBS on locking device.

Allegion, the Allegion logo, Schlage, and the Schlage logo are trademarks of Allegion plc, its subsidiaries and/or affiliates in the United States and other countries. All other trademarks are the property of their respective owners.

About Allegion

Allegion (NYSE: ALLE) is a global pioneer in seamless access, with leading brands like CISA®, Interflex®, LCN®, Schlage®, SimonsVoss® and Von Duprin®. Focusing on security around the door and adjacent areas, Allegion secures people and assets with a range of solutions for homes, businesses, schools and institutions. Allegion had \$2.9 billion in revenue in 2019 and sells products in almost 130 countries. For more, visit www.allegion.com

KRYPTONITE ■ LCN ■  ■ STEELCRAFT ■ VON DUPRIN



© 2020 Allegion
005007, Rev. 09/20
www.allegion.com/us