## STAINLESS SLIMLINE VISION KITS FOR 3/16-1/4" GLASS: VSLS

Low Profile Beveled Vision Lite For Fire Rated Doors.
Self-Attaching Frame Has Single-side fasteners for Glass 3/16" to 1/4"

## **SPECIFICATIONS:**

| Material:                              | 20 Gauge Stainless Steel #4 Finish. frame. Min Size 3" x 3", Max 60" x 104". See Fire Rating Below.   |  |  |
|--|---|--|--|
| Construc-<br>tion:                     | 1-1/4" trim with radius corners, mitered and welded. Continuous glass retainer, countersunk mounting holes in the bevel on non-corridor side.   |  |  |
| Door:                                  | For 1-3/4" door. For other sizes, see models VLFIG and VLFEZIG.  Door cutout = order size.  |  |  |
| Fasteners:                             | #8 x 1" flathead phillips stainless SMS.  |  |  |
| Glass:                                 | 3/16"- 1/4" glazing to be ordered separately from <b>Glazing Section</b> of catalog. Use fire rated glazing with Warnock Hersey (WHI) or UL classification markings for fire rated applications. Visible light is 2" under rough opening size. <u>Glass size is 1" under order size</u> . <u>Fire-Rated Air Louvers Glazing to fit this Product: WS, KFRF, PPF and PYRO</u> . |  |  |
| Fire-Rating,<br>Testing &<br>Listings: | When installed in properly rated and approved door, ratings up to 3 hours can be achieved, <b>depending on the glazing used</b> . See glazing ratings for max exposed area. Tested and Listed for UL 10C and Criteria of UBC 7-2 Positive Pressure. See detailed installation instructions.   |  |  |
|  | , COU.  |  |  |





## **OPTIONS AT ADDITIONAL COST:**

| PAK:                     | Includes Vision Lite, Glass Sized to Fit, Applied Glazing tape for UL10B Installations, Securely Packaged Individually. <b>See First Page in Vision Lite Catalog to order.</b> |  |
|--------------------------|--|--|
| UBC 7-2<br>Installation: | Additional intumescent tape for Positive Pressure UL10C 20 minute combustible core wood doors installation. See detailed installation instructions.                            |  |
| Fasteners:               | Torx Other:  |  |
| Mullions:                | Factory welded to vision lite & painted. See Mullions Page in this section to order.   |  |
| Privacy<br>Screen:       | Add the New Privacy Screen to This Vision Lite—See Web Page for Details  |  |
| Custom:                  | Smaller or larger size or other options; Contact Customer Service for special orders.  |  |

|   |       |          | ]<br>1-1/-<br>1   | 4"   |
|---|-------|----------|---|--|
|   | 7     |          | R Size  |  |
|   | 7     |          | -VISIBLE LIGHT = 2" UNDER ORDER SIZE<br>- GLASS = 1" UNDER ORDER SIZE | ORDER SIZE = DOOR CUTOUT<br>1-3/8" OVER ORDER SIZE |
|   | 11111 |          | —VISIBLE LIGHT:<br>— GLASS = 1"                                       | - ORDER SIZE<br>- 1-3/8" OV                        |
|   | 1     | <b>\</b> | +   |  |
| م |       | <u> </u> | 7.1   | _  |

| Order Format: VSLS | W | Н | Example: VSLS 1212 |  |
|--------------------|---|---|--------------------|--|
|--------------------|---|---|--------------------|--|

Interpretation of Fire and Building Codes May Vary. Consult with the Local Authority Having Jurisdiction (AHJ) to determine appropriate standards.

| → AIR                       |
|-----------------------------|
| LÖÜVERS                     |
| ACTIVAR <sub>INC.</sub>     |
| construction products group |

|   | Distributor: | Width:x Height:  |
|---|--------------|------------------|
|   | Architect:   | Quantity:        |
|   | Contractor:  | Model:           |
| 7 | Project:     | Date: 10/25/2017 |

800-554-6077 QUOTES@ACTIVARCPG.COM ORDERS@ACTIVARCPG.COM SALES@ACTIVARCPG.COM FAX: 952-835-2218