



- ADA Compliant
- Color – Linen **Bradex**®

Product Materials

FRAME: satin finish stainless steel; 18 gauge 1" diameter tubing with 1½" HDPE support bars.
MOUNTING FLANGES: 7 gauge satin finish stainless steel with three mounting holes provided in each flange for installation.
LOWER SUPPORT BRACKET: 16 gauge satin finish stainless steel.
SEAT: 1" thick high-density polyethylene. Linen cobblestone textured finish. All exposed edges are machined smooth. Reversible in field to be right or left hand.

Operation

Hinged seat folds up and out of the way when not in use. When properly installed, seat can support up to 250 lbs. – static load.

Installation

Verify all rough-in dimensions prior to installation. Provide concealed backing or anchors as specified by architect before finished wall is applied. Secure to wall with mounting screws (not included) at holes provided. Locate mounting holes at appropriate height above finished floor to meet seat height requirement. Secure lower support bracket to wall at appropriate location. Seat is reversible, may be made into a right hand seat. Mounting kit available from Bradley. For more information, visit bradleycorp.com.


⚠ WARNING: Be sure to use reinforced backing behind wall where mounting screws or anchoring devices are installed to ensure adequate support for the shower seat. All anchoring devices (supplied by installer) must be appropriate for specific wall construction. Severe personal injury and/or property damage may result from improper mounting.

Guide Specification

Reversible folding linen Bradmar shower seat shall be 1" thick high-density polyethylene. Secured to the frame of 18 gauge, 1" diameter tubing, and 1½" HDPE support bars. Support leg contained in 16 gauge lower support bracket. Shower seat must meet or exceed ADA guidelines.
Overall dimensions: 34½"W x 22"D x ½" thick.

ADA Compliant

- Consult local and national accessibility codes for proper installation guidelines.
- Conformity and compliance to local and national codes is the responsibility of the installer.



Orders composed of products indicated as **Bradex**® will be available to ship in three days after receipt of order at the factory. There is no pricing penalty for this service from Bradley.