

Alarm Lock: Advanced multi-purpose door alarms

The PG21MS Series includes advanced narrow-stile microprocessor-controlled door alarms for surface mounting on a door or door frame. Typical applications include emergency fire escape doors, nursing home stairwell doors, rear restaurant and theater doors.

Advanced new features:

- New designer look
- Two selectable arming options
- Always armed mode – when key is turned counterclockwise to the disarm position, the key cannot be removed. To remove key, turn back to arm mode, thus keeping unit armed always.
- Standard arming mode – when key is inserted turning clockwise will disarm and key can be removed. Turning key clock will arm and key can be removed.
- Status Indicator – RED when armed.
- Entry/Exit delay time options – 15 seconds, 1 min 15 seconds & 3 min 15 seconds
- Key-controlled delivery mode. Door may be propped open, using key to enable authorized users to use door w/o sounding an alarm, eg., permitting scheduled delivery, etc.
- Door ajar/propped open mode. Jumper-selectable door-open detection period. If door is ajar, ie., propped open, following a period from 15 seconds to 3 minutes, the alarm will sound.
- Self-contained and dual-tamper supervised
- Convenient *No-Cut* jumpers
- Improved sweeping siren over 95db
- Visual magnetic alignment mode, eliminates templates
- Long-life 9V battery powered (supplied); Low battery alert.
- Strobe version for audible and visual *door in alarm* identification (shown above).

Non-strobe version also available with new and improved features (inset photo).

Model PG30:

Keypad-controlled narrow stile door alarm, similar to PG21, plus:

- Digital codes for master, management and passage (used for auto-arming)
- 3 security levels for: a) high security b) unattended applications c) flexible control for delivery doors, etc.
- Audible low battery warning
- 3 Programmable 95db siren styles: sweep, pulsed, and steady
- Logo key is dual function test button

PGKPD Accessory:

- For optional use with the PG30, this low-profile, brushed aluminum finished accessory provides all functions of the PG30 from the outside of the door. (Available in metallic silver only.)



Model PG10

- The Pilfergard Model PG10 is an exit door alarm designed to deter the use of the secured door by sounding a twin action alarm when opened by unauthorized personnel. The alarm can be bypassed from inside or outside by the use of a key. (Requires standard mortise cylinder not supplied.) This durable surface mount unit is easily installed and is tamper-supervised with two separate tamper switches. Its test button verifies battery. Optional AC power supply available.



Model LL1

- All of the features of the PG10 unit with addition of a flashing strobe for easy alarm identification.
- Choice of system controllers

