


1850

Welding - Plain Bearing
- Heavy Weight



Notes:

- Bulk packed loose - 10 per box

PRODUCT SPECIFICATIONS

DESCRIPTION:

- ANSI K81081F
- Plain bearing
- Heavy weight
- Flat surface with no swage
- No holes
- Fast riveted pin
- Square corners
- Manufactured with no holes and can easily be welded onto gates, dumpsters, and industrial applications such as bins or warehouse doors

MATERIAL:

- Steel
- Riveted Steel Pin

FINISH:

- PS Plain Steel

PRODUCT SIZE OPTIONS

HINGE SIZE	GAUGE OF METAL	PIN DIAMETER
4 x 4"	.180	.312
4 1/2" x 4 1/2 "	.180	.322
5" x 5"	.180	.322
6" x 6"	.203	.500

HINGE SIZE (INCHES)	HINGE SIZE (MM)	RECOMMENDED MAX DOOR WEIGHT (LBS)	DOOR THICKNESS	MAX DOOR WIDTH
4 x 4	102 x 102	150	1-3/8" (35 mm) to 1-3/4" (45 mm)	36" (91 cm)
4-1/2 x 4-1/2	144 x 114	150	1-3/4" (45 mm) to 2" (51 mm)	36" (91 cm)
5 x 5	127 x 127	175	1-3/4" (45 mm) to 2-1/2" (64 mm)	42" (107 cm)
6 x 6	152 x 152	230	1-3/4" (45 mm) to 2-1/2" (64 mm)	48" (122 cm)

DOOR HEIGHT	NUMBER OF HINGES - DOOR WIDTH < 37"	NUMBER OF HINGES - DOOR WIDTH 37" TO 48"
Up to 60" (152 cm)	2	3
60" (152 cm) to 90" (229 cm)	3	4
90" (152 cm) to 120" (229 cm)	4	5