



VR910-NL with black grip
VR914-NL without black grip

- For use with Von Duprin 98/99 Series rim and vertical rod exit device
- Thru-bolts direct to the exit device
- Non-handed, horizontal keyway

Size

- 11 Gauge(0.120" thick)

Mounting

- For door thickness 1-3/4-2-1/4". 10-24 X 1" and 10-24 X 1-1/2" mounting screw size

Width	Height	Thru-bolt pattern (4 holes)	Clearance grip to door	Projection
5-1/4"	11"	1-3/8" wide x 7" high	1-1/2"	1-7/8"

Finishes

- Available in Stainless Steel US32D
- 304 Series Stainless Steel standard, exceeding industry standards for corrosion resistance. Recommended for external applications
- Models are available with or without attractive black plastisol edge grip
- *Custom finishes are available as engineering special, consult customer service*

Additional information

- 1-5/8" cylinder hole cut-out, centered on horizontal center line and 1/4" offset from vertical center line towards the lock side of the door
- Designed for use with 1-1/4" cylinders. Other cylinders may require additional blocking rings, not supplied
- Protective cylinder collar spins to reduce damage from pipe wrench or other tool.
- Comes with cylinder cup
- *Additional cut-outs and locations are available as engineering special, consult customer service*

A
Hinges & pivots

B54
Pulls & plates

C
Flush bolts & coordinators

D
Latches, catches & bolts

E
Stops

F
Exterior hardware

G
Miscellaneous hardware