

- Security door stops designed for use in high vandalism areas
- Molded from black flame resistant, resilient material around a heavy-duty stud
- Once grouted in concrete, leaves no exposed fasteners to be tampered with or removed
- Ideal for jail or security cell areas where floor mounted stops are required
- FS18L also ideal for concrete wall applications

## Material substrate

Made from rubber

## Finishes

Black rubber

### Dimensions

Dimensions

**Dimensions** 

• Overall height: 1-5/16" Base diameter: 1-1/4"

• Overall height: 2-5/8"

Base size: 1-1/2" W x 2-3/4" L

- FS18S Height: 1-1/2"
- FS18S Diameter: 2"
- FS18S Stud length: 2-1/2"
- FS18L Height: 3-1/2"
- FS18L Diameter: 2"
- FS18L Stud length: 2-1/2"



FS18L

FS18S

## FS434 Floor stop

- For undercut doors up to 1-1/2"
- Packed with fasteners for light duty masonry and wood applications
- Soft, resilient black rubber

## Material substrate

Made from wrought steel

## Available accessory items

• Replaceable soft, resilient black rubber.

# **Finishes**

BHMA	Description	Substrate	Finish
604	Zinc Plated	Steel	US2C



## 430 Floor door stop

- For undercut doors up to 1-1/2".
- Welded wood screws for wood applications.
- White rubber tip

## Material substrate

• Made from cast brass and aluminum

- Available accessory items Replaceable white tips
- Black rubber tips

## Finishes - Brass

BHMA	Description	Substrate	Finish
605	Bright brass	Brass	US3
606	Satin brass	Brass	US4
609	Blackened brass	Brass	US5
613	Oil rubbed bronze	Brass	US10B
619	Satin nickel	Brass	US15
625	Bright chrome	Brass	US26
626	Satin chrome	Brass	US26D

## Finishes - Aluminum

BHMA	Description	Substrate	Finish
666	Bright brass	Aluminum	A3
	Blackened brass	Aluminum	A5
669	Bright nickel	Aluminum	A14
673	Aluminum clear coat	Aluminum	A92

For other colors, consult factory.