



349 Ball catch, dual adjustable - rounded corners

- Recommended for lower frequency opening applications
- For catch in door installations
- Radiused corners allow easy installation with a router
- Dual adjustment for door clearance and holding strength
- Lip strike is designed for use where strike is mounted in jamb
- Free rolling ball insures smooth, positive and trouble-free action
- Adjustable threaded barrel compensates for various door clearances
- Adjustable spring tension
- Rounded corners on strike lip for safety
- Units packed with wood screws

Certifications

- Meets ANSI/BHMA A156.9, B23013

Material substrate

- Made from wrought brass

Dimensions

- Face Plate: 1" wide x 2-1/8" high
- Bore: 7/8" diameter x 1-3/8" deep
- Strike: 1-3/8" wide x 2-1/8" high, lip to center- 7/8"

Finishes

| BHMA | Description | Substrate | Finish |
|----------|-------------------|-----------|----------|
| 605 | Bright brass | Brass | US3 |
| 606 | Satin brass | Brass | US3 |
| 609 | Blackened brass | Brass | US5 |
| 612 | Satin bronze | Brass | US10 |
| 613 | Oil rubbed bronze | Brass | US10B |
| 619 | Satin nickel | Brass | US15 |
| 625 | Bright chrome | Brass | US26 |
| 626 | Satin chrome | Brass | US26D |
| 643e/716 | Aged bronze | Brass | 643e/716 |
| 622 | Matte black | Brass | BLK |

For other colors, consult factory.



2 Elbow Catch

- Ideal for use on the inactive leaf of a pair of cabinet doors
- Surface applied, making installation simple
- Made from cast aluminum

Certifications

- Meets ANSI/BHMA A156.9 B33023

Dimensions

- Plate: 1-3/8" high x 5/8" wide
- Strike: 13/16" high x 5/8" wide

Finishes - Aluminum

| Ives Number | A3 | A5 | A14 | A15 | A92 | A716 |
|-------------|-----|----|-----|-----|-----|------|
| BHMA | 666 | | 669 | 670 | 673 | |

Hinges & pivots

A

Pulls & plates

B

Flush bolts & coordinators

C

Latches, catches & bolts

D17

Stops

E

Exterior hardware

F

Miscellaneous hardware

G