



RL36 Roller latch RL36A Roller latch

- Recommended light duty cabinet and closet applications
- Actuation is simple, closing of the door causes the roller to fall in the depression of the strike, thereby holding the door closed
- The projection of the roller is easily adjusted by turning slotted screw on back of latch
- Maximum projection of the roller is 5/16" allowing for variance in the door clearance
- Fits cylindrical lock cutout
- Nylon roller
- Non-handed
- Units packed with wood screws
- RL36A model packed with ASA strike

Certifications

Meets ANSI/BHMA A156.16, L57082

Material substrate

Made from stainless steel

Available accessory items

Strike—A—ASA

Finishes

ВНМА	Description	Substrate	Finish
630	Satin stainless	Stainless steel	US32D

For other colors, consult factory.





RL38 Roller latch

- Rim style roller latch
- Actuation is simple, closing of the door causes the roller to fall in the depression of the strike, thereby holding the door closed

Dimensions

- The projection of the roller is easily adjusted by turning slotted screw
- Maximum projection of the roller is 3/8" allowing for variance in the door clearance
- Nylon roller
- Non-handed
- Units packed with wood screws

Certifications

Meets ANSI/BHMA A156.16, L27092

Material substrate

Made from stainless steel

Finishes

i mones				
ВНМА	Description	Substrate	Finish	
630	satin stainless	Stainless steel	US32D	

For other colors, consult factory.

Dimensions

- Body: 1" wide x 2-1/4" high x 2" deep
- Strike: 1-1/8" wide x 2-3/4" high x 3/32"
 Thick, lip to center- 1-1/4"
- Optional ASA strike: 1-1/4" wide x 4-7/8" high x 3/32" thick, lip to center- 1-1/4"

Body: 1-3/8" wide x 2" high x 7/8" deep
Strike: 1" wide x 2-1/8" high x 3/8" deep