FS544



### FS455 4" Kick down holder

- Units provide simple hold and release, activated with a touch of the foot.
- Stainless steel spring
- Replaceable black non-marring rubber shoes have corrugated bottoms to provide secure grip. Rubber shoe is securely fastened with screw
- Shoes are easily replaced when worn
- Packed with fasteners for wood applications
- Door-to-floor clearances of 2" or less

### Certifications

Meets ANSI/BHMA 156.16, L11382 for brass and L31382 for aluminum

### Material substrate

Made from cast brass or aluminum

# Available accessory items

 Replaceable black non-marring rubber shoes

### **Dimensions**

- Door-to-floor clearance: 2" or less
- Plate height: 1-3/4"
- Plate width: 1-3/4"

### Finishes - Brass

BHMA	Description	Substrate	Finish
605	Bright brass	Brass	US3
606	Satin brass	Brass	US4
612	Satin bronze	Brass	US10
613	Oil rubbed bronze	Brass	US10B
619	Satin nickel	Brass	US15
622	Matte black	Brass	BLK
625	Bright chrome	Brass	US26
626	Satin chrome	Brass	US26D
	Aged bronze	Brass	643e/716

### Finishes - Aluminum

Satin aluminum	Aluminum	US28
Bright brass	Aluminum	US3AL
Blackened brass	Aluminum	US5AL
Satin bronze	Aluminum	US10AL
Clear satin aluminum	Aluminum	US27
	Bright brass Blackened brass Satin bronze	Bright brass Aluminum Blackened brass Aluminum Satin bronze Aluminum Clear satin aluminum Aluminum

For other colors, consult factory.

# FS544 4" Kick down holder FS555 5" Kick down holder

- Units provide an economical method to hold open doors.
- Stainless steel spring
- Replaceable grey non-marring rubber shoes have corrugated bottoms to provide secure grip. Rubber shoe is securely fastened with screw
- Shoes are easily replaced when worn
- Packed with fasteners for wood applications
- FS544 for door-to-floor clearances of 2" or less
- FS555 for door-to-floor clearances up to 3"

### Certifications

- FS544 Meets ANSI/BHMA 156.16, L11381
- FS555 Meets ANSI/BHMA 156.16, L11391

## Material substrate

Made from cast iron

## Available accessory items

 Replaceable grey non-marring rubber shoes

### Dimensions

FS544

- Door-to-floor clearance: 2" or less
- Plate height: 2-1/4"
- Plate width: 1-7/16"

### FS555

- Door-to-floor clearance: up to 3"
- Plate height: 2-1/4"
- Plate width: 1-7/16"

## Finishes

ВНМА	Description	Substrate	Finish
706	Brass painted	Iron	SP4
691	Bronze painted	Iron	SP10
689	Aluminum painted	Iron	SP28
695	Dark bronze painted	Iron	SP313
	Matte black	Iron	BLK

For other colors, consult factory.

