

IVES® Constant latching flush bolts – Wood doors



FB61P Top and bottom bolts (pair)

FB61T Top bolt only

- For use with wood doors only
- Constant latching—inactive door remains latched until the active door is opened, releasing the automatic bottom bolt and then the top bolt can be manually released. Inactive door will relatch automatically when door closes.
- Low actuation forces
- Non-handed.
- Bolt throw is 3/4" with a 7/8" vertical adjustment.
- Bolt backset is 3/4"

Certifications

- Meets ANSI A156.3 Type 27
- UL Listed 90 Min fire doors 8'0" X 8'0"

Mounting

- 8-32 X 3/8" UFPHMS
- 10-12 X1-1/4" Plastic anchor
- 6-32 X 3/8 FPHMS
- 6 X 3/4 FPHSMS
- 8 X 1 FPHSMS
- 10 X 1 FPHSMS

Dimensions

| Body size (Width X Length X Depth) | Guide size (Width X Length X Thickness) | Strike size (Width X Length X Thickness) | Rub plate size (Width X Length X Thickness) |
|---------------------------------------|--|---|--|
| 1" x 8-1/2" x 2" | 1" x 6" x 1/8" | 15/16" x 2-1/4" x 1/16" | 1-1/4" x 1-11/16" x 3/64" |

Finishes

| BHMA | Description | Substrate | US |
|------|------------------------|-----------------|-------|
| 605 | Bright brass | Brass | US3 |
| 606 | Satin brass | Brass | US4 |
| 612 | Satin bronze | Brass | US10 |
| 613 | Oil rubbed bronze | Brass | US10B |
| BLK | Matte black | Stainless steel | – |
| 629 | Bright stainless steel | Stainless steel | US32 |
| 630 | Satin stainless steel | Stainless steel | US32D |

Custom finishes are available as engineering special, consult customer service.

Available accessory items

- Security pin screws
- DP1 and DP2 dust proof strike, see page C16