

IVES® Constant latching flush bolts – Wood doors



FB61P Top and bottom bolts (pair)

FB61T Top bolt only

- For use with wood doors only
- Constant latching—inactive door remains latched until the active door is opened, releasing the automatic bottom bolt and then the top bolt can be manually released. Inactive door will relatch automatically when door closes.
- Low actuation forces
- Non-handed.
- Bolt throw is 3/4" with a 7/8" vertical adjustment.
- Bolt backset is 3/4"

Certifications

- Meets ANSI A156.3 Type 27
- UL Listed 90 Min fire doors 8'0" X 8'0"

Mounting

- 8-32 X 3/8" UFPHMS
- 10-12 X 1-1/4" Plastic anchor
- 6-32 X 3/8 FPHMS
- 6 X 3/4 FPHSMS
- 8 X 1 FPHSMS
- 10 X 1 FPHSMS

Dimensions

Body size (Width X Length X Depth)	Guide size (Width X Length X Thickness)	Strike size (Width X Length X Thickness)	Rub plate size (Width X Length X Thickness)
1" x 8-1/2" x 2"	1" x 6" x 1/8"	15/16" x 2-1/4" x 1/16"	1-1/4" x 1-11/16" x 3/64"

Finishes

BHMA	Description	Substrate	US
605	Bright brass	Brass	US3
606	Satin brass	Brass	US4
612	Satin bronze	Brass	US10
613	Oil rubbed bronze	Brass	US10B
BLK	Matte black	Stainless steel	—
629	Bright stainless steel	Stainless steel	US32
630	Satin stainless steel	Stainless steel	US32D

Custom finishes are available as engineering special, consult customer service.

Available accessory items

- Security pin screws
- DP1 and DP2 dust proof strike, see page C16