



8311 Pull plate

Certifications

- Meets ANSI A156.06

Mounting

- 1/4-20 mounting hardware
- Specify door thickness. Standard mounting hardware for door thickness of 1-1/2" to 1-3/4" unless otherwise specified. Optional package available for 2" and 2-1/4" thick doors.
- Comes standard with thru-bolt screws and decorative washers.
- Optional mounting hardware available (see general information section for details) F, G
- Mounting hardware for other door thicknesses are available as engineering special, consult customer service.
- Standard mounting package for plate
 - #6 X 5/8 oval head screws
- Optional TEK/TORX package
 - #6 X 5/8 Self-drilling, Self-tapping screws and
 - #6 X 5/8 Torx screws
- Plate prepped with 2 pull mounting holes spaced at 5-1/4" center to center

Widths and heights

- 3-1/2" X 15"
- 4" X 16"
- 6" X 16"

Pull center to center

- 5-1/4"

Finishes

- Available in Aluminum, Brass, and Stainless Steel substrates. See general information section for specific BHMA finish code, finish description, US finish code, and substrate information.
- Standard finishes available: 605, 606, 612, 613, 619, 625, 626, 626-AM, 628, 630, 630-AM, 643e/716, BLK
- Custom finishes are available as engineering special, consult customer service.

Additional information

- Specify PR when ordering a set of pulls for back to back mounting
- Custom widths, heights, and special cut-outs are available as engineering special, consult customer service.

A
Hinges & pivots

B4/5
Pulls & plates

C
Flush bolts & coordinators

D
Latches, catches & bolts

E
Stops

F
Exterior hardware

G
Miscellaneous hardware