



## 5BB1WT 5 Knuckle, ball bearing, wide throw full mortise hinge

- Recommended for medium weight doors (<150 lbs)
- Recommended for medium frequency usage (<400 cycles per day)
- Made with two ball bearing assemblies
- Recommended for use with a door closer
- Packed with fasteners for hollow metal and wood doors  
12-24 x 1/2 UFPHMS, 12 x 1 1/4 FPHWS

### Certifications

- Certified to ANSI/BHMA A156.1 for performance standards
- Meets ANSI/BHMA 156.7 for template hinge dimensions

### Material substrate

- 1040 steel

### Options

- NRP ..... Non-removable pin
- HT ..... Hospital tip
- SH ..... Security stud - comes standard with NRP
- RC-1/4, RC-5/8... Rounded corners
- SEC ..... Security fasteners - pin-in-socket
- TW4 ..... Four wire
- TW4M ..... Four wire with monitor
- TW8 ..... Eight wire
- TW8M ..... Eight wire with monitor
- MON..... Monitor

### Dimensions

Height x Width	Size (mm)	Gauge
4.5 x 5	114 x 127	0.134
4.5 x 6	114 x 152	0.134
5 x 6	127 x 152	0.146
5 x 7	127 x 178	0.146
5 x 8	127 x 203	0.146

Refer to General Hinge Information page to determine proper hinge for application

### 5BB1WT Finishes

BHMA	Description	Substrate	Finish
600	Primer paint	Steel	USP
631	Matte black	Steel	F-BLK
632	Bright brass	Steel	US3
633	Satin brass	Steel	US4
639	Satin bronze	Steel	US10
640	Oil rubbed bronze	Steel	US10B
641	Oxidized bronze	Steel	US10A
643	Blackened bronze	Steel	US11
646	Satin nickel	Steel	US15
651	Bright chrome	Steel	US26
652	Satin chrome	Steel	US26D
643e/716	Aged bronze	Steel	F-643e/716

For other colors, consult factory.