

COO-VAR®

PAINTS, PRIMERS AND SPECIALISED COATINGS

SAFETY DATA SHEET

204/WB101 - ANTI-GRAFFITI CLEAR GLAZE KIT - ACTIVATOR

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	204/WB101 - ANTI-GRAFFITI CLEAR GLAZE KIT - ACTIVATOR
Product number	204/WB101/TKIT - ACTIVATOR
UFI	UFI: FNMP-6223-300Y-13J9

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	HARDENER FOR TWO COMPONENT ANTI-GRAFFITI COATING
Uses advised against	NOT SUITABLE FOR FOR USE IN HOMEWORKER (DIY) APPLICATIONS

1.3. Details of the supplier of the safety data sheet

Supplier	COO-VAR Lockwood Street HULL UK HU2 0HN +441482328053 (T) +441482219266 (F) info@coo-var.co.uk	TEAL & MACKRILL EU B.V. Zandvoortstraat 69 1976 BN IJMUIDEN THE NETHERLANDS +441482328053 (T) +441482219266 (F) info@coo-var.co.uk
Contact person	Technical Department -, 08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri, as above	
Manufacturer	TEAL & MACKRILL LIMITED LOCKWOOD STREET HULL HU2 0HN +44(0)1482 320194(T) +44(0)1482 219266(F) info@teamac.co.uk	

1.4. Emergency telephone number

Emergency telephone	+44 (0) 1482 328053 Coo-Var (08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri)
SDS No.	10755

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards	Not Classified
Health hazards	Acute Tox. 4 - H332 Skin Sens. 1 - H317 STOT SE 3 - H335
Environmental hazards	Not Classified

Human health Contains non-volatile isocyanate. Heating may generate vapours which irritate the respiratory system. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

204/WB101 - ANTI-GRAFFITI CLEAR GLAZE KIT - ACTIVATOR

2.2. Label elements

Hazard pictograms



Signal word	Warning
Hazard statements	H332 Harmful if inhaled. H317 May cause an allergic skin reaction. H335 May cause respiratory irritation.
Precautionary statements	P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P261 Avoid breathing vapour/ spray. P280 Wear protective clothing, gloves, eye and face protection. P302+P352 IF ON SKIN: Wash with plenty of water. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P501 Dispose of contents/ container in accordance with national regulations.
Supplemental label information	RCH002a Restricted to professional users.
Contains	Hexamethylene diisocyanate oligomers, Isocyanurate, Hexamethylene diisocyanate, oligomers, HEXAMETHYLENE-DI-ISOCYANATE
Supplementary precautionary statements	P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P403+P233 Store in a well-ventilated place. Keep container tightly closed.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hexamethylene diisocyanate oligomers, Isocyanurate		30-60%
CAS number: 28182-81-2	EC number: 931-274-8	REACH registration number: 01-2119485796-17-0002
Classification	Classification (67/548/EEC or 1999/45/EC)	
Acute Tox. 4 - H332	Xn;R20. Xi;R37. R43.	
Skin Sens. 1 - H317		
STOT SE 3 - H335		
Hexamethylene diisocyanate, oligomers		30-60%
CAS number: 28182-81-2	EC number: 500-060-2	
Classification	Classification (67/548/EEC or 1999/45/EC)	
Acute Tox. 4 - H332	R43.	
Skin Sens. 1 - H317		
STOT SE 3 - H335		

204/WB101 - ANTI-GRAFFITI CLEAR GLAZE KIT - ACTIVATOR

HEXAMETHYLENE-DI-ISOCYANATE			<1%
CAS number: 822-06-0	EC number: 212-485-8	REACH registration number: 01-2119457571-37-0000	
Classification			
Acute Tox. 4 - H302			
Acute Tox. 1 - H330			
Skin Irrit. 2 - H315			
Eye Irrit. 2 - H319			
Resp. Sens. 1 - H334			
Skin Sens. 1 - H317			
STOT SE 3 - H335			

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Remove soiled, soaked clothing immediately. Remove affected person from source of contamination.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues. Show this sheet to the doctor
Ingestion	Do not induce vomiting. Do not give anything to drink Rinse nose, mouth and throat with water.
Skin contact	Immediately remove contaminated clothing. Wash skin thoroughly with soap and water. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after washing.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after washing. Show this Safety Data Sheet to the medical personnel.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Irritation of nose, throat and airway.
Ingestion	No specific symptoms known.
Skin contact	Skin irritation.
Eye contact	Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations. If in doubt, get medical attention promptly.
-----------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with foam, carbon dioxide, dry powder or water fog.
Unsuitable extinguishing media	Do not use water, if avoidable.

204/WB101 - ANTI-GRAFFITI CLEAR GLAZE KIT - ACTIVATOR

5.2. Special hazards arising from the substance or mixture

Specific hazards Combustible material. Toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting Keep up-wind to avoid fumes. Containers close to fire should be removed or cooled with water. Do not allow water to contact any leaked material.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate.

6.2. Environmental precautions

Environmental precautions Contain spillages using bunding. Avoid the spillage or runoff entering drains, sewers or watercourses.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and place into containers. Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13. Flush contaminated area with plenty of water.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. Collect and dispose of spillage as indicated in Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Mechanical ventilation or local exhaust ventilation may be required. Avoid inhalation of vapours. Avoid spilling. Avoid contact with skin and eyes. Avoid contact with water or humidity. Comply with instructions for use (refer to technical sheet). Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. The Manual Handling Operations Regulations may apply to the handling of containers of this product. To assist employers, the following method of calculating the weight for any pack size is given. Take the pack size volume in litres and multiply this figure by the specific gravity value given in section 9. This will give the net weight of the coating in kilograms. Allowance will then have to be made for the immediate packaging to give an approximate gross weight.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in closed original container at temperatures between 5°C and 25°C. Keep container tightly closed. Keep containers upright. Store away from the following materials: Oxidising materials. Alkalis. Acids.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

Usage description Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible.

204/WB101 - ANTI-GRAFFITI CLEAR GLAZE KIT - ACTIVATOR

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

Hexamethylene diisocyanate oligomers, Isocyanurate

Long-term exposure limit (8-hour TWA): WEL 0.02 ppm Sen

Short-term exposure limit (15-minute): WEL 0.07 ppm Sen
as NCO

Hexamethylene diisocyanate, oligomers

Long-term exposure limit (8-hour TWA): WEL 0.02 ppm Sen

Short-term exposure limit (15-minute): WEL 0.07 ppm Sen

HEXAMETHYLENE-DI-ISOCYANATE

Long-term exposure limit (8-hour TWA): WEL 0,02 mg/m³

Sen

Short-term exposure limit (15-minute): WEL 0,07 mg/m³

as NCO

WEL = Workplace Exposure Limit.

Sen = Capable of causing occupational asthma.

Hexamethylene diisocyanate oligomers, Isocyanurate (CAS: 28182-81-2)

DNEL	Industry - Inhalation; Short term local effects: 1 mg/m ³ Industry - Inhalation; Long term local effects: 0.5 mg/m ³
PNEC	- STP; 38.28 mg/l - Intermittent release; 1.27 mg/l - marine water; 0.0127 mg/l - Sediment; 266700 mg/kg - Soil; 53200 mg/kg

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

No specific ventilation requirements. This product must not be handled in a confined space without adequate ventilation.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. It is recommended that gloves are made of the following material: Nitrile rubber. Barrier cream applied before work may make it easier to clean the skin after exposure, but does not prevent absorption through the skin.

Other skin and body protection

Wear suitable protective clothing as protection against splashing or contamination.

Hygiene measures

No specific hygiene procedures recommended but good personal hygiene practices should always be observed when working with chemical products.

204/WB101 - ANTI-GRAFFITI CLEAR GLAZE KIT - ACTIVATOR

Respiratory protection No specific recommendations. Respiratory protection may be required if excessive airborne contamination occurs.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Clear, yellowish liquid.
Colour	Light (or pale).
Odour	Slight.
Initial boiling point and range	Not measurable (owing to decomposition at > 150°C @ 760 mm Hg)
Flash point	> 120°C OC (Open cup).
Vapour pressure	Hexamethylene-1,6-diisocyanate = 0.014 mbar @ °C
Relative density	approx. 1.14 @ @ 20°C
Solubility(ies)	Miscible with water
Viscosity	approx. 1200 DIN 53019/1 mPas @ 23°C

9.2. Other information

Volatility	zero
Volatile organic compound	This product contains a maximum VOC content of 0 g/litre.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity The following materials may react with the product: Alcohols, glycols. Amines. Bases Protic solvents Water and aqueous solutions with great release of CO₂, and hence risk of a pressure build-up in confined areas, and forms an insoluble solid precipitate.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Not determined.

10.4. Conditions to avoid

Conditions to avoid Avoid contact with water.

10.5. Incompatible materials

Materials to avoid Water, steam, water mixtures.

10.6. Hazardous decomposition products

Hazardous decomposition products Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects No data recorded.

Acute toxicity - inhalation

ATE inhalation (gases ppm) 8,671.18

204/WB101 - ANTI-GRAFFITI CLEAR GLAZE KIT - ACTIVATOR

ATE inhalation (vapours mg/l) 11.03

ATE inhalation (dusts/mists mg/l) 2.89

General information	The product contains small quantities of isocyanate. May cause respiratory allergy. May cause respiratory system irritation.
Inhalation	Vapours may irritate throat/respiratory system. A single exposure may cause the following adverse effects: Coughing. Difficulty in breathing. May cause sensitisation by inhalation.
Ingestion	No harmful effects expected from quantities likely to be ingested by accident.
Skin contact	May cause sensitisation by skin contact.
Eye contact	May cause temporary eye irritation.
Acute and chronic health hazards	Frequent inhalation of vapours, may cause respiratory allergy.
Route of exposure	Inhalation Skin absorption. Ingestion. Skin and/or eye contact.
Medical considerations	Skin disorders and allergies.

SECTION 12: Ecological information

Ecotoxicity The product is not expected to be toxic to aquatic organisms.

12.1. Toxicity

12.2. Persistence and degradability

Persistence and degradability The product is not expected to be biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential The product is not bioaccumulating.

12.4. Mobility in soil

Mobility The product hardens to a solid immobile substance.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects Not determined.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Avoid the spillage or runoff entering drains, sewers or watercourses. Waste is classified as hazardous waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods Empty containers may be disposed of after neutralising any product remaining on the walls of the container with a mixture of water, ammonia and liquid soap.

204/WB101 - ANTI-GRAFFITI CLEAR GLAZE KIT - ACTIVATOR

Waste class When this material, in its liquid state, as supplied, becomes a waste, it is categorised as hazardous waste, with EWC code: 08 05 01 (WASTE ISOCYANANTES). Part-used containers, and not drained and/or rigorously scraped out containers, are categorised as hazardous waste, with EWC code 08 05 01 (WASTE ISOCYANANTES). Ideally this component should be mixed with the appropriate resin base and allowed to react fully producing a solid non hazardous waste. Transferring some, ready to use, mixed Base/Activator to the Activator package and mixing again should ensure that any Activator residue will fully react and harden. The drained and rigorously scraped out container can then be categorised as non-hazardous waste with code 15 01 02(plastic packaging) or 15 01 04 (metal packaging). If mixed with other wastes, the above waste code may not be applicable.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

No information required.

Proper shipping name (ADR/RID) NOT REGULATED

Proper shipping name (IMDG) NOT REGULATED

Proper shipping name (ICAO) NOT REGULATED

14.3. Transport hazard class(es)

No information required.

14.4. Packing group

No information required.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

No information required.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).

204/WB101 - ANTI-GRAFFITI CLEAR GLAZE KIT - ACTIVATOR

EU legislation	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Guidance	Workplace Exposure Limits EH40. CHIP for everyone HSG228. Safety Data Sheets for Substances and Preparations. Approved Classification and Labelling Guide (Sixth edition) L131. Dangerous Substances and Explosive Atmospheres Regulations 2002 [L138]

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

General information	Only trained personnel should use this material.
Revision comments	Issued in new format for Reach compliance in accordance with EC 1272/2008 Issued in accordance with Annex II to REACH, as amended by Commission Regulation (EU) No. 2015/830 Professional use. Unique Formula Identifier (UFI) added Addition of EU supplier information
Issued by	Technical Dept. (P.E.)
Revision date	16/02/2021
Revision	6.2
Supersedes date	23/01/2020
SDS number	10755
SDS status	Approved.
Hazard statements in full	H302 Harmful if swallowed. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H330 Fatal if inhaled. H332 Harmful if inhaled. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation.
Signature	Initials _____

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.