

PRO-LUBE

References: 0402

1. Introduction

A semi-synthetic multi purpose grease with strong adhesive properties and high mechanical strength designed for high speed, high stress applications. Resistant to “fling-off” through centrifugal force.

2. Where to use

On all moving metal parts, to improve slip; to maintain freedom from malfunction and seizure, and on any other metallic components particularly gears, chains, conveyors etc.

3. Where not to use

- Areas of difficult or limited accessibility where conventional low viscosity lubricants (such as Pocket Rocket) will provide superior lubrication and more efficient performance.

4 Benefits

- Long lasting lubrication.
- Resists corrosion.
- High mechanical strength.
- Contains PTFE for improved lubricity.
- Penetrates and thickens.
- Anti-fling properties
- Silicone free.

5. Physical properties. [Lubricant base except where stated]

| | |
|-------------------------------|---|
| Appearance | A turbid, off-white aerosol jet spray with a hydrocarbon odour. |
| pH | Not applicable |
| Specific Gravity | ~0.81 |
| Flammability, as supplied | Extremely Flammable, flash point below -20°C |
| Composition Data, as supplied | A solution of mineral oil, high viscosity synthetic tackifiers and PTFE in an aliphatic hydrocarbon solvent and a hydrocarbon propellant. |
| Service Temperatures | Designed for use at ambient temperature. |

6. Application Details

Shake thoroughly prior to use. Spray directly onto the component from a distance of 15 to 30cm. Allow a couple of minutes for the lubricant to penetrate and thicken.