

Description

A gloss black finish paint for use in high temperature situations. This paint has been formulated for use when elevated temperatures are expected. It can be used on engine blocks, exhaust manifolds, brake drums, wood burning stoves, boiler flue pipes and in many other instances. Based on a silicone modified alkyd, when cured, the resins burn off leaving a heat resistant silicone matrix. A quick drying, gloss finish is the result.

Benefits & Features

- High temperature resistance
- Durable gloss finish
- Use in high temperature automotive situations, and on boilers, stoves etc

Directions for Use

Ensure surface to be painted is free of loose flaking material and is rust and grease free. Shake can for 2 minutes and spray onto surface in light coats with a back and forth motion. Invert can after use and spray to clear nozzle.

Technical Data

Appearance:	Black coloured paint
Odour:	Characteristic paint odour
Contents:	A blend of naphtha and xylene with appropriate colouring pigments propelled by propane/isobutane
Storage:	Below 50°C
Flash Point:	<0°C
Solubility:	Insoluble in water
Temperature Range:	Working temperature up to 650°C

Please Note

This technical data sheet is for general guidance purposes only and may contain information that is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department.

