



Industrial Swingback Step

The ultimate builders step - built to meet the demands of day to day use

Product description

- Reinforced with a patented 7-point connection system and a central steel rod that runs right through the tread.
- Two integrated bucket hooks.
- Treads 85 mm deep for safe standing.
- Smooth, grip-friendly external stile surfaces.
- Stability through slip-resistant plastic end caps.
- High stability thanks to fold-down locking bar on both sides.



to the product



Product features

Anti-splay mechanism: Side locking bar

Coating: natural

Connection between stiles and rungs/stiles: riveted

Load: max. 150 kg

Stile depth: 87 mm

Tread depth: 85 mm

Type of rungs/treads: serrated

Vertical distance between each rung/tread: 218 mm



Hints and special features

Complies with EN 131 Professional.

Product variants

Order number	Base	Number of rungs, incl. platform	Overall base width	Overall length	Stile depth	Stile depth steps/back stay	Vertical ladder height	Working height
49604	0,66 m × 0,43 m	4	0.43 m	0.98 m	40 mm	87mm / 40mm	0.87 m	2.45 m
49605	0,8 m × 0,45 m	5	0.45 m	1.21 m	40 mm	87mm / 40mm	1.08 m	2.65 m
49606	0,95 m × 0,48 m	6	0.48 m	1.44 m	40 mm	87mm / 40mm	1.3 m	2.85 m
49607	1,1 m × 0,5 m	7	0.5 m	1.67 m	40 mm	87mm / 40mm	1.51 m	3.1 m
49608	1,24 m × 0,52 m	8	0.52 m	1.89 m	40 mm	87mm / 40mm	1.73 m	3.25 m
49610	1,53 m × 0,57 m	10	0.57 m	2.36 m	55 mm	87mm / 55mm	2.16 m	3.75 m
49612	1,82 m	12	0.62 m	2.82 m	55 mm	87mm /	2.6 m	4.25 m



Order number	Base	Number of rungs, incl. platform	Overall base width	Overall length	Stile depth	Stile depth steps/back stay	Vertical ladder height	Working height
	× 0,62 m					55mm		