

Reachmaster AGR

Reachmaster™ AGR is a sturdy and easy-to-setup scaffold unit. It replaces diagonal braces with advanced guardrails that can be fitted from one level below to ensure the user can work safely at all times. This means the user no longer has to sit on the platform while fitting the guardrails. And because fewer parts are used, it is not only safer but also quicker to set up.

Product description

- Scaffold dimensions approx.: 1.80 m x 0.72 m.
- 5 different working heights from 4.5 m to 8.5 m.
- The lowest folding unit is ideal for rapid erection and dismantling.
- Minimal space requirement during transport and storage (dimensions when folded only 1.75 m x 0.95 m x 0.20 m).
- Scaffolding category 3 (maximum load of 200 kg/m²) according to DIN EN 1004.
- Advanced guardrail for extra safety and quick assembly/dismantling.
- Robust – Ø 50 mm stiles and rungs.



Product features

Incl. stabilisers: Yes
 Incl. toeboards: Yes
 Platform length: 1.8 m
 Platform width: 0.72 m

Product variants

Order number	Overall height	Platform height	Platform size	Working height
5600011	5.55 m	3.55 m	0,72m x 1,8m	4.55 m
5600012	6.7 m	3.7 m	0,72m x 1,8m	5.7 m
5600013	5.55 m	4.55 m	0,72m x 1,8m	6.55 m
5600014	6.85 m	5.85 m	0,72m x 1,8m	7.85 m
5600015	7.7 m	6.7 m	0,72" x 1,8"	8.7 m