

Skymaster EFAmix X

The Skymaster is strong, sturdy and safely insulated thanks to glass reinforced polyester (GRP) stiles, making it ideal for working with electrical equipment or near electrical hazards.

Product description

- High level of protection provided for working on electrical installations thanks to insulated stiles made from glass-fire-reinforced plastic.
- Aluminium rungs (30 x 30 mm).
- One rigid locking bar.
- High-strength Perlon straps with sewn-in fixing tab to prevent splaying.
- Optimum wrap-around stile guide that encompasses the whole rung.
- Locks safely by means of rung hooks and locking tab.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



Hints and special features

Complies with EN 131 Professional.

Product features

Connection between stiles and rungs/stiles: flanged
 Ladder length as 3-part single ladder: 5.8 m
 Length as 2-part single ladder and as stepladder with push-on section: 4.1 m
 Load: max. 150 kg
 Material: Aluminium / plastic
 Number of rungs: 8
 Number of rungs: 3 x 8
 Overall length, retracted: 2.45 m
 Product type: GRP composite multipurpose ladder, 3 sections
 Stile depth: 73 mm
 Tread depth: 30 mm
 Type of rungs/treads: serrated
 Vertical distance between each rung/tread: 265 mm
 Wide crosspiece: 1 m
 Working height as 3-part single ladder: 6.55 m

Product variants

Order number

GRP41521