

# Skymaster Plus X

The original and still the best! The incredibly versatile Industrial Skymaster is the ladder of choice for professionals.

## Product description

- Upper ladder equipped with top wheel assembly (from size 3 x 8 and above).
- Can be used on steps/stairs (Order Nos. 41526-41522).
- Upper ladder can also be used separately as single ladders for Order Nos. 41526-41522.
- Maximum stability thanks to rigid locking bars on both sides.
- High-strength Perlon straps with sewn-in fixing tab to prevent splaying.
- The horizontal stabiliser bar is fitted with castors for ergonomic transport.
- Optimum wrap-around stile guide that encompasses the whole rung.
- Rung hook and stile guides are bolted in and can therefore be replaced.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.



## Product features

Castors: Rubber  
 Coating: natural  
 Connection between stiles and rungs/stiles: flanged  
 Load: max. 150 kg  
 Material: aluminium  
 Product type: Flanged multipurpose ladder, 3 sections  
 Tread depth: 30 mm  
 Type of rungs/treads: serrated  
 Vertical distance between each rung/tread: 265 mm

## Hints and special features

Optimum stability due to extra-wide horizontal stabiliser bar and two rigid locking bars.  
 Complies with EN 131 Professional.

## Product variants

Order number	Ladder length as 3-part single ladder	Length as 2-part single ladder and as stepladder with push-on section	Number of rungs	Number of rungs	Overall length, retracted	Stile depth	Transport dimensions	Weight	Wide crosspiece	Working height as 3-part single ladder
41526	4.15 m	3 m	6	3 x 6	1.9 m	68 mm	1.890 mm x 520 mm x 170 mm	13.9 kg	0.8 m	4.9 m
41521	5.8 m	4.1 m	8	3 x 8	2.45 m	73 mm	2.452 mm x 490 mm x 200 mm	18.6 kg	1 m	6.55 m
41522	6.9 m	4.95 m	10	3 x 10	3 m	85 mm	3.030 mm x 500 mm x 200 mm	24.4 kg	1.1 m	7.65 m



Order number	Ladder length as 3-part single ladder	Length as 2-part single ladder and as stepladder with push-on section	Number of rungs	Number of rungs	Overall length, retracted	Stile depth	Transport dimensions	Weight	Wide crosspiece	Working height as 3-part single ladder
41523	8.6 m	6.1 m	12	3 × 12	3.55 m	98 mm	3.580 mm × 500 mm × 240 mm	30.2 kg	1.2 m	9.25 m
41524	9.7 m	6.95 m	14	3 × 14	4.15 m	98 mm	4.140 mm × 500 mm × 240 mm	38.5 kg	1.2 m	10.35 m