

Variomaster T

For quick use and safe standing: folds to compact size and is quickly set up.

Product description

- Large-area work platform 0.50 x 1.95 m or 0.60 x 2.50 m.
- Peripheral railing for maximum work safety.
- Simple height adjustment according to the self-locking push-up ladder principle, allowing you to reach different heights with only one work platform.
- Operation of height adjustment by one person.
- Easily collapsible for transport and storage.
- Highly mobile and able to pass through doors when erected and collapsed thanks to rollers (Order No. 53794).
- Extendable stabilisers with sturdy height-adjustable foot plates for stability and for levelling out on uneven ground.
- No ballast weights are required for indoor use.
- Two sizes with height adjustment from 1.25 m to 2.46 m or 1.81 m to 3.58 m platform height.
- Scaffolding category 3 (maximum load of 200 kg/m²) according to DIN EN 1004.



Product features

Guardrail height: 1 m
 Load: max. 300 kg
 Platform length: 2.5 m
 Platform material: Aluminium ribbed plate
 Platform width: 0.6 m
 Tread depth: 30 mm

Product variants

Order number	Footpoint, stabiliser rod extended L x W	Footpoint, stabiliser rod retracted L x W	Overall height	Overall height	Platform height	Transport dimensions	Weight	Width, extended	Width, retracted	Working height	closed length	extended length
53794	1,9m x 2,3 m	0,8m x 2,3 m	=2,31m - 3,52m	2.31 m	1,25m - 2,46m	2.290 mm x 780 mm x 750 mm	92 kg	2.3 m	2.3 m	4.5 m	0.8 m	1.9 m
53795	2,3m x 2,85 m	1,2m x 2,85 m	=2,87m - 4,64m	2.87 m	1,81m - 3,58m	2.850 mm x 1.180 mm x 750 mm	119 kg	2.85 m	2.85 m	5.6 m	1.2 m	2.3 m